

**Exceptional performance
under the most *extreme*
braking conditions...**



Permatex® Ceramic Extreme Brake Parts Lubricant...

**handles *extreme* heat and lasts
throughout the life of the pad.**

This purple, environmentally safe lubricant prevents disc brake squeal and chatter while protecting caliper pins, sleeves, bushings, and pistons against seizing and galling.

The non-silicone, non-petroleum based formula performs under the most adverse braking conditions. With its water and corrosion resistant properties, Permatex® Ceramic Extreme Brake Parts Lubricant is excellent on rolling and sliding surfaces.

- Temperature range -65°F to +2800°F (-54°C to +1538°C)
- Non-melting, 100% synthetic based formula, loaded with ceramic solids
- Lasts longer and easily outperforms ordinary caliper greases and traditional disc brake quiet products
- Prevents long bolt and sleeve seizing and galling
- Compatible with internal/external brake rubber and plastic hardware, including ethylene-propylene rubber

It is available in a 2-pack of 7 gram squeeze pouches (#24124) and an 8 fl. oz. bottle with a convenient, built-in application brush (#24125).

Permatex®

Permatex® Ceramic Extreme Brake Parts Lubricant



Directions For Use

1. Wire brush the caliper housing and anchor plate to remove all dirt and dust.
2. Clean all parts with Permatex® Brake & Parts Cleaners.
3. Apply Permatex® Ceramic Extreme Brake Parts Lubricant to all moving caliper hardware, mating surfaces and steel backing plates of disc brake pads.
4. Lubricant may be applied to the BACKS of brake pads to act as a noise suppressor eliminating caliper brake squeal and chatter. (see above and upper right photos)
5. Any excess grease that squeezes out from the mating surfaces should be removed.

Note: Keep lubricant off pads and rotors.

Suggested Applications:

- Long and short bolts • Sleeve • Bushings
- Outboard pad backing plate • Inboard pad backing plate
- Disc brake calipers • Caliper pins • Pistons



Check out additional brake parts lubricant products from Permatex!

ORDERING INFORMATION

ITEM #	DESCRIPTION	BOX PER CASE	CASE DIMENSIONS	CASE CUBE	GROSS WT. LBS.	UPC PREFIX 686226
24124	Ceramic Extreme Brake Parts Lubricant, (14 g) 2-7 g pouches, carded	6	6.5" D x 9.25" H x 4" W	.17	.65	24124 5
24125	Ceramic Extreme Brake Parts Lubricant, 8 fl. oz. brush-top bottle	6	5.5" D x 5.5" H x 5.62" W	.14	6.02	24125 2
OTHER FINE BRAKE PARTS LUBRICANTS FROM PERMATEX®						
20353	Ultra Disc Brake Caliper Lube, 2 fl. oz. tube with nozzle	6	3.5" D x 6.63" H x 4.75" W	.06	1	20353 3
20356	Ultra Disc Brake Caliper Lube, (14 g) 2-7 g pouches, carded	6	4.87" D x 9.25" H x 6.5" W	.11	.6	20356 4
24110	Ultra Disc Brake Caliper Lube, 8 fl. oz. brush-top bottle	6	8" D x 5.38" H x 5.63" W	.14	2.95	24110 8
24115	Ultra Disc Brake Caliper Lube Hi-Temp Silicone Formula, 8 fl. oz. brush-top bottle	6	8" D x 5.38" H x 5.63" W	.14	4.02	24115 3



Permatex, Inc.
Hartford Square North
10 Columbus Boulevard
Hartford, Connecticut 06106

For technical information or a distributor near you, call toll-free 1-87-PERMATEX (877-376-2839).

Visit our web site at www.permatex.com

Permatex and Design are trademarks of Illinois Tool Works, Inc. © Copyright 2008. ITW Permatex, Inc. All rights reserved. 0803-052 / PX-0323A