

Permatex, Inc.
 10 Columbus Blvd.
 Hartford, CT 06106 USA
 Telephone: 1-87-Permatex
 (877) 376-2839
 Emergency: 800-255-3924
 International Emergency: 813-248-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: SLIK PAK 5TH WHEEL GREASE 350 2OZ
Item No: 01020
Product Type: Lubricant

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	ACGIH; TLV-TWA	OSHA PEL:
LITHIUM-CALCIUM PETROLEUM GREASE BLEND MIXTURE	>60	Not listed	Not Listed
GRAPHITE 7782-42-5	<30	2 mg/m ³ (respir) ACGIH	15 mppcf TWA
MOLYBDENUM DISULFIDE 1317-33-5	<5	10 mg/m ³ (inhalable); 3 mg/m ³ (resp. as insoluble molybdenum)	15 mg/m ³ (as insoluble molybdenum)
SILICA, QUARTZ 14808-60-7	0.1-1.0	0.05 mg/m ³	0.1 mg/m ³ TWA respirable

3. HAZARDS IDENTIFICATION

Toxicity: May cause eye and skin irritation. If ingested, will irritate esophagus and stomach. May irritate respiratory system upon frequent or prolonged use. This product contains encapsulated silicon dioxide (quartz silica). No exposure to free respirable silica is anticipated during normal use of this product. Silica may be released by grinding or machining of coated material. Use NIOSH-approved dust/mist respirator when grinding or machining.

Primary Routes of Entry: Eye and skin contact, ingestion, inhalation

Signs and Symptoms of Exposure: Overexposure may cause eye and skin redness. Ingestion may cause cramps or diarrhea. Based on testing, this product is not likely to be an inhalation hazard and is considered to have a low order of acute toxicity.

Component	Weight%	NTP	ACGIH Carcinogens	IARC
SILICA, QUARTZ 14808-60-7	0.1-1.0		A2 - Suspected Human Carcinogen	Group 1; Monograph 68, 1997

Medical Conditions Recognized as Being Aggravated by Exposure: Preexisting pulmonary and dermatological disorders.

4. FIRST AID MEASURES

Ingestion: Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.

Inhalation: Move to fresh air in case of accidental inhalation of vapours.

Skin Contact: Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point °F(C°): 380°F. COC

Recommended Extinguishing Media: Carbon dioxide, Dry chemical, foam

Special Fire-Fighting Procedures: Use water to cool exposed containers. Water stream directed into fire may cause frothing with subsequent spread of flame. Firefighters should wear self-contained breathing apparatus.

Hazardous Products of Combustion: Oxides of carbon

Unusual Fire/Explosion Hazards: None

5. FIRE FIGHTING MEASURES

Lower Explosive Limit: Not determined.
Upper Explosive Limit: Not determined.

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures: Absorb spill or leak with sand or cloth. Sweep or shovel into an appropriate waste container until disposal.
Prevent from entering waterways or sewers.

7. HANDLING AND STORAGE

Storage: Store away from heat.
Handling: Avoid prolonged skin contact. Keep away from eyes. Wash hands and face after handling this compound.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes: Safety glasses.
Skin: Neoprene or nitrile gloves recommended.
Ventilation: General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.
Respiratory Protection: Not required under normal use. In case of insufficient ventilation, wear suitable respiratory equipment.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Black semi-solid
Odor: Mild petroleum odor
Boiling Point: Not determined.
pH: Does not apply
Solubility in Water: Nil
Specific Gravity: 1.0
VOC Content(Wt.%): None
Vapor Pressure: Not determined
Vapor Density (Air=1): >1 (air = 1)
Evaporation Rate: Negligible

10. STABILITY AND REACTIVITY

Chemical Stability: Stable at normal conditions
Hazardous Polymerization: WILL NOT OCCUR.
Incompatibilities: Strong oxidizers
Conditions to Avoid: Heat
Hazardous Products of Combustion: Oxides of carbon

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Dispose of in accordance with local, state and federal regulations.
US EPA Waste Number: NH - Not a RCRA Hazardous Waste Material

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

Domestic Ground Transport

DOT Shipping Name: Unrestricted
Hazard Class: None
UN/ID Number: None
Marine Pollutant: None

IATA

Proper Shipping Name: Not regulated
Class or Division: None

Product Name: SLIK PAK 5TH WHEEL GREASE 350
2OZ

Item No: 01020

UN/ID Number: None

IMDG

Proper Shipping: Unrestricted
Hazard Class: None
UN Number: None

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

NONE

CALIFORNIA PROP 65:

No California Prop 65 chemicals are known to be present at or above the No Significant Risk Level.

TSCA Inventory Status:

Listed on Inventory: YES All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 1, FLAMMABILITY 1, REACTIVITY 0.

Estimated HMIS Classification: HEALTH 1, FLAMMABILITY 1, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By: Denise Boyd, Manager-Environmental, Health & Safety
Company: Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA 06106

Revision Date: May/14/2008

Revision 5

Number:

Telephone No.: 1-87-Permatex (877) 376-2839