

Permatex, Inc.
 10 Columbus Blvd.
 Hartford, CT 06106 USA
 Telephone: 1-87-Permatex
 (877) 376-2839
 Emergency: 800-255-3924
 International Emergency: 813-348-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: 03346 REARVIEW MIRROR ADHESIVE KIT PART 1
Item No: PTXSA6128D
Product Type: Adhesive

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	Percent	ACGIH 8 Hr. TWA:	OSHA 8 Hr. TWA:
POLYURETHANE METHACRYLATE RESIN MIXTURE	40-50	Not Listed	Not Listed
(METH)ACRYLATE MONOMER MIXTURE	30-40	Not Listed	Not Listed
ACRYLIC ACID 79-10-7	1-10	2 ppm TWA; 5.9 mg/m ³ TWA	10 ppm TWA; 30 mg/m ³ TWA
-DIMETHYLBENZYL HYDROPEROXIDE 80-15-9	1-10	Not Listed	Not Listed
SUBSTITUTED SILANE 2530-85-0	0.1-1.0	Not Listed	Not Listed
SACCHARIN 81-07-2	0.1-1.0	10mg/m ³ nuisance dust	Not Listed
1-ACETYL-2-PHENYLHYDRAZINE 114-83-0	0.1-1.0	Not Listed	Not Listed

3. HAZARDS IDENTIFICATION

Toxicity: May cause eye and skin irritation.
Primary Routes of Entry: Eye and skin contact, ingestion, inhalation.
Signs and Symptoms of Exposure: Repeated skin contact may cause allergic skin reactions. May cause pain, redness or swelling of the eyes and excessive blinking and tear production.

Ingredients	Percent	NTP:	ACGIH Carcinogens	IARC:
ACRYLIC ACID 79-10-7	1-10		A4 - Not Classifiable as a Human Carcinogen	
SACCHARIN 81-07-2	0.1-1.0	Delisted April 2000		Group 3: Vol 73, Page 517: 1999

Medical Conditions Recognized as Being Aggravated by Exposure: Acrylic acid: Upper respiratory and lung diseases, dermatitis.

4. FIRST AID MEASURES

Ingestion: If swallowed, DO NOT induce vomiting. Obtain medical attention immediately.
Inhalation: Move to fresh air in case of accidental inhalation of vapors. Oxygen or artificial respiration if needed.
Skin Contact: Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point (°F/C): More than 200 degrees F. Method: Tag Closed Cup
Recommended Extinguishing Media: Carbon dioxide, Water, dry chemical
Special Fire-Fighting Procedures: Firefighters should wear self-contained breathing apparatus.
Hazardous Products Formed by Fire or Thermal Decomposition: Irritating vapors.

Unusual Fire/Explosion Hazards: None

Lower Explosive Limit: 2.0% Acrylic acid

Upper Explosive Limit: 8.0% Acrylic acid

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures: Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

7. HANDLING AND STORAGE

Storage: Store below 100 degrees F.

Handling: Do not inhale vapors. Avoid prolonged skin contact. Keep away from eyes.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes: Safety glasses.

Skin: rubber or plastic gloves

Ventilation: Provide adequate ventilation

Respiratory Protection: In case of insufficient ventilation, wear suitable respiratory equipment

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Yellow liquid

Odor: irritating

Boiling Point (°F): More than 300 degrees F.

pH: Does not apply

Solubility in Water: Insoluble

Specific Gravity: 1.1 @ 80 degrees F.

VOC Content(Wt.%): Not determined

Vapor Pressure: Not determined

Vapor Density (Air=1): Not Determined

Evaporation Rate: Not Determined

10. STABILITY AND REACTIVITY

Chemical Stability: Stable at normal conditions

Hazardous Polymerization: WILL NOT OCCUR

Incompatibilities: Avoid contact with bases and strong oxidizers.

Conditions to Avoid: Heat

Hazardous Products Formed by Fire or Thermal Decomposition: Irritating vapors.

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations.

US EPA Waste Number: NH - Not a RCRA Hazardous Waste Material

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

Domestic Ground Transport

DOT Shipping Name: Unrestricted

Hazard Class: NONE

UN/ID Number: None

Marine Pollutant: None

IATA

Proper Shipping Name: not regulated

Class or Division: None
UN/NA Number: None

IMDG

Proper Shipping: Unrestricted
Hazard Class: None
UN Number: None

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

SARA 313 Information

ACRYLIC ACID, DIMETHYLBENZYL HYDROPEROXIDE

CALIFORNIA PROP 65:

No California Prop 65 chemicals are known to be present.

TSCA Inventory Status:

Listed on Inventory: **YES** All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 2, FLAMMABILITY 1, REACTIVITY 1

Estimated HMIS Classification: HEALTH 2, FLAMMABILILTY 1, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By: Denise Boyd, Health and Safety Manager
Company: Permatex. Inc. 10 Columbus Blvd. Hartford, CT USA
06106

Revision Date: 02/12/2004

Revision New

Number:

Telephone Number: 1-87-Permatex (877) 376-2839

Permatex, Inc.
 10 Columbus Blvd.
 Hartford, CT 06106 USA
 Telephone: 1-87-Permatex
 (877) 376-2839
 Emergency: 800-255-3924
 International Emergency: 813-348-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: 03346 REARVIEW MIRROR ADHESIVE KIT PART 2
Item No: PTXAS752E
Product Type: Activator

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	Percent	ACGIH 8 Hr. TWA:	OSHA 8 Hr. TWA:
HEPTANE 142-82-5	60-70	400 ppm TWA; 1640 mg/m ³ TWA	500 ppm TWA; 2000 mg/m ³ TWA
PETROLEUM GASES, LIQUEFIED, SWEETENED 68476-86-8	25-35	1000 ppm TWA	Not Listed
ETHANOL 64-17-5	<5	1000 ppm; STEL 1000 ppm	1000 ppm TWA; 1900 mg/m ³ TWA
ORGANO-COPPER COMPOUND 22221-10-9	<1	Cu 0.2 mg/m ³ fume; 1 mg/m ³ dust	Cu 1 mg/m ³ fume; 1 mg/m ³ dust
ORGANO-COPPER COMPOUND 68084-48-0	<1	1 ppm; as Cu dusts or mist	Not Listed
ORGANO-COPPER COMPOUND 85737-14-0	<1	1 ppm; as Cu dust or mist	Not Listed

3. HAZARDS IDENTIFICATION

Toxicity: May cause eye, skin and respiratory irritation. Ingestion may irritate digestive tract and cause nausea, vomiting and diarrhea. Excessive inhalation causes headache, dizziness, nausea, and incoordination.
Primary Routes of Entry: Eye and skin contact, ingestion, inhalation.
Signs and Symptoms of Exposure: Contact with eyes may cause tearing and redness. Excessive accidental exposure may cause headache, dizziness, nausea and mild respiratory irritation. May cause skin irritation.

Ingredients	Percent	NTP:	ACGIH Carcinogens	IARC:
ETHANOL 64-17-5	<5		A4 - Not Classifiable as a Human Carcinogen	Group 1 (drinking alcohol); Vol. 44, pg 35, 1988

Medical Conditions Recognized as Being Aggravated by Exposure: May aggravate preexisting dermatitis. Since this product contain copper compounds, individuals with Wilson's Disease should avoid exposure to this product.

4. FIRST AID MEASURES

Ingestion: If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention.
Inhalation: If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention..
Skin Contact: Remove contaminated clothing. Wash area with soap and water. If irritation persists, seek medical attention.
Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point (°F/C): Flash point not determined. Extremely flammable aerosol per flame extension test.
Recommended Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam.
Special Fire-Fighting Procedures: Firefighters should wear self-contained breathing apparatus. Keep containers cool. Use equipment or shielding required to protect against bursting or venting of containers.
Hazardous Products Formed by Fire or Thermal Decomposition: Oxides of carbon.

Unusual Fire/Explosion Hazards:

Vapors may travel from container toward sources of ignition and flashback. Contents under pressure. Closed containers may rupture or explode when exposed to extreme heat. Keep containers cool. Do not puncture or incinerate container.

Lower Explosive Limit:

Not determined

Upper Explosive Limit:

Not determined

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures:

Eliminate all sources of ignition. Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

7. HANDLING AND STORAGE

Storage:

Store away from heat, sparks or open flame. Do not store at temperatures above 120 degrees F.

Handling:

Avoid contact with skin and eyes. Do not inhale vapors. Do not use near heat, sparks or open flame.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes:

Safety glasses or goggles.

Skin:

Rubber or plastic gloves

Ventilation:

General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits during the use of this product.

Respiratory Protection:

An approved respirator (i.e. NIOSH, etc.) should be worn when exposures are expected to exceed the applicable limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

Green liquid

Odor:

SWEET, ETHEREAL

Boiling Point (°F):

Not determined

pH:

Does not apply

Solubility in Water:

Soluble

Specific Gravity:

0.66

VOC Content(Wt.%):

<98% by weight

Vapor Pressure:

40-80 psig @ 70 degrees F.

Vapor Density (Air=1):

Heavier than air

Evaporation Rate:

<1 (ethyl ether = 1)

10. STABILITY AND REACTIVITY

Chemical Stability:

Stable at normal conditions

Hazardous Polymerization:

WILL NOT OCCUR

Incompatibilities:

Strong oxidizers.

Conditions to Avoid:

High temperatures.

Hazardous Products Formed by Fire or Thermal

Oxides of carbon.

Decomposition:

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations. This container may be recycled in aerosol recycling centers. Before offering for recycling, empty the can by using the product according to the label. If recycling is not available, wrap the container and discard in the trash.

US EPA Waste Number:

D001 as per 40CFR 261.21

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

Domestic Ground Transport

DOT Shipping Name:

Consumer Commodity (not more than one liter)

Hazard Class: ORM-D
UN/ID Number: None
Marine Pollutant: None

IATA

Proper Shipping Name: Consumer Commodity (Not more than 500 ml)
Class or Division: Class 9
UN/NA Number: ID 8000

IMDG

Proper Shipping: Aerosols, Limited Quantity
Hazard Class: Class 2.1
UN Number: UN 1950

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

SARA 313 Information
COPPER COMPOUND

CALIFORNIA PROP 65:
No California Prop 65 chemicals are known to be present.

TSCA Inventory Status:
Listed on Inventory: **YES** All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 1, FLAMMABILITY 4, REACTIVITY 0
Estimated HMIS Classification: HEALTH 1, FLAMMABILITY 4, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.
HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By: Denise Boyd, Health and Safety Manager
Company: Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA
06106

Revision Date: 12/16/2003
Revision 0
Number:

Telephone Number: 1-87-Permatex (877) 376-2839