

Permatex, Inc.
10 Columbus Blvd.
Hartford, CT 06106 USA
Telephone: 1-87-Permatex
(877) 376-2839
Emergency: 800-255-3924
International Emergency: 813-248-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: HEADLIGHT RESTORATION KIT - PLASTIC CLEANER 1 FL.OZ
Item No: 09135
Product Type: Cleaner

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	Weight Percent	ACGIH TLV:	OSHA PEL:
WATER 7732-18-5	60-70	Not Listed	Not Listed
STODDARD SOLVENT 8052-41-3	15-25	100 ppm TWA	500 ppm TWA; 2900 mg/m ³ TWA
CALCIUM CARBONATE 471-34-1	1-10	10 mg/m ³ particulate TWA	Not Listed

3. HAZARDS IDENTIFICATION

Toxicity: May cause eye, skin and respiratory irritation. Aspiration hazard if swallowed.
Primary Routes of Entry: Eye and skin contact, ingestion, inhalation
Signs and Symptoms of Exposure: Excessive overexposure may cause giddiness, dizziness, headache, nausea and in extreme cases, unconsciousness and respiratory depression. Inhaling may cause mild irritation to the nose, throat and respiratory tract and may result in central nervous system (CNS) depression. Overexposure may cause eye and skin redness. Swallowing: This material can enter the lungs during swallowing or vomiting and cause lung inflammation and/or damage. Aspiration into the lungs can cause chemical pneumonia which can be fatal.

Medical Conditions Recognized as Being Aggravated by Exposure: Preexisting eye, skin and respiratory disorders may be aggravated by overexposure to this product.

4. FIRST AID MEASURES

Ingestion: Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation: Move to fresh air in case of accidental inhalation of vapors. Oxygen or artificial respiration if needed. Obtain medical attention.
Skin Contact: Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point (°F/C): 112 degrees F. Method: Setaflash Closed Cup
Recommended Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam.
Special Fire-Fighting Procedures: Firefighters should wear self-contained breathing apparatus.
Hazardous Products of Combustion: Irritating vapors, oxides of carbon and nitrogen, AVOID extreme heat
Unusual Fire/Explosion Hazards: Closed containers may rupture or explode when exposed to extreme heat.

Lower Explosive Limit: 1
Upper Explosive Limit: 12

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures: Eliminate all sources of ignition. Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

7. HANDLING AND STORAGE

Storage: Store away from heat, sparks or open flame. Do not store at temperatures above 120 degrees F.

7. HANDLING AND STORAGE

Handling: Avoid prolonged skin contact. Keep away from eyes. Do not inhale vapors. Do not use near heat, sparks or open flame.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes: Safety glasses
Skin: Rubber or plastic gloves.
Ventilation: General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.
Respiratory Protection: An approved respirator (i.e. NIOSH, etc.) should be worn when exposures are expected to exceed the applicable limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: White liquid
Odor: Petroleum Odor
Boiling Point: >212 degrees F.
pH: 9
Solubility in Water: Miscible
Specific Gravity: 0.99
VOC Content(Wt.%): 21% by weight
Vapor Pressure: 3 mm Hg @ 68 degrees F.
Vapor Density (Air=1): 4.7
Evaporation Rate: <1 (air = 1)

10. STABILITY AND REACTIVITY

Chemical Stability: Stable at normal conditions
Hazardous Polymerization: Will not occur.
Incompatibilities: Strong oxidizers
Conditions to Avoid: Keep away from heat, sparks and open flame
Hazardous Products of Combustion: Irritating vapors, oxides of carbon and nitrogen, AVOID extreme heat

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations.
US EPA Waste Number: D001 as per 40CFR 261.21

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

Domestic Ground Transport

DOT Shipping Name: Unrestricted
Hazard Class: None
UN/ID Number: None
Marine Pollutant: None

IATA

Proper Shipping Name: Consumer Commodity (Not more than 1 liter)
Class or Division: Class 9
UN/NA Number: ID 8000

IMDG

Proper Shipping: Petroleum Distillates, n.o.s., Limited Quantity
Hazard Class: Class 3 PGIII
UN Number: UN 1268

Product Name: HEADLIGHT RESTORATION KIT -
PLASTIC CLEANER 1 FL.OZ

Item No: 09135

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

NONE

CALIFORNIA PROP 65:

No California Prop 65 chemicals are known to be present at or above the No Significant Risk Level.

TSCA Inventory Status:

Listed on Inventory: YES All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 2, FLAMMABILITY 2, REACTIVITY 1

Estimated HMIS Classification: HEALTH 2, FLAMMABILITY 2, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By: Denise Boyd, Health and Safety Manager
Company: Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA 06106

Revision Date: January/31/2007

Revision 3

Number: