

Permatex, Inc.
10 Columbus Blvd.
Hartford, CT 06106 USA
Telephone: 1-87-Permatex
(877) 376-2839
Emergency: 800-255-3924 (ChemTel)
International Emergency: +01-813-248-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: CERAMIC EXTREME BRAKE PARTS LUBRICANT 7 GR. 2-PK
Item No: 24124
Product Type: Lubricant

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	ACGIH; TLV-TWA	OSHA PEL
SYNTHETIC BASE OILS (TRADE SECRET)	>90	Not listed	Not listed

3. HAZARDS IDENTIFICATION

Toxicity: May cause eye and skin irritation.
Primary Routes of Entry: Eye and skin contact, ingestion, inhalation
Signs and Symptoms of Exposure: Overexposure may cause eye and skin redness.

Medical Conditions Recognized as Being Aggravated by Exposure: Preexisting skin disorders.

4. FIRST AID MEASURES

Ingestion: If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention.
Inhalation: Move to fresh air in case of accidental inhalation of vapours. Get medical attention/advice if you feel unwell.
Skin Contact: Remove contaminated clothing. Wash area with soap and water. If irritation persists, seek medical attention.
Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point °F(C°): >500°F COC
Recommended Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam.
Special Fire-Fighting Procedures: Treat as oil fire. Firefighters should wear self-contained breathing apparatus.
Hazardous Products of Combustion: Oxides of carbon
Unusual Fire/Explosion Hazards: None.
Lower Explosive Limit: Not determined.
Upper Explosive Limit: Not determined.

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures: Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

7. HANDLING AND STORAGE

Storage: Store away from heat.
Handling: Avoid contact with skin and eyes. Wash thoroughly after handling. Product may cause surfaces to become slippery.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes: Safety glasses.
Skin: Neoprene or nitrile gloves recommended.
Ventilation: General ventilation is usually adequate.
Respiratory Protection: Not normally necessary.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Purple semi-solid
Odor:	Mild
Boiling Point:	Not determined.
pH:	Does not apply
Solubility in Water:	Insoluble
Specific Gravity:	0.94
VOC(Wt.%):	None
Vapor Pressure:	Not Determined
Vapor Density (Air=1):	> 1 (air = 1)
Evaporation Rate:	<1 (butyl acetate = 1)

10. STABILITY AND REACTIVITY

Chemical Stability:	Stable at normal conditions
Hazardous Polymerization:	Will not occur
Incompatibilities:	Strong oxidizers
Conditions to Avoid:	Welding.
Hazardous Products of Combustion:	Oxides of carbon

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal:	Disposal should be made in accordance with federal, state and local regulations.
US EPA Waste Number:	NH - Not a RCRA Hazardous Waste Material

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

Ground Transport (DOT)

DOT Shipping Name:	Not regulated
Hazard Class:	None
UN/ID Number:	None

IATA

Proper Shipping Name:	Not regulated
Class or Division:	None
UN/ID Number:	None

IMDG

Proper Shipping:	Not regulated
Hazard Class:	None
UN Number:	None

Marine Pollutant: None

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

NONE

California Proposition 65: No California Prop 65 chemicals are known to be present.

TSCA Inventory Status: All components of this product are listed (or exempt) on the EPA TSCA inventory.

Product Name: CERAMIC EXTREME BRAKE PARTS
LUBRICANT 7 GR. 2-PK

Item No: 24124

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 1, FLAMMABILITY 1 REACTIVITY 1.

Estimated HMIS Classification: HEALTH 1, FLAMMABILITY 1, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By: Denise Boyd, Manager-Environmental, Health & Safety
Company: Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA 06106

Revision Date: May 11, 2011

Revision 3

Number:

Telephone No.: 1-87-Permatex (877) 376-2839