

Permatex, Inc.  
 10 Columbus Blvd.  
 Hartford, CT 06106 USA  
 Telephone: 1-87-Permatex  
 (877) 376-2839  
 Emergency: 800-255-3924  
 International Emergency: 813-248-0585

## Material Safety Data Sheet

### 1. PRODUCT IDENTIFICATION

**Product Name:** PIT CREWS CHOICE 20Z TB CG  
**Item No:** 25831  
**Product Type:** Sealant

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	Weight Percent	ACGIH TLV:	OSHA PEL:
ACRYLIC POLYMER MIXTURE	>50	Not Listed	Not Listed
WATER 7732-18-5	>35	Not Listed	Not Listed
ETHANOL 64-17-5	<5	1000 ppm; STEL 1000 ppm	1000 ppm TWA; 1900 mg/m <sup>3</sup> TWA
ESTER ALCOHOL 25265-77-4	<5	Not Listed	Not Listed

### 3. HAZARDS IDENTIFICATION

**Toxicity:** May cause eye, skin and respiratory irritation. Ingestion of ethyl alcohol may cause dizziness, faintness, drowsiness, decreased awareness, depression, euphoria, abdominal discomfort, nausea, vomiting, lack of coordination and coma. Inhalation of high concentrations may cause irritation of respiratory tract. Prolonged or repeated skin contact may cause drying or defatting of skin..

**Primary Routes of Entry:** Eye and skin contact, ingestion, inhalation

**Signs and Symptoms of Exposure:** Excessive overexposure may cause giddiness, dizziness, headache, nausea and in extreme cases, unconsciousness and respiratory depression. Overexposure may cause eye and skin redness.

Ingredient	Weight Percent	NTP	ACGIH Carcinogens	IARC
ETHANOL 64-17-5	<5		A4 - Not Classifiable as a Human Carcinogen	Group 1 (drinking alcohol); Vol. 44, pg 35, 1988

**Medical Conditions Recognized as Being Aggravated by Exposure:** Preexisting pulmonary and dermatological disorders.

### 4. FIRST AID MEASURES

**Ingestion:** If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention.

**Inhalation:** If not breathing, give artificial respiration. Oxygen or artificial respiration if needed. Obtain medical attention.

**Skin Contact:** Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

**Eye Contact:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

### 5. FIRE FIGHTING MEASURES

**Flash Point (°F/C):** >200° F

**Recommended Extinguishing Media:** Carbon Dioxide, Dry Chemicals, Foam.

**Special Fire-Fighting Procedures:** Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool.

**Hazardous Products of Combustion:** Acrylic monomers, ammonia, oxides of carbon.

**Unusual Fire/Explosion Hazards:** Material may flash above 200 degrees F. Polymer film may burn.

**Lower Explosive Limit:** 3.3 Ethyl alcohol

**Upper Explosive Limit:** 19.0 Ethyl alcohol

**6. ACCIDENTAL RELEASE MEASURES**

**Spill Procedures:** Scrape up putty and place in an appropriate waste container for disposal.

**7. HANDLING AND STORAGE**

**Storage:** Store below 100 degrees F. Do not allow freezing.  
**Handling:** Avoid contact with skin and eyes. Do not inhale vapors.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Eyes:** Safety glasses  
**Skin:** Neoprene or nitrile gloves recommended.  
**Ventilation:** General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.  
**Respiratory Protection:** Not required under normal use. An approved respirator (i.e. NIOSH, etc.) should be worn when exposures are expected to exceed the applicable limits.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Appearance:** White thixotropic paste  
**Odor:** AMMONIA  
**Boiling Point:** 212°F  
**pH:** 7.3  
**Solubility in Water:** SOLUBLE  
**Specific Gravity:** 1.05  
**VOC Content(Wt.%):** 4.8% by weight  
**Vapor Pressure:** Approximately 20 mm Hg  
**Vapor Density (Air=1):** Heavier than air  
**Evaporation Rate:** Slower than ether

**10. STABILITY AND REACTIVITY**

**Chemical Stability:** Stable at normal conditions  
**Hazardous Polymerization:** WILL NOT OCCUR.  
**Incompatibilities:** Acids, Oxidizing agents.  
**Conditions to Avoid:** Heat  
**Hazardous Products of Combustion:** Acrylic monomers, ammonia, oxides of carbon.

**11. TOXICOLOGICAL INFORMATION**

See Section 3

**12. ECOLOGICAL INFORMATION**

No data available

**13. DISPOSAL CONSIDERATIONS**

**Recommended Method of Disposal:** Disposal should be made in accordance with federal, state and local regulations.  
**US EPA Waste Number:** NH - Not a RCRA Hazardous Waste Material

**14. TRANSPORTATION INFORMATION**

**DOT (49CFR 172)**

**Domestic Ground Transport**

**DOT Shipping Name:** Unrestricted  
**Hazard Class:** None  
**UN/ID Number:** None  
**Marine Pollutant:** None

**IATA**

**Proper Shipping Name:** Not regulated  
**Class or Division:** None  
**UN/NA Number:** None

**IMDG**

**Proper Shipping:** Unrestricted  
**Hazard Class:** None

**UN Number:** None

**15. REGULATORY INFORMATION**

**SARA 313 Chemicals:** The following component(s) is listed as a SARA Section 313 Toxic Chemical.

NONE

**CALIFORNIA PROP 65:**

No California Prop 65 chemicals are known to be present.

**TSCA Inventory Status:**

**Listed on Inventory:** YES All components of this product are listed (or exempt) on the EPA TSCA inventory.

**16. OTHER INFORMATION**

**Estimated NFPA Rating:** HEALTH 1, FLAMMABILITY 1, REACTIVITY 0

**Estimated HMIS Classification:** HEALTH 1, FLAMMABILITY 1, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

**Prepared By:** Denise Boyd, Health and Safety Manager  
**Company:** Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA 06106

**Revision Date:** January/11/2007  
**Revision Number:** 2