

Permatex, Inc.
10 Columbus Blvd.
Hartford, CT 06106 USA
Telephone: 1-87-Permatex
(877) 376-2839
Emergency: 800-255-3924

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: SURFACE INSENSITIVE INSTANT ADHESIVE 1LB
Item No: 41661
Product Type: Cyanoacrylate ester

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	Percent	ACGIH 8 Hr. TWA:	OSHA 8 Hr. TWA:
ALKYL CYANOACRYLATE 7085-85-0	90-100	0.2 ppm TWA	Not Listed
HYDROQUINONE 123-31-9	0.1-1.0	2 mg/m ³ TWA	2 mg/m ³ TWA
POLY (METHYL METHACRYLATE) 9011-14-7	1-10	Not Listed	Not Listed

3. HAZARDS IDENTIFICATION

Toxicity: Skin contact may cause burns. Bonds skin rapidly and strongly. Causes eye irritation. Irritates mucous membranes.
Primary Routes of Entry: Eye and skin contact, ingestion, inhalation.
Signs and Symptoms of Exposure: Vapor is irritating to eyes and mucous membranes above TLV. Prolonged and repeated overexposure to vapors may produce symptoms of non-allergic asthma in sensitive individuals.

Ingredients	Percent	NTP:	ACGIH Carcinogens	IARC:
HYDROQUINONE 123-31-9	0.1-1.0		Group A3	Group 3; Vol. 71, pg 691, 1999
POLY (METHYL METHACRYLATE) 9011-14-7	1-10			Group 3 Vol. 19, pg 187; 1979

Medical Conditions Recognized as Being Aggravated by Exposure: None known

4. FIRST AID MEASURES

Ingestion: Ingestion is not likely. The adhesive solidifies and adheres in the mouth. If lips are accidentally stuck together, apply lots of warm water to the lips and encourage maximum wetting and pressure from saliva inside the mouth. Peel or roll lips apart. Do not try to pull the lips with direct opposing action. Saliva will lift the adhesive in one half to two days.

Inhalation: Move to fresh air in case of accidental inhalation of vapors. Oxygen or artificial respiration if needed. Obtain medical attention.

Skin Contact: Remove excess adhesive. Soak in warm, soapy water. The adhesive will come loose from the skin in several hours. Cured adhesive does not present a health hazard even when bonded to the skin. For skin adhesion, first immerse the bonded surfaces in warm, soapy water. Peel or roll the surfaces apart with the aid of a blunt edge, e.g., spatula or teaspoon handle; then remove adhesive from the skin with soap and water. Do not try to pull surfaces apart with a direct opposing action. Cyanoacrylates give off heat on solidification. In rare cases, a large drop will increase in temperature enough to cause a burn. Burns should be treated normally after the lump of cyanoacrylate is released from the tissue as described above.

Eye Contact: In the event that eyelids are stuck together or bonded to the eyeball, wash thoroughly with warm water and apply a gauze patch. The eye will open without further action, typically in 1-4 days. There will be no residual damage. Do not try to open the eyes by manipulation. If cyanoacrylate is introduced into the eyes, it will attach to the eye protein and will disassociate from it over intermittent periods, generally several hours. This will cause periods of weeping until clearance is achieved. During this period, double vision may be experienced together with a lachrymatory effect, and it is important to understand the cause and realize that disassociation will normally occur within a matter of hours, even with gross contamination.

5. FIRE FIGHTING MEASURES

Flash Point (°F/C): 185 degrees F. Method: Tag Closed Cup
Recommended Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam.

Special Fire-Fighting Procedures: Firefighters should wear self-contained breathing apparatus.
Hazardous Products Formed by Fire or Thermal Decomposition: Irritating vapors.
Unusual Fire/Explosion Hazards: May polymerize exothermically.

Lower Explosive Limit: Not determined.
Upper Explosive Limit: Not determined.

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures: Flood with water to polymerize. Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

7. HANDLING AND STORAGE

Storage: Store below 75 degrees F.
Handling: Avoid contact with skin and eyes. Do not inhale vapors. Keep container closed when not in use. Wash hands before eating and smoking.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes: Safety glasses.
Skin: Polyethylene or rubber gloves Do not use cotton.
Ventilation: Positive down-draft exhaust ventilation should be provided to maintain vapor concentrations below TLV.
Respiratory Protection: Not normally necessary. An approved respirator (i.e. NIOSH, etc.) should be worn when exposures are expected to exceed the applicable limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear liquid
Odor: irritating
Boiling Point (°F): More than 300 degrees F.
pH: Does not apply
Solubility in Water: Polymerized
Specific Gravity: 1.08 @ 75 degrees F.
VOC Content(Wt.%): <20 g/l (California SCAQMD Method 316B)
Vapor Pressure: Less than 0.2 mm Hg @ 75 degrees F.
Vapor Density (Air=1): Approximately 3
Evaporation Rate: Not Determined

10. STABILITY AND REACTIVITY

Chemical Stability: Stable at normal conditions
Hazardous Polymerization: MAY OCCUR Hazardous polymerization may occur if over-catalyzed or insufficiently aerated after catalyzation. This polymerization is exothermic.
Incompatibilities: Polymerized by contact with water, alcohols, amines or alkalies.
Conditions to Avoid: Avoid contact with clothes, fabrics, rags or tissue. Contact with these material may cause polymerization.
Hazardous Products Formed by Fire or Thermal Decomposition: Irritating vapors.

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations.
US EPA Waste Number: NH - Not a RCRA Hazardous Waste Material

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

Product name: SURFACE INSENSITIVE INSTANT
ADHESIVE 1LB

Item 41661

Domestic Ground Transport

DOT Shipping Name: Unrestricted
Hazard Class: NONE
UN/ID Number: None
Marine Pollutant: None

IATA

Proper Shipping Name: not regulated
Class or Division: None
UN/NA Number: None

IMDG

Proper Shipping: Unrestricted
Hazard Class: None
UN Number: None

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

SARA 313 Information

NONE

CALIFORNIA PROP 65:

No California Prop 65 chemicals are known to be present.

TSCA Inventory Status:

Listed on Inventory: **YES** All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 2, FLAMMABILITY 2, REACTIVITY 1
Estimated HMIS Classification: HEALTH 2, FLAMMABILITY 2, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By: Denise Boyd, Health and Safety Manager
Company: Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA
06106

Revision Date: 06/17/2004

Revision New

Number:

Telephone Number: 1-87-Permatex (877) 376-2839