

Permatex, Inc.
 10 Columbus Blvd.
 Hartford, CT 06106 USA
 Telephone: 1-87-Permatex
 (877) 376-2839
 Emergency: 800-255-3924
 International Emergency: +01-813-248-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: 133AR ANTI-SEIZE LUBRICANT 1OZ
Item No: 81343
Product Type: Lubricant

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	ACGIH; TLV-TWA	OSHA PEL
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC 64742-52-5	20-40	Not listed	Not listed
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC 64742-53-6	20-40	5 mg/m ³ TWA ACGIH	Not listed
CALCIUM OXIDE 1305-78-8	15-25	2 mg/m ³	5 mg/m ³
ALUMINIUM POWDER 7429-90-5	<10	1 mg/m ³	15 mg/m ³
GRAPHITE 7782-42-5	<10	2 mg/m ³	15 mppcf
MINERAL OIL 64741-44-2	<5	5 mg/m ³	Not listed

3. HAZARDS IDENTIFICATION

Toxicity: May cause eye and skin irritation. May cause nose, throat and respiratory irritation. May cause gastrointestinal irritation. High concentrations may cause central nervous system (CNS) depression.

Primary Routes of Entry: Eye and skin contact, ingestion, inhalation

Signs and Symptoms of Exposure: Overexposure may cause eye and skin redness, difficulty breathing and vomiting. Excessive accidental exposure may cause headache, dizziness, nausea and mild respiratory irritation. Inhalation of dust at levels above recommended exposure limit may cause metallic or sweet taste, irritation of pharynx and possible ulceration with perforation of the nasal septum.

Medical Conditions Recognized as Being Aggravated by Exposure: Persons with respiratory problems such as emphysema and asthma should avoid inhalation. Since this product contain copper compounds, individuals with Wilson's Disease should avoid exposure to this product.

4. FIRST AID MEASURES

Ingestion: Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.

Inhalation: Move to fresh air in case of accidental inhalation of vapours. If symptoms persist, call a physician.

Skin Contact: Wash off with soap and water. If skin irritation persists, call a physician.

Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point °F(C°): >200° F TCC

Recommended Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam.

Special Fire-Fighting Procedures: Firefighters should wear self-contained breathing apparatus. Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool.

Hazardous Products of Combustion: Oxides of carbon, Metal oxide fumes

Unusual Fire/Explosion Hazards: May ignite when sufficient heat is applied.

5. FIRE FIGHTING MEASURES

Lower Explosive Limit: 30% aluminum metal; 1% oil
Upper Explosive Limit: 7% oil

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures: Eliminate all sources of ignition. Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

7. HANDLING AND STORAGE

Storage: Store away from heat, sparks or open flame. Do not store at temperatures above 100°F (38°C).
Handling: Avoid prolonged skin contact. Keep away from eyes. Do not inhale vapors. Do not use near heat, sparks or open flame. Wash hands and face after handling this compound.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes: Safety glasses.
Skin: Neoprene or nitrile gloves recommended.
Ventilation: General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.
Respiratory Protection: An approved organic vapor respirator should be worn when exposures are expected to exceed the applicable limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Silver paste
Odor: Petroleum distillates
Boiling Point: Not determined
pH: Does not apply
Solubility in Water: Nil
Specific Gravity: 1.17
VOC(Wt.%): None
Vapor Pressure: <5 mm Hg
Vapor Density (Air=1): <1
Evaporation Rate: <1 (butyl acetate = 1)

10. STABILITY AND REACTIVITY

Chemical Stability: Stable at normal conditions
Hazardous Polymerization: Will not occur.
Incompatibilities: Strong oxidizers, alkalis, mineral acids, selected amines.
Conditions to Avoid: Heat.
Hazardous Products of Combustion: Oxides of carbon, Metal oxide fumes

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations..
US EPA Waste Number: NH - Not a RCRA Hazardous Waste Material

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

Ground Transport (DOT)

DOT Shipping Name: Not Regulated
Hazard Class: None
UN/ID Number: None

IATA

Proper Shipping Name: Not regulated
Class or Division: None

14. TRANSPORTATION INFORMATION

UN/ID Number: None

IMDG

Proper Shipping: Not regulated

Hazard Class: None

UN Number: None

Marine Pollutant: None

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

NONE

California Proposition 65: No California Prop 65 chemicals are known to be present at or above the No Significant Risk Level

TSCA Inventory Status: All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 1, FLAMMABILITY 1 REACTIVITY 1 .

Estimated HMIS Classification: HEALTH 1, FLAMMABILITY 1, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By: Denise Boyd, Manager-Environmental, Health & Safety
Company: Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA 06106

Revision Date: April 28, 2009

Revision 2

Number:

Telephone No.: 1-87-Permatex (877) 376-2839