



Toll Free: 87 PERMATEX
(877-376-2839)

10 Columbus Blvd., Hartford,
Connecticut 06106

6875 Parkland Boulevard, Solon
Ohio 44139

Technical Data Sheet

NOS[®] Octane Booster Racing Formula

AAM Revised 02/09

PRODUCT DESCRIPTION

NOS[®] Racing Formula Octane Booster was designed for racing use only. It was developed to increase octane effect ratings as much 60 points or 6 full octane numbers. It is formulated to eliminate the pre-ignition (pinging) common to lower octane gasoline, and helps in all situations from pulling a load up a steep grade to racing with nitrous oxide at the track. Contains MMT with powertane and nitromethane.

PRODUCT BENEFITS

- Safe for oxygen sensors and catalytic converters
- Increases octane effect of unleaded gasoline 7 points
- Cleans fuel injectors and combustion chamber
- Excellent as a lead substitute
- Reduces hydrocarbon and carbon monoxide emissions
- Provides corrosion protection
- Improves fuel efficiency
- Prevents valve sticking
- Eliminates engine knocking and pinging
- Restores lost horsepower
- Prevents stalling and hesitation
- Water suppressant properties

TYPICAL APPLICATIONS

- Recommended for racing engines including carbureted, fuel injected, turbo and super-charged
- Excellent smoke suppressant for 2 cycle engines
- Recommended for high-performance engines plus marine, industrial, lawn, farm and recreational vehicles

NOTE: NOT recommended for use on diesel engines of any type

DIRECTIONS FOR USE

1. Remove child resistant cap and puncture foil seal with a sharp object. Screw the supplied fuel adapter onto the bottle.
2. Add the contents of the bottle to at least 16 gallons of gasoline. If spilled onto painted surface, wipe off immediately.
3. Replace cap after use and dispose of bottle, fuel adapter and contaminated rags or towels in accordance with federal, state and local regulations.
4. Never expose liquid product to direct or indirect sunlight.

NOTE: NOT LEGAL FOR STREET USE

For Cleanup

1. Wipe off any spilled fluid with a dry cloth.
2. Clean hands with Permatex[®] Fast Orange[®] hand cleaner or soap and water.

PHYSICAL PROPERTIES

	Typical Value
Chemical Type	Hydrocarbon blend, special additives
Appearance	Pale liquid
Odor	Slight hydrocarbon odor

GENERAL INFORMATION

This product is not recommended for use in pure oxygen and/or oxygen rich systems.

For safe handling information on this product, consult the Material Safety Data Sheet, (MSDS).

ORDERING INFORMATION

Part Number	Container Size
12010	12 fl. oz. bottle, boxed

STORAGE

Products shall be ideally stored in a cool, dry location in unopened containers at a temperature between 8° and 28°C (46° and 82°F) unless otherwise labeled. Optimal storage is at the lower half of this temperature range. To prevent contamination of unused product, do not return any material to its original container.

NOTE

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. **Permatex, Inc. specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Permatex, Inc. products and disclaims any liability for consequential or incidental damages of any kind, including lost profits.** This product may be covered by one or more United States or foreign patents or patent applications.

NOT FOR PRODUCT SPECIFICATIONS.
THE TECHNICAL DATA CONTAINED HEREIN ARE INTENDED AS REFERENCE ONLY.
PLEASE CONTACT PERMATEX, INC., TECHNICAL SERVICE DEPARTMENT FOR ASSISTANCE AND RECOMMENDATIONS FOR YOUR SPECIFIC APPLICATION.
PERMATEX, INC., HARTFORD SQUARE NORTH, 10 COLUMBUS BOULEVARD, HARTFORD, CT 06106 PHONE - (1-87)PERMATEX