



Toll Free: 87 PERMATEX  
(877-376-2839)

10 Columbus Blvd., Hartford,  
Connecticut 06106

6875 Parkland Boulevard, Solon  
Ohio 44139

## Technical Data Sheet

# NOS® Complete Fuel System Cleaner

AAM Revised 02/08

### PRODUCT DESCRIPTION

NOS® Complete Fuel System Cleaner is designed for performance cleaning for fuel injected and carbureted engines. It eliminates knocks and pings while improving acceleration. The Complete Fuel System Cleaner is a heavy-duty cleaner designed for use only twice a year or every 6000 miles.

### PRODUCT BENEFITS

- Cleans the entire fuel system - from tank to combustion chambers
- Prevents new deposits from forming
- Will not harm oxygen sensors and catalytic converters
- Reduces hydrocarbon and carbon monoxide emissions
- Improves fuel efficiency
- Meets CRC carburetor clean-up test
- Prevents valve sticking
- Restores lost horsepower
- Prevents stalling and hesitation

### TYPICAL APPLICATIONS

- All fuel injected engines
- All carbureted engines
- Recommended treatment every 6000 miles

Note: NOT recommended for use in diesel engines of any type

### DIRECTIONS FOR USE

Add to no less than 16 gallons of gasoline.

1. Remove child resistant cap and puncture foil seal with a sharp object.
2. Add the contents of the bottle to at least 16 gallons of gasoline. If spilled onto painted surface, wipe off immediately.
3. Replace cap after use and dispose of bottle and any contaminated rags or towels in accordance with all federal, state and local regulations.
4. For continued fuel system cleanup, repeat treatment every 6000 miles

### For Clean-up

1. Wipe off any spilled fluid with a dry cloth.
2. Clean hands with Permatex® Fast Orange® hand cleaner or soap and water.

### PHYSICAL PROPERTIES

Chemical Type

#### Typical Value

Hydrocarbon blend, special additives  
Pale liquid  
Slight hydrocarbon odor

Appearance  
Odor

### GENERAL INFORMATION

**This product is not recommended for use in pure oxygen and/or oxygen rich systems.**

**For safe handling information on this product, consult the Material Safety Data Sheet, (MSDS).**

### ORDERING INFORMATION

Part Number	Container Size
12203	16 Fl. Oz. bottle

### STORAGE

Products shall be ideally stored in a cool, dry location in unopened containers at a temperature between 8° and 28°C (46° and 82°F) unless otherwise labeled. Optimal storage is at the lower half of this temperature range. To prevent contamination of unused product, do not return any material to its original container.

### NOTE

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. **ITW Permatex, Inc. specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Permatex, Inc. products and disclaims any liability for consequential or incidental damages of any kind, including lost profits.** This product may be covered by one or more United States or foreign patents or patent applications.

NOT FOR PRODUCT SPECIFICATIONS.

THE TECHNICAL DATA CONTAINED HEREIN ARE INTENDED AS REFERENCE ONLY.

PLEASE CONTACT PERMATEX, INC., TECHNICAL SERVICE DEPARTMENT FOR ASSISTANCE AND RECOMMENDATIONS FOR YOUR SPECIFIC APPLICATION.  
PERMATEX, INC., HARTFORD SQUARE NORTH, 10 COLUMBUS BOULEVARD, HARTFORD, CT 06106 PHONE - (1-877)PERMATEX)