



Toll Free: 87 PERMATEX
(877-376-2839)

10 Columbus Blvd., Hartford,
Connecticut 06106

6875 Parkland Boulevard, Solon
Ohio 44139

Technical Data Sheet

Permatex® PermaSorb™ Multi- purpose Cellulose Absorbent

AAM Revised 02/09

PRODUCT DESCRIPTION

Permatex® PermaSorb™ Multi-Purpose Cellulose Absorbent safely absorbs all liquids including oil, coolant, ATF, brake fluid, paint and solvents on contact. It is made from 100% reclaimed, unbleached wood cellulose fiber and contains no carcinogens that may cause respiratory hazards making it safe for the user to handle. The biodegradable fibers lock liquids to prohibit leeching into soil. This is an environmentally friendly product that can be disposed in landfills, incinerated or bioremediation.

PRODUCT BENEFITS

- A clay alternative
- Instant acting
- Non-dusty
- Environmentally friendly
- Biodegradable
- Safe to use
- Seven times more absorbent than clay products
- Light weight

SUGGESTED APPLICATIONS

- Spills on garage floors
- Spills on shop floors
- Driveways
- Sidewalks

DIRECTIONS FOR USE

1. Place a dam of PermaSorb™ around spill.
2. Then cover spill completely with PermaSorb™.
3. With a stiff floor brush, immediately sweep PermaSorb™ part way through spill then bring back and forth.
4. Gather from all directions until spill is completely picked up. Sweep aside.
5. Lightly re-apply PermaSorb™ and sweep over spill area to remove any remaining spill residue.
6. Sweep up completely and dispose of residue according to federal, state and local regulations for absorbed material.

PHYSICAL PROPERTIES

	Typical Value
Chemical Type	Cellulose
Appearance	Grey granules
Odor	Wet paper
Specific Gravity	0.17
Flash Point, OC °F (°C)	450(232)

GENERAL INFORMATION

For safe handling information on this product, consult the Material Safety Data Sheet, (MSDS).

ORDERING INFORMATION

Part Number	Container Size
38490	28 Liter Bag

STORAGE

Products shall be ideally stored in a cool, dry location in unopened containers at a temperature between 8° and 28°C (46° and 82°F) unless otherwise labeled. Optimal storage is at the lower half of this temperature range. To prevent contamination of unused product, do not return any material to its original container.

NOTE

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. **Permatex, Inc. specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Permatex, Inc. products and disclaims any liability for consequential or incidental damages of any kind, including lost profits.** This product may be covered by one or more United States or foreign patents or patent applications.

NOT FOR PRODUCT SPECIFICATIONS.

THE TECHNICAL DATA CONTAINED HEREIN ARE INTENDED AS REFERENCE ONLY.

PLEASE CONTACT PERMATEX, INC., TECHNICAL SERVICE DEPARTMENT FOR ASSISTANCE AND RECOMMENDATIONS FOR YOUR SPECIFIC APPLICATION.
PERMATEX, INC., HARTFORD SQUARE NORTH, 10 COLUMBUS BOULEVARD, HARTFORD, CT 06106 PHONE – (1-87PERMATEX)