



Toll Free: 87 PERMATEX
(877-376-2839)

10 Columbus Blvd., Hartford,
Connecticut 06106

6875 Parkland Boulevard, Solon
Ohio 44139

Technical Data Sheet

Permatex® Carburetor & Parts Cleaner

AAM Revised 10/02

PRODUCT DESCRIPTION

Permatex® Carburetor & Parts Cleaner is a fast acting, highly concentrated, cold immersion type metal parts cleaner. It will not discolor or harm metal. It strips away baked-on carbon, gum, varnish and other products of combustion. As well as grease, oil and lacquer.

S.I.N.: 834-300

PRODUCT BENEFITS

- Effectively cleans grease, gum and carbon deposits
- Fast acting
- Cold immersion, no heating required
- Will not discolor metal

TYPICAL APPLICATIONS

- Carburetors
- Throttle plates
- Choke plates

DIRECTIONS FOR USE

1. Disassemble carburetor.
2. Place it and other metal parts to be cleaned into a metal dip basket.
3. Immerse parts into solution and let stand for approximately 15 minutes. (A longer time may be required for heavy build-up.)



4. After immersion, remove parts slowly and allow to drain for a few minutes.
5. If additional cleaning is required, dry parts before returning to container.
6. Do not add any additional chemicals to the solvent bath.
7. Do not put plastic or rubber parts into the cleaner.

PROPERTIES OF UNCURED MATERIAL

	Typical Value
Chemical Type	Solvent/surfactant mix
Appearance	Clear to slightly cloudy liquid
Odor	Solvent/ammonia
Color	Amber
Specific Gravity	0.93
Flash Point, TCC, °C (°F)	48.9 (120)

GENERAL INFORMATION

This product is not recommended for use in pure oxygen and/or oxygen rich systems and should not be selected for use with chlorine or other strong oxidizing materials.

For safe handling information on this product, consult the Material Safety Data Sheet, (MSDS).

ORDERING INFORMATION

Part Number	Container Size
82578 (46F)	1 gal. Can
82579 (46Y)	3.5 gal. Pail
82580 (46YB)	3.5 gal. Pail w/ Dip Basket

STORAGE

Products shall be ideally stored in a cool, dry location in unopened containers at a temperature between 8° to 28°C (46° to 82°F) unless otherwise labeled. Optimal storage is at the lower half of this temperature range. To prevent contamination of unused product, do not return any material to its original container.

NOTE

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. **Permatex, Inc. specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Permatex, Inc. products and disclaims any liability for consequential or incidental damages of any kind, including lost profits.** This product may be covered by one or more United States or foreign patents or patent applications.