



Toll Free: 87 PERMATEX
(877-376-2839)

10 Columbus Blvd., Hartford,
Connecticut 06106

6875 Parkland Boulevard, Solon
Ohio 44139

Technical Data Sheet

Permatex[®] Plastic Cleaner

INDUSTRIAL

PRODUCT DESCRIPTION

S.I.N.: 834-300

Permatex[®] Plastic Cleaner is a white, creamy liquid with a mild, pleasant odor. The principal use for Permatex[®] Plastic Cleaner was in the aviation field for cleaning plastic windows and canopies. However, because of its excellent properties, has many applications in automotive, marine, motorcycle and industrial areas as well as numerous household uses. It is specifically developed for use as a polish and cleaner capable of removing accumulated service soils and producing a smooth, lustrous finish on clear and pigmented plastic surfaces. Although Permatex[®] Plastic Cleaner was developed for use on clear surfaces made of acrylic polymer (Lucite, Plexiglass, etc.), it is also effective on other plastic surfaces, clear or opaque, including polycarbonates (Lexan), acetates, rigid vinyls, polystyrene (Polysar, Styron) and high pressure laminates (Formica, Nevamar, Lamin-art, Textolite). It may also be used as a cleaner and polish for hard enameled surfaces, glass, ceramics and stainless steel. Conforms to Federal Specification P-P 560, Type I.

PRODUCT BENEFITS

- Gives a clean, smooth, lustrous finish on plastics
- Forms a water-repellent, anti static shield
- Extends the life of plastics
- Reduces replacement costs
- Improves visibility
- Contains no ozone depleting compounds
- Easy application
- Removes grease, lubricants, stains and dirt

TYPICAL APPLICATIONS

- Plastic windows
- Canopies
- Instrument covers
- Goggles
- Lenses
- Motorcycle helmets
- Motorcycle windshields
- Boat and aircraft windshields
- Excellent on acrylic, polycarbonate, acetates, rigid vinyl, polystyrene and decorative laminates.

DIRECTIONS FOR USE

- 1 Flush extremely dirty surfaces with water.
- 2 Shake well before use.
- 3 Using light pressure, apply a thin, even coat with soft, clean cloth in a circular motion.

CHEMICAL PROPERTIES

Chemical Type

Appearance

Odor

Specific Gravity

Viscosity

Flash Point, Setaflash Closed Cup, °F

Typical Value

Naphtha, Emulsifiers

White, creamy liquid

Mild petroleum

0.99

Flow is similar to SAE 10

Motor Oil

112

GENERAL INFORMATION

For safe handling information on this product, consult the Material Safety Data Sheet, (MSDS).

ORDERING INFORMATION

Part Number	Container Size
80183 (403D)	16 fl. oz. spout-top can

STORAGE

Products shall be ideally stored in a cool, dry location in unopened containers at a temperature between 8_ to 28_C (46_ to 82_F) unless otherwise labeled. Optimal storage is at the lower half of this temperature range. To prevent contamination of unused product, do not return any material to its original container.

NOTE

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. **Permatex, Inc. specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Permatex, Inc. products and disclaims any liability for consequential or incidental damages of any kind, including lost profits.** This product may be covered by one or more United States or foreign patents or patent applications.

NOT FOR PRODUCT SPECIFICATIONS.

THE TECHNICAL DATA CONTAINED HEREIN ARE INTENDED AS REFERENCE ONLY.

PLEASE CONTACT PERMATEX, INC., TECHNICAL SERVICE DEPARTMENT FOR ASSISTANCE AND RECOMMENDATIONS FOR YOUR SPECIFIC APPLICATION.
PERMATEX, INC., HARTFORD SQUARE NORTH, 10 COLUMBUS BOULEVARD, HARTFORD, CT 06106 PHONE - (1-87PERMATEX) Revised 10/02