



Toll Free: 87 PERMATEX
(877-376-2839)

10 Columbus Blvd., Hartford,
Connecticut 06106

6875 Parkland Boulevard, Solon
Ohio 44139

Technical Data Sheet

Permatex[®] Force 109[®] 5-Way Spray

AAM Revised 10/02

PRODUCT DESCRIPTION

Permatex[®] Force 109[®] 5-way Spray is a general purpose liquid aerosol lubricant, penetrating oil, rust preventive and water displacer primarily designed to reduce friction in non-load bearing metallic and non-metallic mechanical assemblies.

S.I.N.: 834-300

PRODUCT BENEFITS

Permatex[®] Force 109[®] 5-way Spray quickly:


- Penetrates
- Lubricates
- Eliminates moisture
- Frees
- Protects

TYPICAL APPLICATIONS

- Penetrates mechanical mechanisms
- Lubricates non-load bearing assemblies
- Eliminates moisture from spark plugs, ignition wires, etc.
- Frees frozen threaded or bearing assemblies
- Protects parts and assemblies from corrosion

DIRECTIONS FOR USE

1. Provide adequate ventilation.
2. Shake can thoroughly before use. Note: There is no ball agitator inside the can. For best results, aerosol can should be at room temperature before spraying.
3. Holding can 8 to 10 inches from the surface for open area lubrication, or use the extension tube provided for hard to reach areas, press the nozzle and discharge the product on the assembly.



For Cleanup

1. Clean hands with Permatex[®] brand hand cleaners.

PROPERTIES OF MATERIAL

Chemical Type
Appearance
Odor
Flash Point

NFPA 704 Flammability Rating

Typical Value
Petroleum distillate
Clear liquid
Mild petroleum
Aerosol, contents under pressure,
consult MSDS
4 (Highly flammable)

GENERAL INFORMATION

This product is not recommended for use in pure oxygen and/or oxygen rich systems and should not be selected as a lubricant for chlorine or other strong oxidizing materials.

For safe handling information on this product, consult the Material Safety Data Sheet, (MSDS).

ORDERING INFORMATION

Part Number	Container Size
80068 (109DA)	9 oz. net aerosol can

STORAGE

Products shall be ideally stored in a cool, dry location in unopened containers at a temperature between 8_ to 28_C (46_ to 82_F) unless otherwise labeled. Optimal storage is at the lower half of this temperature range.

NOTE

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. **Permatex, Inc. specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Permatex, Inc. products and disclaims any liability for consequential or incidental damages of any kind, including lost profits.** This product may be covered by one or more United States or foreign patents or patent applications.

NOT FOR PRODUCT SPECIFICATIONS.
THE TECHNICAL DATA CONTAINED HEREIN ARE INTENDED AS REFERENCE ONLY.
PLEASE CONTACT PERMATEX, INC., TECHNICAL SERVICE DEPARTMENT FOR ASSISTANCE AND RECOMMENDATIONS FOR YOUR SPECIFIC APPLICATION.
PERMATEX, INC., HARTFORD SQUARE NORTH, 10 COLUMBUS BOULEVARD, HARTFORD, CT 06106 PHONE - (1-87)PERMATEX)