



Permatex® Threadlocker Gel

in the GEL TWIST™
Applicator...

Puts you in control
of your threaded
assemblies.



Permatex®

Permatex® Introduces the Latest Technology in Threadlocking...

Permatex® Threadlocker Gels in the GEL TWIST™ Applicator.

Permatex® Threadlocker Gels in the patent-pending GEL TWIST™ pin-point applicator is the next generation in Threadlocking! Far more reliable than conventional locking methods, Permatex® Threadlocker Gels will secure threaded assemblies with the same quality as other chemical solutions, without the problems. No more liquid drips or solid stick globs to deal with. No more mess to clean or costly waste to worry about. No need for costly washer inventories and unreliable results. Permatex® Threadlocker Gels in the GEL TWIST™ applicator put you in control of your threaded assemblies!



The GEL TWIST™ Advantage



The patent-pending GEL TWIST™ pin-point applicator with the extended nozzle allows for easy application in “hard-to-reach” locations. Easily portable, it can be carried in your toolbox or shirt pocket without the fear of leakage.

Available in **Medium Strength BLUE Gel** and **High Strength RED Gel**,

the gel formula will not drip or run like traditional liquid threadlockers making it ideal for use on **vertical** applications because it stays on the part which reduces waste and clean-up time. It locks and seals while preventing parts from loosening due to vibration or differential thermal expansion and protects threads from corrosion.

Permatex® Threadlocker Gels in the GEL TWIST™ Applicator...

the latest in chemical and packaging technology in one great product. Only from Permatex®, the leaders in Automotive Threadlocking.



Easy to Use GEL TWIST™ Pin-Point Applicator

1. Remove protective cap.
2. Turn dial to expose 1/8" to 1/4" of material beyond tip.
3. Apply Threadlocker to engagement area. (Typically, the male fitting covering 5 to 6 threads.) Avoid direct contact of tip to metal surfaces.*
4. Assemble parts and tighten to recommended torque. Replace protective cap.

* If contact occurs, expose 1/16" of material and wipe off with a clean towel.

Permatex® Threadlocker Gels in the GEL TWIST™ Applicator

APPLICATION COMPARISON CHART

FEATURES/BENEFITS	Permatex® Threadlocker Gel in the GEL TWIST™ Applicator	Liquid Threadlocker	Threadlocking Stick	Toothed Lock Washer	Serrated Toothed Flange Nut
Prevents corrosion	✓	✓	✓		
Eliminates the need for multiple size inventory	✓	✓	✓		
Will not damage parts in assembly or disassembly	✓	✓	✓		
Prevents seizing	✓	✓	✓		
Seals potential leak paths	✓	✓	✓		
Can be applied to vertical applications	✓		✓	✓	✓
Precision application	✓	✓		N/A	N/A
Will not run	✓		✓	N/A	N/A
Will not glob	✓	✓		N/A	N/A
Wicks into threads	✓	✓		N/A	N/A
Blind hole applications	✓	✓		N/A	N/A
Prevents vibrational loosening	✓	✓	✓		
Prevents loosening due to differential thermal expansion	✓	✓	✓		

PRODUCT DESCRIPTIONS

Medium Strength Threadlocker BLUE Gel

An all-purpose medium strength blue threadlocker gel that reliably secures all nut and bolt applications 1/4" to 1" (6mm to 25mm). Locks and seals threaded assemblies while preventing parts from loosening due to vibration or thermal differential expansion. Removable with hand tools for easy disassembly.

Suggested Applications: Ideal for valve cover bolts, water pump bolts, oil pan bolts, drive shaft bolts, rocker arm adjustment nuts and carburetor studs



High Strength Threadlocker RED Gel

A high strength red threadlocker gel for heavy-duty applications. Ideal for reliably securing all permanent nut and bolt applications 3/8" to 1" (10mm to 25mm) and greater. Locks and seals while preventing parts from loosening due to vibration. Eliminates the need for split ring lock washers, toothed lock washers, serrated toothed flange nuts and ribbed flange bolts. Requires heat or special tools for removal.

Suggested Applications: Permanently locks studs for applications such as ring gear bolts, frame bolts and is particularly well suited for cylinder block and rocker arm studs.

ORDERING INFORMATION

ITEM NO.	DESCRIPTION	UNITS PER CASE	CASE DIMENSIONS	CASE CUBE	GROSS WT. LBS.	UPC PREFIX 686226
24010	Permatex® Medium Strength Threadlocker BLUE Gel*, 10 g carded	6	8.63" L x 4.75" W x 5.63" D	.13	.72	24010 1
27010	Permatex® High Strength Threadlocker RED Gel*, 10 g carded	6	8.63" L x 4.75" W x 5.63" D	.13	.66	27010 8

* in the GEL TWIST™ applicator



Permatex, Inc.
Hartford Square North
10 Columbus Boulevard
Hartford, Connecticut 06106

Contact Permatex Toll Free for technical information or to place an order 87-PERMATEX (877-376-2839). To fax an order: 1-800-432-2067.

Visit our Web Site at www.permatex.com

Permatex, Design and GEL TWIST are trademarks of Permatex, Inc. © Copyright 2004. Permatex, Inc. All rights reserved. 0407-196/PX-0225