

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: US OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada WHMIS which includes the amended Hazardous Products Act (HPA) and the Hazardous Products Regulation (HPR)

Revision Date 09-Jun-2025 Version 2

1. Identification

Product identifier

Product Name 81840 EXTREME REARVIEW MIRROR PROF STRENGTH ADHESIVE PART 1

Other means of identification

Product Code PTX194319VV

UN number or ID number UN3264

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Adhesive

Restrictions on use No information available

Details of the supplier of the safety data sheet

Manufacturer Address May Also Be Distributed by:

ITW Permatex, Inc. ITW Permatex Canada 6875 Parkland Blvd. 101-2360 Bristol Circle

Solon, Ohio 44139 USA

Telephone: 1-87-Permatex

Oakville, ON Canada L6H 6M5

Telephone: (800) 924-6994

(866) 732-9502

E-mail address mail@permatex.com

Emergency telephone number

Company Phone Number 866-732-9502

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924

International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003453

24-hour emergency phone number No information available

2. Hazard(s) identification

Classification

Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 1 Sub-category A
Serious eye damage/eye irritation	Category 1
Skin sensitization	Category 1
Carcinogenicity	Category 1B

Specific target organ toxicity (repeated exposure)

Category 2

Label elements

Contains Acrylic acid; CUMENE HYDROPEROXIDE; 2-Hydroxyethyl methacrylate; CUMENE



Danger

Hazard statements

Harmful if inhaled.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

May cause cancer.

May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements - Prevention

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves, protective clothing, eye protection and face protection.

Use only outdoors or in a well-ventilated area.

Do not breathe dust.

Wash face, hands and any exposed skin thoroughly after handling.

Contaminated work clothing should not be allowed out of the workplace.

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention.

Immediately call a POISON CENTER or doctor.

Specific treatment (see supplemental first aid instructions on this label).

Eyes

Immediately call a POISON CENTER or doctor.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. **Skin**

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

Wash contaminated clothing before reuse.

IF ON SKIN: Wash with plenty of water and soap.

If skin irritation or rash occurs: Get medical advice and attention.

Take off contaminated clothing and wash it before reuse.

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER or doctor if you feel unwell.

Immediately call a POISON CENTER or doctor.

Ingestion

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

Precautionary Statements - Storage

Store locked up.

Precautionary Statements - Disposal

Dispose of contents and container in accordance with local, regional, national, and international regulations as applicable.

Unknown acute toxicity

47.3017 % of the mixture consists of ingredient(s) of unknown acute oral toxicity.

52.3717 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity.

96.37795 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas).

96.37795 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor).

86.6717 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist).

Other Information

May be harmful if swallowed. May be harmful in contact with skin. Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

3. Composition/information on ingredients

Substance

Not applicable.

<u>Mixture</u>

Chemical name	CAS No.	Weight-%	Information Review	Date HMIRA filed and date exemption granted (if applicable)
Acrylic acid	79-10-7	5-10%	-	-
CUMENE HYDROPEROXIDE	80-15-9	1-5%	-	-
2-Hydroxyethyl methacrylate	868-77-9	0.1-1%	-	-
CUMENE	98-82-8	0.1-1%	-	-

4. First-aid measures

Description of first aid measures

General advice Immediate medical attention is required. Show this safety data sheet to the doctor in

attendance. IF exposed or concerned: Get medical advice/attention.

Inhalation Remove to fresh air. If breathing has stopped, give artificial respiration. Get medical

attention immediately. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If breathing is difficult, (trained personnel

should) give oxygen. Delayed pulmonary edema may occur.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep

eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present

and easy to do. Continue rinsing. Get immediate medical attention.

Skin contactWash off immediately with soap and plenty of water while removing all contaminated clothes

and shoes. Get immediate medical attention. May cause an allergic skin reaction.

Ingestion Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious

person. Get immediate medical attention.

Self-protection of the first aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Avoid breathing vapors or mists. Use personal protective equipment as required. See

section 8 for more information.

Most important symptoms and effects, both acute and delayed

Symptoms Burning sensation. Itching. Rashes. Hives. Coughing and/ or wheezing. Difficulty in

breathing.

Effects of Exposure May cause cancer. May cause damage to organs through prolonged or repeated exposure.

Indication of any immediate medical attention and special treatment needed

Note to physicians Product is a corrosive material. Use of gastric lavage or emesis is contraindicated.

Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure. May cause sensitization in susceptible persons. Treat symptomatically.

5. Fire-fighting measures

surrounding environment.

Small Fire In case of fire, use water spray, foam, dry chemical, or CO2. Large Fire In case of fire, use water spray, foam, dry chemical, or CO2.

Unsuitable extinguishing mediaDo not scatter spilled material with high pressure water streams.

Specific hazards arising from the

chemical

The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating gases and vapors. Product is or contains a sensitizer. May

cause sensitization by skin contact.

Hazardous combustion products No information available.

Explosion data

Sensitivity to mechanical impact None. **Sensitivity to static discharge** None.

Special protective equipment and precautions for fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Attention! Corrosive material. Avoid contact with skin, eyes or clothing. Ensure adequate

ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Avoid breathing vapors or mists.

Other information Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. Handling and storage

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with

skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before

reuse. Avoid breathing vapors or mists.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from moisture. Store locked up. Keep out of the reach of children. Store away from other materials.

8. Exposure controls/personal protection

Control Parameters Exposure Limits

Chemical name	Chemical name ACGIH TLV		NIOSH
Acrylic acid TWA: 2 ppm		(vacated) TWA: 10 ppm	TWA: 2 ppm;
79-10-7	pSk	(vacated) TWA: 30 mg/m ³	TWA: 6 mg/m³;
		Sdv	-
CUMENE TWA: 5 ppm		TWA: 50 ppm	TWA: 50 ppm;
98-82-8		TWA: 245 mg/m ³	TWA: 245 mg/m ³ ;
		(vacated) TWA: 50 ppm	IDLH: 900 ppm
		(vacated) TWA: 245 mg/m ³	
		dSk	
		Sdv	

Chemical name	Alberta	British Columbia	Ontario	Quebec
Acrylic acid	TWA: 2 ppm;	TWA: 2 ppm;	TWA: 2 ppm;	TWAEV: 2 ppm;
79-10-7	TWA: 5.9 mg/m ³ ;	Adverse reproductive	dSk	TWAEV: 5.9 mg/m ³ ;
	pSk	effect		Sd
	-	Sk		
CUMENE	TWA: 50 ppm;	TWA: 25 ppm;	TWA: 50 ppm;	TWAEV: 5 ppm;
98-82-8	TWA: 246 mg/m ³ ;	STEL: 75 ppm;		

Chemical name	Manitoba	New Brunswick	Newfoundland and Labrador	Nova Scotia
Acrylic acid	TWA: 2 ppm; pSk	TWA: 2 ppm; pSk	TWA: 2 ppm; pSk	TWA: 2 ppm; pSk
CUMENE	TWA: 5 ppm;	TWA: 50 ppm;	TWA: 5 ppm;	TWA: 5 ppm;

Chemical name	Nunavut	Prince Edward Island	Saskatchewan	Yukon
Acrylic acid	TWA: 2 ppm; STEL: 4 ppm;	TWA: 2 ppm;	TWA: 2 ppm; STEL: 4 ppm;	
	Sk		pSd	
CUMENE	TWA: 50 ppm; STEL: 74 ppm;	TWA: 5 ppm;	TWA: 50 ppm; STEL: 74 ppm;	TWA: 50 ppm; TWA: 245 mg/m³; STEL: 75 ppm; STEL: 365 mg/m³; Sk

Appropriate engineering controls

Engineering controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Face protection shield. Tight sealing safety goggles. Wear safety glasses with side shields

(or goggles).

Hand protection Wear suitable gloves.

Skin and body protection Wear suitable protective clothing. Chemical resistant apron.

Use appropriate respiratory protection. Respiratory protection

General hygiene considerations Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do

not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

No information available. Thermal hazards

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state

Appearance No information available

Color Clear

Odor No information available **Odor threshold** No information available

Property Values Remarks • Method

pН No data available Melting point / freezing point No data available > 150 °C / 302 °F Boiling point / boiling range > 95 °C / 203 °F Flash point

Cleveland Open Cup **Evaporation rate** Butyl acetate = 1 < 1

Flammability (solid, gas) No data available

Flammability Limit in Air

Upper flammability limit: No data available Lower flammability limit: No data available Vapor pressure <5 mmHg @ 75°F

Vapor density Air = 1**>**1 Relative density 1.1 @ 80°F

Water solubility Insoluble Solubility(ies) No data available Partition coefficient No data available **Autoignition temperature** No data available **Decomposition temperature** No data available Kinematic viscosity No data available Dynamic viscosity No data available

Particle characteristics

No data available Particle Size **Particle Size Distribution** No data available

Other information

No information available **Explosive properties Oxidizing properties** No information available Softening point No information available Molecular weight No information available

VOC content 11%

Density No information available **Bulk density** No information available

10. Stability and reactivity

No information available. Reactivity

Revision Date 09-Jun-2025

Chemical stability Stable under normal conditions.

Possibility of hazardous reactions None under normal processing.

Hazardous polymerization No information available.

Conditions to avoid Exposure to air or moisture over prolonged periods. Excessive heat.

Incompatible materials Acids. Bases. Oxidizing agent.

Hazardous decomposition products None known based on information supplied.

11. Toxicological information

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. Corrosive by inhalation.

(based on components). Inhalation of corrosive fumes/gases may cause coughing, choking, headache, dizziness, and weakness for several hours. Pulmonary edema may occur with tightness in the chest, shortness of breath, bluish skin, decreased blood pressure, and increased heart rate. Inhaled corrosive substances can lead to a toxic edema of the lungs.

Pulmonary edema can be fatal. Harmful by inhalation.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye damage.

(based on components). Corrosive to the eyes and may cause severe damage including

blindness. May cause irreversible damage to eyes.

Skin contact Specific test data for the substance or mixture is not available. Corrosive. (based on

components). Causes burns. May cause sensitization by skin contact. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. May be

harmful in contact with skin.

Ingestion Specific test data for the substance or mixture is not available. Causes burns. (based on

components). Ingestion causes burns of the upper digestive and respiratory tracts. May cause severe burning pain in the mouth and stomach with vomiting and diarrhea of dark blood. Blood pressure may decrease. Brownish or yellowish stains may be seen around the mouth. Swelling of the throat may cause shortness of breath and choking. May cause lung

damage if swallowed. May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Redness. Burning. May cause blindness. Coughing and/ or wheezing. Itching. Rashes.

Hives.

<u>Acute toxicity</u> Harmful by inhalation.

Numerical measures of toxicity

The following ATE values have been calculated for the mixture

 ATEmix (oral)
 3,607.40 mg/kg

 ATEmix (dermal)
 3,645.30 mg/kg

 ATEmix (inhalation-gas)
 99,999.00 ppm

 ATEmix (inhalation-vapor)
 99,999.00 mg/l

 ATEmix (inhalation-dust/mist)
 1.417 mg/l

Unknown acute toxicity

47.3017 % of the mixture consists of ingredient(s) of unknown acute oral toxicity

52.3717 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

96.37795 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)

96.37795 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

PTX194319VV - 81840 EXTREME REARVIEW MIRROR PROF STRENGTH ADHESIVE PART 1

86.6717 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Acrylic acid	= 1500 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 3.6 mg/L (Rat) 4 h
79-10-7			= 11.1 mg/L (Rat) 1 h
CUMENE HYDROPEROXIDE 80-15-9	= 382 mg/kg (Rat)	= 0.126 mL/kg (Rabbit)	= 220 ppm (Rat) 4 h
2-Hydroxyethyl methacrylate 868-77-9	= 5564 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	•
CUMENE 98-82-8	= 1400 mg/kg (Rat)	= 12300 μL/kg (Rabbit)	> 3577 ppm (Rat) 6 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes severe skin burns and eye

damage.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye damage. Causes

burns

Respiratory or skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity No information available.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for

ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Acrylic acid	A4 - Not Classifiable as	Group 3 -	-	-
79-10-7	a Human Carcinogen	Unclassifiable as to		
		carcinogenicity in		
		humans		
CUMENE	A3 - Confirmed Animal	Group 2B - Possibly	Reasonably Anticipated	Present
98-82-8	Carcinogen with	carcinogenic to humans	To Be A Human	
	Unknown Relevance to		Carcinogen	
	Humans			

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly carcinogenic to humans

Group 3 - Not classifiable as to carcinogenicity in humans

NTP (National Toxicology Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

Occupational Safety and Health Administration of the US Department of Labor

X - Present

Reproductive toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard No information available.

12. Ecological information

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Acrylic acid 79-10-7	EC50: =0.17mg/L (96h, Pseudokirchneriella subcapitata) EC50: =0.04mg/L (72h, Desmodesmus subspicatus)	Brachydanio rerio)	<u>-</u>	EC50: =95mg/L (48h, Daphnia magna)
CUMENE HYDROPEROXIDE 80-15-9	-	LC50: =3.9mg/L (96h, Oncorhynchus mykiss)	-	-
2-Hydroxyethyl methacrylate 868-77-9	-	LC50: 213 - 242mg/L (96h, Pimephales promelas) LC50: =227mg/L (96h, Pimephales promelas)	-	-
CUMENE 98-82-8	EC50: =2.6mg/L (72h, Pseudokirchneriella subcapitata)	LC50: 6.04 - 6.61mg/L (96h, Pimephales promelas) LC50: =4.8mg/L (96h, Oncorhynchus mykiss) LC50: =2.7mg/L (96h, Oncorhynchus mykiss) LC50: =5.1mg/L (96h, Poecilia reticulata)	-	EC50: =0.6mg/L (48h, Daphnia magna) EC50: 7.9 - 14.1mg/L (48h, Daphnia magna)

Persistence and degradability

No information available.

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Acrylic acid 79-10-7	0.46
CUMENE HYDROPEROXIDE 80-15-9	1.6
2-Hydroxyethyl methacrylate 868-77-9	0.42
CUMENE 98-82-8	3.55

Other adverse effects

No information available.

13. Disposal considerations

Waste treatment methods

Waste from residues/unused products

Dispose of in accordance with local regulations. Dispose of waste in accordance with

environmental legislation.

Contaminated packaging

Do not reuse empty containers.

14. Transport information

DOT

UN number or ID number UN3264

Proper shipping name

Transport hazard class(es) 8
Packing group ||
DOT Marine Pollutant |

Marine pollutant Acrylic acid, CUMENE HYDROPEROXIDE.

Description UN3264, Corrosive liquid, acidic, inorganic, n.o.s.(Acrylic acid, CUMENE

HYDROPEROXIDE), 8, II, Limited Quantity

Special Provisions 386, B2, IB2, T11, TP2, TP27

TDG

UN number or ID number UN3264

UN proper shipping name Corrosive liquid, acidic, inorganic, n.o.s.

Transport hazard class(es) 8
Packing group | |

Marine pollutant name Acrylic acid

Description UN3264, Corrosive liquid, acidic, inorganic, n.o.s.(Acrylic acid, CUMENE

HYDROPEROXIDE), 8, II, Limited Quantity

MEX

UN number or ID number UN3264

UN proper shipping name Corrosive liquid, acidic, inorganic, n.o.s.

Transport hazard class(es) 8
Packing group | |

Description UN3264, Corrosive liquid, acidic, inorganic, n.o.s. (Acrylic acid, CUMENE

HYDROPEROXIDE), 8, II, Limited Quantity

Special Provisions 274

ICAO (air)

UN number or ID number UN3264

UN proper shipping name Corrosive liquid, acidic, inorganic, n.o.s.

Transport hazard class(es) 8
Packing group | |

Description UN3264, Corrosive liquid, acidic, inorganic, n.o.s.(Acrylic acid, CUMENE

HYDROPEROXIDE), 8, II, Limited Quantity

Special Provisions A3

IATA

UN number or ID number UN3264

UN proper shipping name Environmentally hazardous substance, liquid, n.o.s.

Transport hazard class(es) 8
Packing group II
ERG Code 8L
Special Provisions A3, A803

Description UN3264, Corrosive liquid, acidic, inorganic, n.o.s.(Acrylic acid, CUMENE

HYDROPEROXIDE), 8, II, Limited Quantity

<u>IMDG</u>

UN number or ID number UN3264

UN proper shipping name
Transport hazard class(es) 8
Packing group || F.A. S.

EmS-No. F-A, S-B Special Provisions 274

Description UN3264, Corrosive liquid, acidic, inorganic, n.o.s. (Acrylic acid, CUMENE

HYDROPEROXIDE), 8, II, Limited Quantity, Marine pollutant

15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

International Inventories

Complies **TSCA** Complies **DSL/NDSL EINECS/ELINCS** Does not comply Complies **ENCS** Complies **IECSC** Complies KECI Complies **PICCS AICS** Complies Complies **NZIoC**

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing Chemicals Inventory

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	SARA 313 - Threshold Values %
Acrylic acid - 79-10-7	1.0
CUMENE HYDROPEROXIDE - 80-15-9	1.0
SACCHARIN - 81-07-2	1.0
CUMENE - 98-82-8	0.1

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Chemical name		Hazardous Substances RQs	Extremely Hazardous	Reportable Quantity (RQ)
			Substances RQs	
	Acrylic acid	5000 lb /	-	RQ 5000 lb final RQ
	79-10-7	kg (final RQ)		RQ 2270 kg final RQ

CUMENE HYDROPEROXIDE	10 lb /	-	RQ 10 lb final RQ
80-15-9	kg (final RQ)		RQ 4.54 kg final RQ
CUMENE	5000 lb /	-	RQ 5000 lb final RQ
98-82-8	kg (final RQ)		RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical name	California Proposition 65	
CUMENE - 98-82-8	Carcinogen	

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Acrylic acid	X	X	X
79-10-7			
CUMENE HYDROPEROXIDE	X	X	X
80-15-9			
SACCHARIN	X	X	X
81-07-2			
PROPYLENE GLYCOL	X	-	X
57-55-6			
CUMENE	X	X	X
98-82-8			
P-BENZOQUINONE	X	X	X
106-51-4			

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. Other information

NFPA Health hazards 3 Flammability 1 Instability 0 Special hazards - HMIS Health hazards 3 * Flammability 1 Physical hazards 0 Personal protection X Chronic Hazard Star Legend *= Chronic Health Hazard

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend

SVHC: Substances of Very High Concern for Authorization:
PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances
vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances

STOT: Specific Target Organ Toxicity ATE: Acute Toxicity Estimate LC50: 50% Lethal Concentration

LD50: 50% Lethal Dose

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value * Skin designation

+ Sensitizers

Key literature references and sources for data used to compile the SDS

U.S. Agency for Toxic Substances and Disease Registry (ATSDR)

U.S. Environmental Protection Agency ChemView Database

European Food Safety Authority (EFSA)

U.S. Environmental Protection Agency

Acute Exposure Guideline Level(s) (AEGL(s))

U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act

U.S. Environmental Protection Agency High Production Volume Chemicals

Food Research Journal

Hazardous Substance Database

International Uniform Chemical Information Database (IUCLID)

Japan National Institute of Technology and Evaluation (NITE)

Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)

NIOSH (National Institute for Occupational Safety and Health)

National Library of Medicine's ChemID Plus (NLM CIP)

National Library of Medicine's PubMed database (NLM PUBMED)

U.S. National Toxicology Program (NTP)

New Zealand's Chemical Classification and Information Database (CCID)

International Organization for Economic Co-operation and Development (OECD) Environment, Health, and Safety Publications International Organization for Economic Co-operation and Development (OECD) High Production Volume Chemicals Program International Organization for Economic Co-operation and Development (OECD) Screening Information Data Set United Nations World Health Organization (WHO)

Revision Date 09-Jun-2025

Revision Note No information available.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: US OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada WHMIS which includes the amended Hazardous Products Act (HPA) and the Hazardous Products Regulation (HPR)

Revision Date 09-Jun-2025 Version 2

1. Identification

Product identifier

Product Name 81840 EXTREME REARVIEW MIRROR PROF STRENGTH ADHESIVE PART 2

Other means of identification

Product Code PTX394319VV

UN number or ID number UN1219

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Activator.

Restrictions on use No information available

Details of the supplier of the safety data sheet

Manufacturer Address May Also Be Distributed by:

ITW Permatex, Inc. ITW Permatex Canada 6875 Parkland Blvd. 101-2360 Bristol Circle

Solon, Ohio 44139 USA Oakville, ON Canada L6H 6M5 Telephone: 1-87-Permatex Telephone: (800) 924-6994

(866) 732-9502

E-mail address mail@permatex.com

Emergency telephone number

Company Phone Number 866-732-9502

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924

International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003453

24-hour emergency phone number No information available

2. Hazard(s) identification

Classification

Flammable liquids	Category 2
Serious eye damage/eye irritation	Category 2A
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Specific target organ toxicity (single exposure)	Category 3

Label elements

Contains 2-PROPANOL; Naphtha (petroleum), hydrotreated heavy



Danger

Hazard statements

Highly flammable liquid and vapor.

Causes serious eye irritation.

May cause genetic defects.

May cause cancer.

May cause drowsiness or dizziness.

Precautionary Statements - Prevention

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves, protective clothing, eye protection and face protection.

Wash face, hands and any exposed skin thoroughly after handling.

Avoid breathing dust, fume, gas, mist, vapors and spray.

Use only outdoors or in a well-ventilated area.

Ground and bond container and receiving equipment.

Use non-sparking tools.

Take action to prevent static discharges.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep container tightly closed.

Use explosion-proof electrical, ventilating and lighting equipment.

Keep cool.

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention.

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice and attention.

Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER or doctor if you feel unwell.

Fire

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Precautionary Statements - Storage

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Precautionary Statements - Disposal

Dispose of contents and container in accordance with local, regional, national, and international regulations as applicable.

- 2.1 % of the mixture consists of ingredient(s) of unknown acute oral toxicity.
- 2.1 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity.
- 98.6 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas).
- 2.1 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor).
- 98.6 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist).

Other Information

May be harmful if inhaled.

3. Composition/information on ingredients

Substance

Not applicable.

<u>Mixture</u>

Chemical name	CAS No.	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
2-PROPANOL	67-63-0	80-100%	-	-
ORGANO-COPPER COMPOUND	68084-48-0	1-5%	-	-
Naphtha (petroleum), hydrotreated heavy	64742-48-9	0.1-1%	-	-

4. First-aid measures

Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get

medical advice/attention.

Inhalation Remove to fresh air. IF exposed or concerned: Get medical advice/attention.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep

eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Skin contactWash off immediately with soap and plenty of water while removing all contaminated clothes

and shoes.

Ingestion Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious

person. Call a physician.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the material(s)

involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid

contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms May cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapor

concentrations may cause symptoms like headache, dizziness, tiredness, nausea and

vomiting.

Effects of Exposure May cause cancer. Mutagenic effects.

Indication of any immediate medical attention and special treatment needed

5. Fire-fighting measures

PTX394319VV - 81840 EXTREME REARVIEW MIRROR PROF STRENGTH ADHESIVE PART 2

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.

Small Fire In case of fire, use water spray, foam, dry chemical, or CO2. **Large Fire** In case of fire, use water spray, foam, dry chemical, or CO2.

Unsuitable extinguishing mediaDo not scatter spilled material with high pressure water streams.

Specific hazards arising from the

chemical

Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Hazardous combustion products No information available.

Explosion data

Sensitivity to mechanical impact None. **Sensitivity to static discharge** Yes.

Special protective equipment and precautions for fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See

section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the

product must be grounded. Do not touch or walk through spilled material.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor

suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other

non-combustible material and transfer to containers for later disposal.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert

absorbent material. Pick up and transfer to properly labeled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. Handling and storage

Precautions for safe handling

Advice on safe handling

Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Remove contaminated clothing and shoes. In case of insufficient ventilation, wear suitable respiratory equipment.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up.

8. Exposure controls/personal protection

Control Parameters Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
2-PROPANOL	TWA: 200 ppm	TWA: 400 ppm	TWA: 400 ppm;
67-63-0	STEL: 400 ppm	TWA: 980 mg/m ³	TWA: 980 mg/m ³ ;
		(vacated) TWA: 400 ppm	STEL: 500 ppm
		(vacated) TWA: 980 mg/m ³	STEL: 1225 mg/m ³
		(vacated) STEL: 500 ppm	IDLH: 2000 ppm
		(vacated) STEL: 1225 mg/m ³	
ORGANO-COPPER COMPOUND	TWA: 1 mg/m³ Cu dust and	-	TWA: 1 mg/m ³ ; Cu dust and
68084-48-0	mist		mist
			IDLH: 100 mg/m³ Cu dust and
			mist

Chemical name	Alberta	British Columbia	Ontario	Quebec
2-PROPANOL	TWA: 200 ppm;	TWA: 200 ppm;	TWA: 200 ppm;	TWAEV: 200 ppm;
67-63-0	TWA: 492 mg/m ³ ;	STEL: 400 ppm;	STEL: 400 ppm;	STEV: 400 ppm;
	STEL: 400 ppm;			
	STEL: 984 mg/m ³ ;			

Chemical name	Manitoba	New Brunswick	Newfoundland and Labrador	Nova Scotia
2-PROPANOL	TWA: 200 ppm;	TWA: 200 ppm;	TWA: 200 ppm;	TWA: 200 ppm;
	STEL: 400 ppm;	STEL: 400 ppm;	STEL: 400 ppm;	STEL: 400 ppm;

Chemica	al name	Nunavut	Prince Edward Island	Saskatchewan	Yukon
2-PROI	PANOL	TWA: 200 ppm;	TWA: 200 ppm;	TWA: 200 ppm;	TWA: 400 ppm;
		STEL: 400 ppm;	STEL: 400 ppm;	STEL: 400 ppm;	TWA: 980 mg/m ³ ;
					STEL: 500 ppm;
					STEL: 1225 mg/m ³ ;
					Sk

Biological occupational exposure limits

Chemical name	ACGIH
2-PROPANOL	40 mg/L - urine (Acetone) - end of shift at end of workweek
67-63-0	

Appropriate engineering controls

Engineering controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

PTX394319VV - 81840 EXTREME REARVIEW MIRROR PROF STRENGTH ADHESIVE PART 2

Wear safety glasses with side shields (or goggles). Tight sealing safety goggles. Eye/face protection

Hand protection Wear suitable gloves.

Skin and body protection Wear suitable protective clothing. Antistatic boots. Chemical resistant apron. Wear fire/flame

resistant/retardant clothing.

No protective equipment is needed under normal use conditions. If exposure limits are Respiratory protection

exceeded or irritation is experienced, ventilation and evacuation may be required. Use

appropriate respiratory protection.

Do not eat, drink or smoke when using this product. Contaminated work clothing should not General hygiene considerations

be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.

Thermal hazards No information available.

9. Physical and chemical properties

Information on basic physical and chemical properties

Liquid **Physical state**

No information available **Appearance**

Color Bluish Green

Odor No information available **Odor threshold** No information available

Property Values

рΗ No data available Melting point / freezing point No data available Boiling point / boiling range 82 °C / 179.6 °F °C / 53.6 °F Flash point 12

Evaporation rate 7.7 Flammability (solid, gas) No data available

Flammability Limit in Air

Upper flammability limit: 12.0% Lower flammability limit: 2.0%

Vapor pressure 32 mm Hg @ 68°F

Vapor density 2.1

0.79 @ 77°F Relative density Water solubility Soluble in water No data available Solubility(ies) No data available Partition coefficient **Autoignition temperature** No data available **Decomposition temperature** No data available Kinematic viscosity No data available **Dvnamic viscosity** No data available

Particle characteristics

Particle Size No data available **Particle Size Distribution** No data available

Other information

No information available **Explosive properties Oxidizing properties** No information available Softening point No information available Molecular weight No information available **VOC** content

No information available Density

Remarks • Method

Tag Closed Cup Butyl acetate = 1

Air = 1

PTX394319VV - 81840 EXTREME REARVIEW MIRROR PROF STRENGTH ADHESIVE PART 2

Bulk density No information available

10. Stability and reactivity

Reactivity No information available.

Chemical stability Stable under normal conditions.

Possibility of hazardous reactions
None under normal processing.

Hazardous polymerization No information available.

Conditions to avoid Heat, flames and sparks.

Incompatible materialsNone known based on information supplied.

Hazardous decomposition products None known based on information supplied.

11. Toxicological information

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. May cause irritation of

respiratory tract. May cause drowsiness or dizziness. May be harmful if inhaled.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye irritation.

(based on components). May cause redness, itching, and pain.

Skin contact Specific test data for the substance or mixture is not available. May cause irritation.

Prolonged contact may cause redness and irritation.

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause

gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms May cause redness and tearing of the eyes. Inhalation of high vapor concentrations may

cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Acute toxicity .

Numerical measures of toxicity

The following ATE values have been calculated for the mixture

 ATEmix (oral)
 5,233.20 mg/kg

 ATEmix (dermal)
 13,264.20 mg/kg

 ATEmix (inhalation-gas)
 99,999.00 ppm

 ATEmix (inhalation-vapor)
 31.20 mg/l

 ATEmix (inhalation-dust/mist)
 99,999.00 mg/l

- 2.1 % of the mixture consists of ingredient(s) of unknown acute oral toxicity
- 2.1 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity
- 98.6 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)
- 2.1 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)
- 98.6 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Component Information

	Chemical name	Oral LD50	Dermal LD50	Inhalation LC50	
Ī	2-PROPANOL	5050 mg/kg	12800 mg/kg	> 10000 ppm (Rat) 6 h	

67-63-0			
Naphtha (petroleum), hydrotreated	> 6000 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	> 8500 mg/m³ (Rat) 4 h
heavy			
64742-48-9			

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationNo information available.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Respiratory or skin sensitization No information available.

Germ cell mutagenicity Contains a known or suspected mutagen. Classification based on data available for

ingredients. May cause genetic defects.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for

ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
2-PROPANOL	A4 - Not Classifiable as	-	-	-
67-63-0	a Human Carcinogen			

Reproductive toxicity No information available.

STOT - single exposure May cause drowsiness or dizziness.

STOT - repeated exposure No information available.

Aspiration hazard No information available.

12. Ecological information

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to	Crustacea
			microorganisms	
2-PROPANOL	EC50: >1000mg/L (96h,	LC50: =9640mg/L (96h,	-	EC50: =13299mg/L
67-63-0	Desmodesmus	Pimephales promelas)		(48h, Daphnia magna)
	subspicatus)	LC50: =11130mg/L		
	EC50: >1000mg/L (72h,	(96h, Pimephales		
	Desmodesmus	promelas)		
	subspicatus)	LC50: >1400000µg/L		
		(96h, Lepomis		
		macrochirus)		
Naphtha (petroleum),	-	LC50: =2200mg/L (96h,	-	-
hydrotreated heavy		Pimephales promelas)		
64742-48-9				

Persistence and degradability No information available.

Bioaccumulation

Component Information

Chemical name	Partition coefficient
2-PROPANOL	0.05
67-63-0	

Other adverse effects No information available.

13. Disposal considerations

Waste treatment methods

Waste from residues/unused

products

Should not be released into the environment. Dispose of in accordance with local

regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld

containers.

US EPA Waste Number Waste designations and classifications should be determined by the end user based on the

application for which the product was used.

14. Transport information

DOT

UN number or ID number UN1219
Proper shipping name UN1219

Transport hazard class(es) 3
Packing group || I
DOT Marine Pollutant | NP

Description UN1219, Isopropanol, 3, II

Special Provisions IB2, T4, TP1

Emergency Response Guide 129

Number

TDG

UN number or ID number UN1219 UN proper shipping name UN1219

Transport hazard class(es) 3
Packing group ||

Description UN1219, Isopropanol, 3, II

MEX

UN number or ID number UN1219 UN proper shipping name Isopropanol

Transport hazard class(es) 3
Packing group ||

Description UN1219, Isopropanol, 3, II

ICAO (air)

UN number or ID number UN1219
UN proper shipping name Isopropanol

Transport hazard class(es)
Packing group

Description UN1219, Isopropanol, 3, II

Special Provisions A180

IATA

UN number or ID number UN1219

PTX394319VV - 81840 EXTREME REARVIEW MIRROR PROF STRENGTH ADHESIVE PART 2

UN proper shipping name Isopropanol

Transport hazard class(es) 3
Packing group II
ERG Code 3L
Special Provisions A180

Description UN1219, Isopropanol, 3, II

IMDG

UN number or ID number UN1219 UN proper shipping name Isopropanol

Transport hazard class(es) 3
Packing group

EmS-No. F-E, S-D

Description UN1219, Isopropanol, 3, II, (12°C c.c.)

15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

International Inventories

Complies **TSCA** Complies **DSL/NDSL** Complies **EINECS/ELINCS ENCS** Does not comply **IECSC** Complies Complies **KECI** Complies **PICCS AICS** Complies Complies **NZIoC**

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances **IECSC** - China Inventory of Existing Chemical Substances

KECL - Korean Existing Chemicals Inventory

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	SARA 313 - Threshold Values %		
2-PROPANOL - 67-63-0	1.0		
ORGANO-COPPER COMPOUND - 68084-48-0	1.0		

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical name	CWA - Reportable	CWA - Toxic Pollutants	CWA - Priority	CWA - Hazardous
	Quantities		Pollutants	Substances
ORGANO-COPPER COMPOUND 68084-48-0	-	X	-	-

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
2-PROPANOL	X	X	X
67-63-0			
ORGANO-COPPER COMPOUND	X	-	X
68084-48-0			

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. Other information

NFPA Health hazards 2 Flammability 3 Instability 0 Special hazards - Health hazards 2 Flammability 3 Physical hazards 0 Personal protection X Chronic Hazard Star Legend *= Chronic Health Hazard*

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend

SVHC: Substances of Very High Concern for Authorization:
PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances
vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances

STOT: Specific Target Organ Toxicity

ATE: Acute Toxicity Estimate LC50: 50% Lethal Concentration

LD50: 50% Lethal Dose

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value * Skin designation

+ Sensitizers

Key literature references and sources for data used to compile the SDS

U.S. Agency for Toxic Substances and Disease Registry (ATSDR) U.S. Environmental Protection Agency ChemView Database European Food Safety Authority (EFSA)

U.S. Environmental Protection Agency

Acute Exposure Guideline Level(s) (AEGL(s))

U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act

U.S. Environmental Protection Agency High Production Volume Chemicals

Food Research Journal

Hazardous Substance Database

International Uniform Chemical Information Database (IUCLID)

Japan National Institute of Technology and Evaluation (NITE)

Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)

NIOSH (National Institute for Occupational Safety and Health)

National Library of Medicine's ChemID Plus (NLM CIP)

National Library of Medicine's PubMed database (NLM PUBMED)

U.S. National Toxicology Program (NTP)

New Zealand's Chemical Classification and Information Database (CCID)

International Organization for Economic Co-operation and Development (OECD) Environment, Health, and Safety Publications International Organization for Economic Co-operation and Development (OECD) High Production Volume Chemicals Program International Organization for Economic Co-operation and Development (OECD) Screening Information Data Set

United Nations World Health Organization (WHO)

Revision Date 09-Jun-2025

Revision Note No information available.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.