



Toll Free: 87 PERMATEX  
(877-376-2839)

6875 Parkland Boulevard, Solon  
Ohio 44139

## Technical Data Sheet

# Permatex® Engine Oil Stop Leak

Revised 06/2023

### PRODUCT DESCRIPTION

Permatex® Engine Oil Stop Leak is formulated to help stop and prevent engine oil leaks and oil burning without dismantling. The stop leak can also be used as an additive to help swell and recondition the rubber and neoprene seals within your engine. Permatex® Engine Oil Stop Leak will assist in reducing engine noise, oil consumption and increase oil pressure decreasing the risk of future leaks. This formula is compatible with all minerals, synthetic, single and multigrade oils and suitable for regular and low SAPS applications.

### PRODUCT BENEFITS

- Prevents and stops engine oil leaks without dismantling.
- Reconditions rubber and neoprene seals of the crankshaft, camshaft, and valve stems.
- Compatible with all mineral, synthetic, single and multigrade oils.
- Suitable for regular and low SAPS applications.

### TYPICAL APPLICATIONS

- Petrol (gas), LPG, hybrid, and diesel engines.
- All rubber and neoprene seal rings in the engine.
- Valve steam seals
- Regular and low SAPS applications.

### DIRECTIONS FOR USE

1. At operating temperature or while engine is warm, add contents to engine oil with engine turned off.
2. Add the entire content of one can to the engine oil. Run engine to circulate and drive vehicle normally. (12 oz bottle treats up to 6 liters of engine oil)
3. Allow up to 200 miles (300 km) for Engine Oil Stop Leak to be fully effective.
4. If the leak persists, mechanical repairs may be necessary.
5. Application does not influence oil change intervals. Use at each oil change or as needed between oil changes.

### PROPERTIES

	Typical Value
Chemical Type	Petroleum
Appearance	Transparent yellow
Odor	Mild
Specific Gravity	0.85
Viscosity @100C	300 cps

### GENERAL INFORMATION

For safe handling information on this product, consult the Material Safety Data Sheet, (MSDS).

### ORDERING INFORMATION

Part Number	Container Size
30302	PX Engine Oil Stop Leak 12 oz

### STORAGE

Products shall be ideally stored in a cool, dry location in unopened containers at a temperature between 8° to 28°C (46° to 82°F) unless otherwise labeled. Optimal storage is at the lower half of this temperature range. To prevent contamination of unused product, do not return any material to its original container.

### NOTE

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. **Permatex, Inc. specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Permatex, Inc. products and disclaims any liability for consequential or incidental damages of any kind, including lost profits.** This product may be covered by one or more United States or foreign patents or patent applications.

NOT FOR PRODUCT SPECIFICATIONS.  
THE TECHNICAL DATA CONTAINED HEREIN ARE INTENDED AS REFERENCE ONLY.  
PLEASE CONTACT PERMATEX, INC., TECHNICAL SERVICE DEPARTMENT FOR ASSISTANCE AND RECOMMENDATIONS FOR YOUR SPECIFIC APPLICATION.  
PERMATEX, INC., 6875 PARKLAND BOULEVARD, SOLON, OH 44139 PHONE – (1-87PERMATEX) Revised 09/02