



Toll Free: 87 PERMATEX  
(877-376-2839)

6875 Parkland Boulevard, Solon  
Ohio 44139

## Technical Data Sheet

# Permatex® Power Steering Stop Leak

Revised 06/2023

### PRODUCT DESCRIPTION

Permatex® Power Steering Stop Leak is a professional product formulated to enhance the capability of your power steering fluid. A power steering system encounters high pressures and temperatures which can cause power steering fluid performance to deteriorate. This exceptional product increases the viscosity of the power steering fluid, while reducing squeaks that can often occur. Permatex® Power Steering Stop Leak extends your power steering fluid longevity, revitalizes seals and O-rings and prevents seal leaks. Not recommended for use in specialty or non-petroleum based synthetic fluids. Permatex® Power Steering Stop Leak cannot correct mechanical defects of malfunctions.

### PRODUCT BENEFITS

- Stops and prevents seal leaks without dismantling
- Extends power steering fluid life
- Revitalizes neoprene seals and O-rings
- Reduces noise and squeaks
- Prevents aging and oxidation of power steering oil
- Cleans and protects

### TYPICAL APPLICATIONS

- Conventional and automatic transmissions
- Compatible with synthetic and semi synthetic power steering fluids

### DIRECTIONS FOR USE

1. Allow engine and cooling system to cool. Remove the power steering dipstick and check the reservoir level.
2. Add 4 oz of Permatex® Power Steering Stop Leak into the power steering pump/reservoir. Do not overfill. If necessary, remove enough fluid from the reservoir to add 4 oz. (4 oz of stop leak treats 2 liters of power steering oil/fluid). Top off with power steering fluid as needed.
3. Drive the vehicle for 5-10 minutes to circulate the power steering fluid.
4. Allow up to 100 miles for Permatex® Power Steering Stop Leak to be fully effective.
5. If leak persists, a second application of Permatex® Power Steering Stop Leak should be used.

### PROPERTIES

	Typical Value
Chemical Type	Petroleum
Appearance	Clear to slight haze
Odor	Mild
Specific Gravity	0.88
Viscosity @100C	53 cps

### GENERAL INFORMATION

For safe handling information on this product, consult the Material Safety Data Sheet, (MSDS).

### ORDERING INFORMATION

Part Number	Container Size
30303	PX Power Steering Repair 12 oz

### STORAGE

Products shall be ideally stored in a cool, dry location in unopened containers at a temperature between 8° to 28°C (46° to 82°F) unless otherwise labeled. Optimal storage is at the lower half of this temperature range. To prevent contamination of unused product, do not return any material to its original container.

### NOTE

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. **Permatex, Inc. specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Permatex, Inc. products and disclaims any liability for consequential or incidental damages of any kind, including lost profits.** This product may be covered by one or more United States or foreign patents or patent applications.

NOT FOR PRODUCT SPECIFICATIONS.

THE TECHNICAL DATA CONTAINED HEREIN ARE INTENDED AS REFERENCE ONLY.  
PLEASE CONTACT PERMATEX, INC., TECHNICAL SERVICE DEPARTMENT FOR ASSISTANCE AND RECOMMENDATIONS FOR YOUR SPECIFIC APPLICATION.  
PERMATEX, INC., 6875 PARKLAND BOULEVARD, SOLON, OH 44139 PHONE - (1-87PERMATEX) Revised 09/02