



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:  
US OSHA Hazard Communication Standard (29 CFR 1910.1200)

Revision Date 09-Apr-2024

Version 9

## 1. IDENTIFICATION

### Product identifier

**Product Name** THE RIGHT STUFF GASKET MAKER 4 OZ AE

### Other means of identification

**Product Code** 25223

### Recommended use of the chemical and restrictions on use

**Recommended Use** Sealant

**Uses advised against** No information available

### Details of the supplier of the safety data sheet

#### Manufacturer Address

ITW Permatex, Inc.  
6875 Parkland Blvd.  
Solon, Ohio 44139 USA  
Telephone: 1-87-Permatex  
(866) 732-9502

#### May Also Be Distributed by:

ITW Permatex Canada  
101-2360 Bristol Circle  
Oakville, ON Canada L6H 6M5  
Telephone: (800) 924-6994

**Company Phone Number** 866-732-9502

#### 24-hour emergency phone number

Chem-Tel: 800-255-3924  
International Emergency:  
00+1+ 813-248-0585  
Contract Number: MIS0003453

**E-mail address:** mail@permatex.com

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Carcinogenicity	Category 1B
Specific target organ toxicity (single exposure)	Category 1
Specific target organ toxicity (repeated exposure)	Category 2
Gases under pressure	Compressed gas

### Label elements

#### Emergency Overview

**Signal word**

**Danger**

Causes serious eye irritation  
May cause an allergic skin reaction  
May cause cancer  
Causes damage to organs  
May cause damage to organs through prolonged or repeated exposure  
Contains gas under pressure; may explode if heated



**Appearance** Black

**Physical state** Paste / Gel Liquid

**Odor** Mild

**Precautionary Statements - Prevention**

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Use personal protective equipment as required  
Wash face, hands and any exposed skin thoroughly after handling  
Contaminated work clothing must not be allowed out of the workplace  
Wear protective gloves  
Do not breathe dust/fume/gas/mist/vapors/spray  
Do not pierce or burn, even after use  
Pressurized container may burst if heated

**Precautionary Statements - Response**

IF exposed: Call a POISON CENTER or doctor/physician

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
If eye irritation persists: Get medical advice/attention  
IF ON SKIN: Wash with plenty of soap and water  
If skin irritation or rash occurs: Get medical advice/attention  
Wash contaminated clothing before reuse

**Precautionary Statements - Storage**

Protect from sunlight. Do not expose to temperatures exceeding 49 °C/120 °F  
Store locked up

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

Not applicable

**Other Information**

May be harmful in contact with skin. Causes mild skin irritation.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical name	CAS No.	Weight-%
CALCIUM CARBONATE	471-34-1	25 - <50%
STEARIC ACID	57-11-4	1 - <2.5%
CARBON BLACK	1333-86-4	1 - <2.5%
2-BUTANONE OXIME	96-29-7	0.1 - <0.5%

#### 4. FIRST AID MEASURES

##### Description of first aid measures

<b>General advice</b>	Call 911 or emergency medical service. Remove and isolate contaminated clothing and shoes.
<b>Eye contact</b>	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.
<b>Skin contact</b>	In case of contact with liquefied gas, thaw frosted parts with lukewarm water.
<b>Inhalation</b>	Move victim to fresh air. If breathing is irregular or stopped, administer artificial respiration. Administer oxygen if breathing is difficult.
<b>Ingestion</b>	Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Call a physician. Do NOT induce vomiting.
<b>Self-protection of the first aider</b>	Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

##### Most important symptoms and effects, both acute and delayed

<b>Symptoms</b>	May cause allergic skin reaction.
-----------------	-----------------------------------

##### Indication of any immediate medical attention and special treatment needed

<b>Note to physicians</b>	Keep victim warm and quiet.
---------------------------	-----------------------------

#### 5. FIRE-FIGHTING MEASURES

##### Suitable extinguishing media

Use extinguishing agent suitable for type of surrounding fire, Dry chemical or CO<sub>2</sub>, Water spray, fog or regular foam, Move containers from fire area if you can do it without risk, Damaged cylinders should be handled only by specialists

**Small Fire** In case of fire, use water spray, foam, dry chemical, or CO<sub>2</sub>.

**Large Fire** In case of fire, use water spray, foam, dry chemical, or CO<sub>2</sub>.

##### Unsuitable extinguishing media

None

##### Specific hazards arising from the chemical

Some may burn but none ignite readily. Ruptured cylinders may rocket.

**Hazardous combustion products** No information available.

##### Explosion data

**Sensitivity to Mechanical Impact** None.

**Sensitivity to Static Discharge** None.

**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

**6. ACCIDENTAL RELEASE MEASURES****Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Do not touch or walk through spilled material. Stop leak if you can do it without risk.

**Other Information** Ventilate the area.

**For emergency responders** Use personal protection recommended in Section 8.

**Environmental precautions**

**Environmental precautions** Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material. Prevent entry into waterways, sewers, basements or confined areas. See section 12 for additional ecological information.

**Methods and material for containment and cleaning up**

**Methods for containment** If possible, turn leaking containers so that gas escapes rather than liquid. Allow substance to evaporate.

**Methods for cleaning up** Do not direct water at spill or source of leak.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

**7. HANDLING AND STORAGE****Precautions for safe handling**

**Advice on safe handling** Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin and eyes. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use personal protective equipment as required. Use with local exhaust ventilation. All equipment used when handling the product must be grounded. Do not breathe dust/fume/gas/mist/vapors/spray. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).

**Conditions for safe storage, including any incompatibilities**

**Storage Conditions** Store locked up. Protect from sunlight. Store in a well-ventilated place. Protect from moisture. Keep containers tightly closed in a cool, well-ventilated place. Keep away from heat. Keep in properly labeled containers.

**Packaging materials** No information available.

**Incompatible materials** Strong oxidizing agents

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Control parameters****Exposure Guidelines**

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
CALCIUM CARBONATE	-	-	TWA: 10 mg/m <sup>3</sup> total dust

471-34-1			TWA: 5 mg/m <sup>3</sup> respirable dust
STEARIC ACID 57-11-4	TWA: 10 mg/m <sup>3</sup> inhalable particulate matter TWA: 3 mg/m <sup>3</sup> respirable particulate matter	-	-
CARBON BLACK 1333-86-4	TWA: 3 mg/m <sup>3</sup> inhalable particulate matter	TWA: 3.5 mg/m <sup>3</sup> (vacated) TWA: 3.5 mg/m <sup>3</sup>	IDLH: 1750 mg/m <sup>3</sup> TWA: 3.5 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup> Carbon black in presence of Polycyclic aromatic hydrocarbons PAH

NIOSH IDLH Immediately Dangerous to Life or Health

### Appropriate engineering controls

**Engineering Controls**                      Showers  
   Eyewash stations  
   Ventilation systems

### Individual protection measures, such as personal protective equipment

**Eye/face protection**                      Tight sealing safety goggles.

**Skin and body protection**                Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.

**Respiratory protection**                    Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.

**General Hygiene Considerations**        When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

**Physical state**                                Paste / Gel Liquid  
**Appearance**                                Black  
**Odor**    Mild  
**Color**    Black  
**Odor threshold**                                No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	7-8	
Melting point / freezing point	No information available	
Boiling point / boiling range	No information available	Polymerization
Flash point	> 95 °C / > 203 °F	Tag Closed Cup
Evaporation rate	< 1	Butyl acetate = 1
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	No information available	
Lower flammability limit:	No information available	
Vapor pressure	<5 mmHg @ 70°F	
Vapor density	3	Air = 1
Relative density	1.34	
Water solubility	Not applicable	Polymerization
Solubility(ies)	No information available	
Partition coefficient	No information available	
Autoignition temperature	No information available	
Hyphen	No information available	
Kinematic viscosity	No information available	
Dynamic viscosity	No information available	

**Explosive properties** No information available  
**Oxidizing properties** No information available

**Other information**

**Softening point** No information available  
**Molecular weight** No information available  
**Density** No information available  
**Bulk density** No information available  
**SADT (self-accelerating decomposition temperature)** No information available

**10. STABILITY AND REACTIVITY****Reactivity**

No information available

**Chemical stability**

Stable under normal conditions

**Possibility of hazardous reactions**

None under normal processing.

**Hazardous polymerization**

No information available.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Strong oxidizing agents

**Hazardous decomposition products**

Carbon oxides

**11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

**Inhalation** May cause irritation of respiratory tract.  
**Eye contact** Contact with eyes may cause irritation. May cause redness and tearing of the eyes.  
**Skin contact** May cause skin irritation and/or dermatitis. May cause sensitization by skin contact.  
**Ingestion** Ingestion may cause irritation to mucous membranes.

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
CALCIUM CARBONATE 471-34-1	= 6450 mg/kg ( Rat )	> 2000 mg/kg ( Rat )	> 3 mg/L ( Rat ) 4 h
STEARIC ACID 57-11-4	= 4600 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	-
CARBON BLACK 1333-86-4	> 15400 mg/kg ( Rat )	> 2000 mg/kg ( Rat )	> 4.6 mg/m <sup>3</sup> ( Rat ) 4 h
2-BUTANONE OXIME 96-29-7	= 930 mg/kg ( Rat )	1000 - 1800 mg/kg ( Rabbit )	> 4.83 mg/L ( Rat ) 4 h

**Symptoms related to the physical, chemical and toxicological characteristics**

**Symptoms** No information available.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Serious eye damage/eye irritation** Causes serious eye irritation.  
**Sensitization** May cause sensitization by skin contact.  
**Germ cell mutagenicity** No information available.  
**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
CARBON BLACK 1333-86-4	A3	Group 2B	-	X

**Legend**

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - *Animal Carcinogen*

IARC (International Agency for Research on Cancer)

Group 2B - *Possibly Carcinogenic to Humans*

Occupational Safety and Health Administration of the US Department of Labor

X - *Present*

**Target organ effects** Eyes, Lymphatic System, Respiratory system, Skin.

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 6080 mg/kg

ATEmix (dermal) 4416 mg/kg

ATEmix (inhalation-dust/mist) 0.4 mg/l

**12. ECOLOGICAL INFORMATION****Ecotoxicity****Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility**

No information available.

Chemical name	Partition coefficient
2-BUTANONE OXIME 96-29-7	0.65

**Other adverse effects**

No information available

**13. DISPOSAL CONSIDERATIONS****Waste treatment methods**

**Disposal of wastes** Disposal should be in accordance with applicable regional, national and local laws and regulations.

**Contaminated packaging** Do not reuse container.

**US EPA Waste Number** Not applicable

This product contains one or more substances that are listed with the State of California as a hazardous waste.

#### 14. TRANSPORT INFORMATION

##### DOT

UN/ID No	UN 1950
Proper shipping name	Aerosols, Limited Quantity (LQ)
Transport hazard class(es)	2.2
Emergency Response Guide Number	126

##### IATA

UN number or ID number	ID 8000
Proper shipping name	Consumer commodity
Transport hazard class(es)	9
ERG Code	9L

##### IMDG

UN number or ID number	UN 1950
Proper shipping name	Aerosols, Limited Quantity (LQ)
Transport hazard class(es)	2.2
EmS-No	F-D, S-U

#### 15. REGULATORY INFORMATION

##### International Inventories

TSCA	Complies
DSL/NDL	Complies
EINECS/ELINCS	Does not comply
ENCS	Does not comply
IECSC	Complies
KECI	Complies
PICCS	Complies
AICS	Complies

##### Legend:

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDL** - Canadian Domestic Substances List/Non-Domestic Substances List  
**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**IECSC** - China Inventory of Existing Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances

##### US Federal Regulations

##### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

##### SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No



**CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

**CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

**US State Regulations****California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical name	California Proposition 65
CARBON BLACK 1333-86-4	*Carcinogen (airborne, unbound particles of respirable size)

- \*The asterisked chemical(s) listed are not subject to Proposition 65 because they are not airborne in the finished product

**U.S. State Right-to-Know Regulations**

Chemical name	New Jersey	Massachusetts	Pennsylvania
CARBON BLACK 1333-86-4	X	X	X
ALUMINIUM POWDER 7429-90-5	X	X	X

**U.S. EPA Label Information**

EPA Pesticide Registration Number Not applicable

**WHMIS Hazard Class**

A Compressed gases, D2B - Toxic materials

**16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION**

<b>NFPA</b>	Health hazards 2	Flammability 1	Instability 0	-
<b>HMIS</b>	Health hazards 2	Flammability 1	Physical hazards 0	Personal protection B

Revision Date 09-Apr-2024

**Disclaimer**

Illinois Tool Works Inc. believes the information contained in this data sheet is accurate as of the date compiled. However, Illinois Tool Works Inc. makes no warranty, express or implied, as to the accuracy, reliability or completeness of the information. User is responsible for evaluating whether such information or this product is fit for a particular purpose and suitable for a particular use or application. The information in this data sheet may not be valid if this product is used in combination with other products or in processes for which it was not designed. Illinois Tool Works Inc. disclaims any liability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of this product. Ensure you have the most current version of this data sheet by contacting us or reviewing our web site.

End of Safety Data Sheet