



# SAFETY DATA SHEET

Revision Date 24-Feb-2020

Version 7

## 1. IDENTIFICATION

### Product identifier

**Product Name** 122GA CHAIN LUBE 5 OZ AE

### Other means of identification

**Product Code** 80075

### Recommended use of the chemical and restrictions on use

**Recommended Use** Lubricant

**Uses advised against** No information available

### Details of the supplier of the safety data sheet

#### Manufacturer Address

ITW Permatex  
6875 Parkland Blvd.  
Solon, Ohio 44139 USA  
Telephone: 1-87-Permatex  
(866) 732-9502

#### 24-hour emergency phone number

Chem-Tel: 800-255-3924  
International Emergency:  
00+1+ 813-248-0585  
Contract Number: MIS0003453

#### May Also Be Distributed by:

ITW Permatex Canada  
101-2360 Bristol Circle  
Oakville, ON Canada L6H 6M5  
Telephone: (800) 924-6994

**E-mail address:** mail@permatex.com

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A
Aspiration toxicity	Category 1
Flammable liquids	Category 2
Gases under pressure	Liquefied gas

### Label elements

#### **Emergency Overview**

#### Signal word

**Danger**

May cause genetic defects  
May cause cancer  
May be fatal if swallowed and enters airways  
Highly flammable liquid and vapor  
Extremely flammable aerosol

Contains gas under pressure; may explode if heated



**Appearance** Brown

**Physical state** Liquid

**Odor** Mild

#### Precautionary Statements - Prevention

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use explosion-proof electrical/ ventilating/ lighting/ equipment  
 Use non-sparking tools  
 Take precautionary measures against static discharge

#### Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

In case of fire: Use CO<sub>2</sub>, dry chemical, or foam to extinguish.

#### Precautionary Statements - Storage

Store locked up  
 Store in a well-ventilated place. Keep cool

#### Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

Not applicable

#### Other Information

May be harmful in contact with skin. Harmful to aquatic life with long lasting effects. Harmful to aquatic life.

Unknown acute toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-47-8	10 - 30
PROPANE	74-98-6	5 - 10
BUTANE	106-97-8	5 - 10

### 4. FIRST AID MEASURES

#### Description of first aid measures

<b>General advice</b>	Call 911 or emergency medical service. Remove and isolate contaminated clothing and shoes.
<b>Eye contact</b>	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
<b>Skin contact</b>	In case of contact with liquefied gas, thaw frosted parts with lukewarm water.
<b>Inhalation</b>	Move victim to fresh air. If breathing is irregular or stopped, administer artificial respiration. Administer oxygen if breathing is difficult.
<b>Ingestion</b>	IF SWALLOWED: Call a physician or poison control center immediately. Do NOT induce vomiting. Rinse mouth.
<b>Self-protection of the first aider</b>	Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

**Most important symptoms and effects, both acute and delayed**

**Symptoms** See section 2 for more information.

**Indication of any immediate medical attention and special treatment needed**

**Note to physicians** Keep victim warm and quiet.

## 5. FIRE-FIGHTING MEASURES

**Suitable extinguishing media**

Use extinguishing agent suitable for type of surrounding fire, Dry chemical or CO<sub>2</sub>, Water spray, fog or regular foam, Move containers from fire area if you can do it without risk, Damaged cylinders should be handled only by specialists

**Unsuitable extinguishing media**

None

**Specific hazards arising from the chemical**

Some may burn but none ignite readily. Ruptured cylinders may rocket.

**Explosion data**

**Sensitivity to Mechanical Impact** None.

**Sensitivity to Static Discharge** None.

**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Do not touch or walk through spilled material. Stop leak if you can do it without risk.

**Other Information** Ventilate the area.

**Environmental precautions**

**Environmental precautions** Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material. Prevent entry into waterways, sewers, basements or confined areas.

**Methods and material for containment and cleaning up**

**Methods for containment** If possible, turn leaking containers so that gas escapes rather than liquid. Allow substance to evaporate.

**Methods for cleaning up** Do not direct water at spill or source of leak.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Advice on safe handling** Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly after handling. Contents under pressure. Remove all sources of ignition. Do not puncture or incinerate cans.

### Conditions for safe storage, including any incompatibilities

**Storage Conditions** Do not expose to temperatures exceeding 50 °C/122 °F. Store locked up.

**Incompatible materials** Strong oxidizing agents

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
PROPANE 74-98-6	: See Appendix F: Minimal Oxygen Content, explosion hazard	TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup> (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m <sup>3</sup>	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup>
BUTANE 106-97-8	STEL: 1000 ppm explosion hazard	(vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m <sup>3</sup>	IDLH: 1600 ppm TWA: 800 ppm TWA: 1900 mg/m <sup>3</sup>

NIOSH IDLH *Immediately Dangerous to Life or Health*

**Other Information** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

### Appropriate engineering controls

**Engineering Controls** Showers  
Eyewash stations  
Ventilation systems

### Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin and body protection** Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.

**Respiratory protection** Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.

**General Hygiene Considerations** Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

**Physical state** Liquid

Appearance Brown  
 Odor Mild  
 Odor threshold No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No information available	
Melting point / freezing point	No information available	
Boiling point / boiling range	> 38 °C / > 100 °F	
Flash point	-104 °C / -155 °F	Gives a flame projection at full valve opening or flashback at any degree of valve opening
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	9.5%	
Lower flammability limit:	1.9%	
Vapor pressure	No information available	
Vapor density	No information available	
Relative density	0.81	
Water solubility	No information available	
Solubility(ies)	No information available	
Partition coefficient	No information available	
Autoignition temperature	355°C (674°F)	
Decomposition temperature	No information available	
Kinematic viscosity	No information available	
Dynamic viscosity	No information available	
Explosive properties	No information available	
Oxidizing properties	No information available	

Other Information

Softening point No information available  
 Molecular weight No information available  
 VOC Content (%) 18  
 Density No information available  
 Bulk density No information available  
 SADT (self-accelerating decomposition temperature) No information available

## 10. STABILITY AND REACTIVITY

Reactivity  
 No information available

Chemical stability  
 Stable under normal conditions

Possibility of Hazardous Reactions  
 None under normal processing.

Conditions to avoid  
 Heat, flames and sparks.

Incompatible materials  
 Strong oxidizing agents

Hazardous Decomposition Products  
 Carbon oxides  
 Aldehydes

## 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

<b>Inhalation</b>	May cause irritation of respiratory tract.
<b>Eye contact</b>	Contact with eyes may cause irritation. May cause redness and tearing of the eyes.
<b>Skin contact</b>	May cause skin irritation and/or dermatitis.
<b>Ingestion</b>	Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT 64742-47-8	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 5.2 mg/L ( Rat ) 4 h
PROPANE 74-98-6	-	-	> 800000 ppm ( Rat ) 15 min
BUTANE 106-97-8	-	-	= 658 g/m <sup>3</sup> ( Rat ) 4 h

**Information on toxicological effects**

**Symptoms** No information available.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization** No information available.  
**Germ cell mutagenicity** No information available.  
**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.  
 ACGIH (American Conference of Governmental Industrial Hygienists)  
*A2 - Suspected Human Carcinogen*  
 IARC (International Agency for Research on Cancer)  
*Group 1 - Carcinogenic to Humans*  
 NTP (National Toxicology Program)  
*Known - Known Carcinogen*  
 OSHA (Occupational Safety and Health Administration of the US Department of Labor)  
*X - Present*

**Target Organ Effects** Central nervous system.

The following values are calculated based on chapter 3.1 of the GHS document .

<b>ATEmix (oral)</b>	6256 mg/kg
<b>ATEmix (dermal)</b>	3080 mg/kg
<b>ATEmix (inhalation-gas)</b>	1290847 mg/l

**12. ECOLOGICAL INFORMATION****Ecotoxicity**

2 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility**

No information available.

Chemical Name	Partition coefficient
PROPANE 74-98-6	2.3
BUTANE 106-97-8	2.89

**Other adverse effects**

No information available

**13. DISPOSAL CONSIDERATIONS****Waste treatment methods**

<b>Disposal of wastes</b>	Disposal should be in accordance with applicable regional, national and local laws and regulations.
<b>Contaminated packaging</b>	Do not reuse container.
<b>US EPA Waste Number</b>	D001

**14. TRANSPORT INFORMATION****DOT**

<b>UN/ID No</b>	1950
<b>Proper shipping name:</b>	Aerosols, Limited Quantity (LQ)
<b>Hazard Class</b>	2.1
<b>Emergency Response Guide Number</b>	126

**IATA**

<b>UN/ID No</b>	ID 8000
<b>Proper shipping name:</b>	Consumer commodity
<b>Hazard Class</b>	9
<b>ERG Code</b>	9L

**IMDG**

<b>UN/ID No</b>	1950
<b>Proper shipping name:</b>	Aerosols, Limited Quantity (LQ)
<b>Hazard Class</b>	2.1
<b>EmS-No</b>	F-D, S-U

**15. REGULATORY INFORMATION****International Inventories**

<b>TSCA</b>	Complies
<b>DSL/NDSL</b>	Complies
<b>EINECS/ELINCS</b>	Complies
<b>ENCS</b>	Not determined
<b>IECSC</b>	Complies
<b>KECL</b>	Complies
<b>PICCS</b>	Complies
<b>AICS</b>	Complies

**Legend:**

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List  
**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**IECSC** - China Inventory of Existing Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances

**US Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

**SARA 311/312 Hazard Categories**

Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

**CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

**CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

**US State Regulations****California Proposition 65**

This product contains the following Proposition 65 chemicals

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
BUTANE 106-97-8	X	X	X
PROPANE 74-98-6	X	X	X

**U.S. EPA Label Information**

EPA Pesticide Registration Number Not applicable

**WHMIS Hazard Class**

A Compressed gases, B5 - Flammable aerosol, D2B - Toxic materials

**16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION**

<b><u>NFPA</u></b>	Health hazards 2	Flammability 3	Instability 0	-
<b><u>HMIS</u></b>	Health hazards 2	Flammability 3	Physical hazards 0	Personal protection B

NFPA (National Fire Protection Association)

HMIS (Hazardous Material Information System)

Revision Date 24-Feb-2020

**Disclaimer**

Illinois Tool Works Inc. believes the information contained in this data sheet is accurate as of the date compiled. However, Illinois Tool Works Inc. makes no warranty, express or implied, as to the accuracy, reliability or completeness of the information. User is responsible for evaluating whether such information or this product is fit for a particular purpose and suitable for a particular use or application. The information in this data sheet may not be valid if this product is used in combination with other products or in processes for which it was not designed. Illinois Tool Works Inc. disclaims any liability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of this product. Ensure you have the most current version of this data sheet by contacting us or reviewing our web site.

**End of Safety Data Sheet**