



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
US OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada WHMIS
2015 which includes the amended Hazardous Products Act (HPA) and the Hazardous
Products Regulation (HPR)

Revision Date 10-Feb-2025

Version 1

1. Identification

Product identifier

Product Name 133MA ANTI-SEIZE LUBRICANT 8.5 OZ

Other means of identification

Product Code 81464

UN number or ID number 1950

Synonyms CAN Item Number 76765

Recommended use of the chemical and restrictions on use

Recommended Use Aerosol Lubricant

Restrictions on use No information available

Details of the supplier of the safety data sheet

Manufacturer Address

ITW Permatex, Inc.
6875 Parkland Blvd.
Solon, Ohio 44139 USA
Telephone: 1-87-Permatex
(866) 732-9502

May Also Be Distributed by:

ITW Permatex Canada
101-2360 Bristol Circle
Oakville, ON Canada L6H 6M5
Telephone: (800) 924-6994

E-mail address mail@permatex.com

Emergency telephone number

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924
International Emergency:
00+1+ 813-248-0585
Contract Number: MIS0003453

24-hour emergency phone number No information available

2. Hazard(s) identification

Classification

Aerosols	Category 1
Serious eye damage/eye irritation	Category 2A
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Specific target organ toxicity (single exposure)	Category 3
Aspiration hazard	Category 1

Label elements

Contains ACETONE; NAPHTHA (PETROLEUM), HYDROTREATED LIGHT; HEPTANE

**Danger****Hazard statements**

Extremely flammable aerosol.
Pressurized container: May burst if heated.
Causes serious eye irritation.
May cause genetic defects.
May cause cancer.
May cause drowsiness or dizziness.
May be fatal if swallowed and enters airways.

Precautionary Statements - Prevention

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Use personal protective equipment as required.
Wash face, hands and any exposed skin thoroughly after handling.
Avoid breathing dust, fume, gas, mist, vapors and spray.
Use only outdoors or in a well-ventilated area.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not spray on an open flame or other ignition source.
Do not pierce or burn, even after use.

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention.

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice and attention.

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
Do NOT induce vomiting.

Precautionary Statements - Storage

Store locked up.
Store in a well-ventilated place. Keep container tightly closed.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
Protect from sunlight.

Precautionary Statements - Disposal

Dispose of contents and container to an approved waste disposal plant.

37 % of the mixture consists of ingredient(s) of unknown acute oral toxicity.
29 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity.
100 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas).
100 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor).
35 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist).

Other Information

May be harmful if swallowed. Causes mild skin irritation. Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

3. Composition/information on ingredients

Substance

Not applicable.

Mixture**Synonyms** CAN Item Number 76765.

Chemical name	CAS No.	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
ACETONE	67-64-1	15-40%	-	-
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT	64742-49-0	10-30%	-	-
GRAPHITE	7782-42-5	7-13%	-	-
CALCIUM OXIDE	1305-78-8	7-13%	-	-
ALUMINIUM POWDER	7429-90-5	5-10%	-	-
HEPTANE	142-82-5	5-10%	-	-
CARBON DIOXIDE	124-38-9	5-10%	-	-

4. First-aid measures**Description of first aid measures****General advice**

Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention. Immediate medical attention is required.

Inhalation

Remove to fresh air. Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur.

Eye contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.

Skin contact

Wash skin with soap and water.

Ingestion

Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Get immediate medical attention.

Self-protection of the first aider

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8).

Most important symptoms and effects, both acute and delayed**Symptoms**

Difficulty in breathing. Coughing and/ or wheezing. Dizziness. May cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Prolonged contact may cause redness and irritation.

Effects of Exposure

May cause cancer. Mutagenic effects.

Indication of any immediate medical attention and special treatment needed

Note to physicians Because of the danger of aspiration, emesis or gastric lavage should not be employed unless the risk is justified by the presence of additional toxic substances.

5. Fire-fighting measures

Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Large Fire	CAUTION: Use of water spray when fighting fire may be inefficient.
Unsuitable extinguishing media	Do not scatter spilled material with high pressure water streams.
Specific hazards arising from the chemical	No information available.
Explosion data	
Sensitivity to mechanical impact	None.
Sensitivity to static discharge	None.
Special protective equipment and precautions for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions	Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Avoid contact with skin, eyes or clothing.
Other information	Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment	Prevent further leakage or spillage if safe to do so.
Methods for cleaning up	Pick up and transfer to properly labeled containers.
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.

7. Handling and storage

Precautions for safe handling

Advice on safe handling	Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Remove contaminated clothing and shoes. Ensure adequate ventilation. Avoid breathing vapors or mists. In case of insufficient ventilation, wear suitable respiratory equipment.
--------------------------------	---

Conditions for safe storage, including any incompatibilities

Storage Conditions	Store locked up. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach of children. Store away from other materials.
---------------------------	---

8. Exposure controls/personal protection

Control parameters

Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
ACETONE 67-64-1	TWA: 250 ppm STEL: 500 ppm	TWA: 1000 ppm TWA: 2400 mg/m ³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m ³ (vacated) STEL: 2400 mg/m ³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors. (vacated) STEL: 1000 ppm	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m ³
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT 64742-49-0	TWA: 100 ppm Sk*	-	-
GRAPHITE 7782-42-5	TWA: 2 mg/m ³ respirable particulate matter all forms except graphite fibers	TWA: 15 mg/m ³ total dust synthetic TWA: 5 mg/m ³ respirable fraction synthetic TWA: 15 mppcf respirable dust natural (vacated) TWA: 2.5 mg/m ³ respirable dust natural (vacated) TWA: 10 mg/m ³ total dust synthetic (vacated) TWA: 5 mg/m ³ respirable fraction synthetic TWA: 15 mppcf natural	IDLH: 1250 mg/m ³ TWA: 2.5 mg/m ³ natural respirable dust
CALCIUM OXIDE 1305-78-8	TWA: 2 mg/m ³	TWA: 5 mg/m ³ (vacated) TWA: 5 mg/m ³ not in effect as a result of reconsideration	IDLH: 25 mg/m ³ TWA: 2 mg/m ³
ALUMINIUM POWDER 7429-90-5	TWA: 1 mg/m ³ respirable particulate matter	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 5 mg/m ³ Al Aluminum	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust TWA: 5 mg/m ³ Al
HEPTANE 142-82-5	TWA: 400 ppm STEL: 500 ppm	TWA: 500 ppm TWA: 2000 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 1600 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 2000 mg/m ³	IDLH: 750 ppm Ceiling: 440 ppm 15 min Ceiling: 1800 mg/m ³ 15 min TWA: 85 ppm TWA: 350 mg/m ³
CARBON DIOXIDE 124-38-9	TWA: 5000 ppm STEL: 30000 ppm	TWA: 5000 ppm TWA: 9000 mg/m ³ (vacated) TWA: 10000 ppm (vacated) TWA: 18000 mg/m ³ (vacated) STEL: 30000 ppm (vacated) STEL: 54000 mg/m ³	IDLH: 40000 ppm TWA: 5000 ppm TWA: 9000 mg/m ³ STEL: 30000 ppm STEL: 54000 mg/m ³

Chemical name	Alberta	British Columbia	Ontario	Quebec
ACETONE 67-64-1	TWA: 500 ppm TWA: 1200 mg/m ³ STEL: 750 ppm STEL: 1800 mg/m ³	TWA: 250 ppm STEL: 500 ppm	TWA: 250 ppm STEL: 500 ppm	TWA: 500 ppm TWA: 1190 mg/m ³ STEL: 1000 ppm STEL: 2380 mg/m ³
GRAPHITE 7782-42-5	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³
CALCIUM OXIDE 1305-78-8	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³

ALUMINIUM POWDER 7429-90-5	TWA: 10 mg/m ³ TWA: 5 mg/m ³	TWA: 1.0 mg/m ³	TWA: 1 mg/m ³	TWA: 10 mg/m ³ TWA: 5 mg/m ³
HEPTANE 142-82-5	TWA: 400 ppm TWA: 1640 mg/m ³ STEL: 500 ppm STEL: 2050 mg/m ³	TWA: 400 ppm STEL: 500 ppm	TWA: 400 ppm STEL: 500 ppm	TWA: 400 ppm STEL: 500 ppm
CARBON DIOXIDE 124-38-9	TWA: 5000 ppm TWA: 9000 mg/m ³ STEL: 30000 ppm STEL: 54000 mg/m ³	TWA: 5000 ppm STEL: 15000 ppm	TWA: 5000 ppm STEL: 30000 ppm	TWA: 5000 ppm TWA: 9000 mg/m ³ STEL: 30000 ppm STEL: 54000 mg/m ³

Chemical name	Manitoba	New Brunswick	Newfoundland and Labrador	Nova Scotia
ACETONE	TWA: 250 ppm STEL: 500 ppm	TWA: 250 ppm STEL: 500 ppm	TWA: 250 ppm STEL: 500 ppm	TWA: 250 ppm STEL: 500 ppm
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT	TWA: 100 ppm Sk*		TWA: 100 ppm Sk*	TWA: 100 ppm Sk*
GRAPHITE	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³
CALCIUM OXIDE	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³
ALUMINIUM POWDER	TWA: 1 mg/m ³	TWA: 1 mg/m ³	TWA: 1 mg/m ³	TWA: 1 mg/m ³
HEPTANE	TWA: 400 ppm STEL: 500 ppm	TWA: 400 ppm STEL: 500 ppm	TWA: 400 ppm STEL: 500 ppm	TWA: 400 ppm STEL: 500 ppm
CARBON DIOXIDE	TWA: 5000 ppm STEL: 30000 ppm	TWA: 5000 ppm STEL: 30000 ppm	TWA: 5000 ppm STEL: 30000 ppm	TWA: 5000 ppm STEL: 30000 ppm

Chemical name	Nunavut	Prince Edward Island	Saskatchewan	Yukon
ACETONE	TWA: 500 ppm STEL: 750 ppm	TWA: 250 ppm STEL: 500 ppm	TWA: 500 ppm STEL: 750 ppm	TWA: 1000 ppm TWA: 2400 mg/m ³ STEL: 1250 ppm STEL: 3000 mg/m ³
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT		TWA: 100 ppm		
GRAPHITE	TWA: 2 mg/m ³ STEL: 4 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³ STEL: 4 mg/m ³	TWA: 20 mppcf TWA: 30 mppcf TWA: 10 mg/m ³
CALCIUM OXIDE	TWA: 2 mg/m ³ STEL: 4 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³ STEL: 4 mg/m ³	TWA: 2 mg/m ³ STEL: 4 mg/m ³
ALUMINIUM POWDER	TWA: 10 mg/m ³ STEL: 20 mg/m ³	TWA: 1 mg/m ³	TWA: 10 mg/m ³ STEL: 20 mg/m ³	
HEPTANE	TWA: 400 ppm STEL: 500 ppm	TWA: 400 ppm STEL: 500 ppm	TWA: 400 ppm STEL: 500 ppm	TWA: 400 ppm TWA: 1600 mg/m ³ STEL: 500 ppm STEL: 2000 mg/m ³
CARBON DIOXIDE	TWA: 5000 ppm STEL: 30000 ppm	TWA: 5000 ppm STEL: 30000 ppm	TWA: 5000 ppm STEL: 30000 ppm	TWA: 5000 ppm TWA: 9000 mg/m ³ STEL: 15000 ppm STEL: 27000 mg/m ³

Biological occupational exposure limits

Chemical name	ACGIH
ACETONE 67-64-1	25 mg/L - urine (Acetone) - end of shift

Appropriate engineering controls

Engineering controls

Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection	Wear safety glasses with side shields (or goggles).
Hand protection	Wear suitable gloves.
Skin and body protection	Wear suitable protective clothing.
Respiratory protection	Appropriate respiratory protection should be selected and used according to the chemical nature, hazards and use of this product and safety requirements of the local jurisdiction. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.
General hygiene considerations	Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.

9. Physical and chemical properties**Information on basic physical and chemical properties**

Physical state	Aerosol
Appearance	No information available
Color	Gray
Odor	Solvent
Odor threshold	No information available

Property	Values	Remarks • Method
pH	No data available	10% in deionized water
Melting point / freezing point	No data available	Estimated
Boiling point / boiling range	No data available	Polymerization
Flash point	< -18 °C / -0.4 °F	Gives a flame projection at full valve opening or flashback at any degree of valve opening
Evaporation rate	Not applicable	Butyl acetate = 1
Flammability (solid, gas)	No data available	Flammable in the presence of the following materials or conditions: open flames, sparks and static discharge.
Flammability Limit in Air		None known
Upper flammability limit:	No data available	
Lower flammability limit:	No data available	
Vapor pressure	No Data Available	mmHg
Vapor density	>1	Air = 1
Relative density	0.885-0.905	
Water solubility	No data available	Insoluble in water
Solubility(ies)	No Data Available	None known
Partition coefficient	No Data Available	None known
Autoignition temperature	No data available	Estimated
Decomposition temperature	No data available	Remarks: Self-Accelerating decomposition temperature (SADT): 50 °C SADT-Self Accelerating Decomposition Temperature. Lowest temperature at which the tested package size will undergo a self-accelerating decomposition reaction.
Kinematic viscosity	No Data Available	Kinematic viscosity at 100 degrees C
Dynamic viscosity	No data available	Remarks: Self-Accelerating decomposition temperature (SADT): 50 °C SADT-Self Accelerating Decomposition Temperature. Lowest temperature at which the tested package size will undergo a self-accelerating decomposition reaction.

Other information

Explosive properties	No information available
Oxidizing properties	No information available
Softening point	No information available
Molecular weight	No information available
VOC content	24.5%
Density	No information available
Bulk density	No information available

10. Stability and reactivity

Reactivity	No information available.
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	None under normal processing.
Conditions to avoid	None known based on information supplied.
Incompatible materials	None known based on information supplied.
Hazardous decomposition products	Carbon oxides. Copper compounds.

11. Toxicological information

Information on likely routes of exposure

Product Information

Inhalation	Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract. May cause drowsiness or dizziness.
Eye contact	Specific test data for the substance or mixture is not available. May cause irritation. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.
Skin contact	Repeated exposure may cause skin dryness or cracking. Specific test data for the substance or mixture is not available. Prolonged contact may cause redness and irritation. Causes mild skin irritation.
Ingestion	Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms	Difficulty in breathing. Coughing and/ or wheezing. Dizziness. May cause redness and tearing of the eyes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Prolonged contact may cause redness and irritation.
-----------------	--

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	4,329.40 mg/kg
ATEmix (dermal)	5,132.30 mg/kg
ATEmix (inhalation-gas)	99,999.00 ppm
ATEmix (inhalation-vapor)	99,999.00 mg/l
ATEmix (inhalation-dust/mist)	5.22 mg/l

37 % of the mixture consists of ingredient(s) of unknown acute oral toxicity
 29 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity
 100 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)
 100 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)
 35 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
ACETONE 67-64-1	= 5800 mg/kg (Rat)	> 15700 mg/kg (Rabbit)	= 50100 mg/m ³ (Rat) 8 h
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT 64742-49-0	> 5000 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 73680 ppm (Rat) 4 h
GRAPHITE 7782-42-5	-	-	> 2000 mg/m ³ (Rat) 4 h
CALCIUM OXIDE 1305-78-8	> 2000 mg/kg (Rat)	> 2500 mg/kg (Rat)	> 6.04 mg/L (Rat) 4 h
ALUMINIUM POWDER 7429-90-5	-	-	> 0.888 mg/L (Rat) 4 h
HEPTANE 142-82-5	-	= 3000 mg/kg (Rabbit)	> 29.29 mg/L (Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes mild skin irritation.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Respiratory or skin sensitization No information available.

Germ cell mutagenicity Contains a known or suspected mutagen. Classification based on data available for ingredients. May cause genetic defects.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT 64742-49-0	A3	-	-	-

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

Reproductive toxicity No information available.

STOT - single exposure May cause drowsiness or dizziness.

STOT - repeated exposure No information available.

Aspiration hazard May be fatal if swallowed and enters airways.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
ACETONE 67-64-1	-	LC50: 4.74 - 6.33mL/L (96h, Oncorhynchus mykiss) LC50: 6210 - 8120mg/L (96h, Pimephales promelas) LC50: =8300mg/L (96h, Lepomis macrochirus)	-	EC50: 10294 - 17704mg/L (48h, Daphnia magna) EC50: 12600 - 12700mg/L (48h, Daphnia magna)
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT 64742-49-0	-	LC50: =8.41mg/L (96h, Oncorhynchus mykiss)	-	-
GRAPHITE 7782-42-5	-	LC50: >100mg/L (96h, Danio rerio)	-	-
CALCIUM OXIDE 1305-78-8	-	LC50: =1070mg/L (96h, Cyprinus carpio)	-	-
HEPTANE 142-82-5	-	LC50: =375.0mg/L (96h, Cichlid fish)	-	-

Persistence and degradability No information available.

Bioaccumulation

Component Information

Chemical name	Partition coefficient
ACETONE 67-64-1	-0.24
HEPTANE 142-82-5	4.66

Other adverse effects No information available.

13. Disposal considerations

Waste treatment methods

Waste from residues/unused products Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Do not reuse empty containers.

US EPA Waste Number Waste designations and classifications should be determined by the end user based on the application for which the product was used.

14. Transport information

DOT

UN number or ID number 1950
 Proper shipping name Limited Quantity (LQ) Alcohols, n.o.s.
 Transport hazard class(es) 2.1
 Emergency Response Guide Number 126

TDG

UN number or ID number 1950
 UN proper shipping name Aerosols, Limited Quantity (LQ)
 Transport hazard class(es) 2.1

MEX

UN number or ID number 1950
 UN proper shipping name Aerosols, Limited Quantity (LQ)
 Transport hazard class(es) 2.1

IATA

UN number or ID number ID 8000
 UN proper shipping name Consumer Commodity
 Transport hazard class(es) 9

IMDG

UN number or ID number 1950
 UN proper shipping name Aerosols Limited Quantity (LQ)
 Transport hazard class(es) 2.1

15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Does not comply
IECSC	Complies
KECI	Complies
PICCS	Complies
AICS	Complies
NZIoC	Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing Chemicals Inventory
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances
NZIoC - New Zealand Inventory of Chemicals

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	SARA 313 - Threshold Values %

ALUMINIUM POWDER - 7429-90-5	1.0
------------------------------	-----

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	Reportable Quantity (RQ)
ACETONE 67-64-1	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
ACETONE 67-64-1	X	X	X
GRAPHITE 7782-42-5	X	X	X
ALUMINIUM POWDER 7429-90-5	X	X	X
HEPTANE 142-82-5	X	X	X
CARBON DIOXIDE 124-38-9	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. Other information

NFPA	Health hazards 2	Flammability 4	Instability 0	Special hazards -
HMIS	Health hazards 3*	Flammability 0	Physical hazards 0	Personal protection X
Chronic Hazard Star Legend	* = Chronic Health Hazard			

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend

- SVHC: Substances of Very High Concern for Authorization:
- PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances
- vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances
- STOT: Specific Target Organ Toxicity
- ATE: Acute Toxicity Estimate
- LC50: 50% Lethal Concentration
- LD50: 50% Lethal Dose

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
+	Sensitizers		

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR)
U.S. Environmental Protection Agency ChemView Database
European Food Safety Authority (EFSA)
Environmental Protection Agency
Acute Exposure Guideline Level(s) (AEGl(s))
U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
U.S. Environmental Protection Agency High Production Volume Chemicals
Food Research Journal
Hazardous Substance Database
International Uniform Chemical Information Database (IUCLID)
National Institute of Technology and Evaluation (NITE)
Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)
NIOSH (National Institute for Occupational Safety and Health)
National Library of Medicine's ChemID Plus (NLM CIP)
National Library of Medicine's PubMed database (NLM PUBMED)
U.S. National Toxicology Program (NTP)
New Zealand's Chemical Classification and Information Database (CCID)
Organization for Economic Co-operation and Development Environment, Health, and Safety Publications
Organization for Economic Co-operation and Development High Production Volume Chemicals Program
Organization for Economic Co-operation and Development Screening Information Data Set
World Health Organization

Revision Date 10-Feb-2025

Revision Note No information available.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.