



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
US OSHA Hazard Communication Standard (29 CFR 1910.1200)

Revision Date 17-Jul-2024

Version 6

1. IDENTIFICATION

Product identifier

Product Name ULTRA BLACK GASKET MAKER 8.75OZ AE

Other means of identification

Product Code 82080

Recommended use of the chemical and restrictions on use

Recommended Use Sealant

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address

ITW Permatex, Inc.
6875 Parkland Blvd.
Solon, Ohio 44139 USA
Telephone: 1-87-Permatex
(866) 732-9502

24-hour emergency phone number

Chem-Tel: 800-255-3924
International Emergency:
00+1+ 813-248-0585
Contract Number: MIS0003453

E-mail address: mail@permatex.com

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Carcinogenicity	Category 2
Gases under pressure	Compressed gas

Label elements

Emergency Overview

Signal word

Warning

Causes serious eye irritation
May cause an allergic skin reaction
Suspected of causing cancer
Contains gas under pressure; may explode if heated



Appearance Black **Physical state** Paste / Gel Liquid **Odor** Mild

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Wash face, hands and any exposed skin thoroughly after handling
Avoid breathing dust/fume/gas/mist/vapors/spray
Contaminated work clothing must not be allowed out of the workplace
Wear protective clothing, gloves, and eye protection or face shield

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

IF ON SKIN: Wash with plenty of soap and water

If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

Precautionary Statements - Storage

Protect from sunlight. Do not expose to temperatures exceeding 49 °C/120 °F

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

Harmful to aquatic life with long lasting effects.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No.	Weight-%
CALCIUM CARBONATE	471-34-1	25 - <50%
LIMESTONE	1317-65-3	10 - <25%
STEARIC ACID	57-11-4	1 - <2.5%
CARBON BLACK	1333-86-4	0.5 - <1%
2-BUTANONE OXIME	96-29-7	0.1 - <0.5%

4. FIRST AID MEASURES

Description of first aid measures

General advice	Call 911 or emergency medical service. Remove and isolate contaminated clothing and shoes.
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.
Skin contact	In case of contact with liquefied gas, thaw frosted parts with lukewarm water.
Inhalation	Move victim to fresh air. If breathing is irregular or stopped, administer artificial respiration. Administer oxygen if breathing is difficult.
Ingestion	Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Call a physician. Do NOT induce vomiting.
Self-protection of the first aider	Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

Most important symptoms and effects, both acute and delayed

Symptoms See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

Note to physicians Keep victim warm and quiet.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing agent suitable for type of surrounding fire, Dry chemical or CO₂, Water spray, fog or regular foam, Move containers from fire area if you can do it without risk, Damaged cylinders should be handled only by specialists

Unsuitable extinguishing media

None

Specific hazards arising from the chemical

Some may burn but none ignite readily. Ruptured cylinders may rocket.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Do not touch or walk through spilled material. Stop leak if you can do it without risk.

Other Information Ventilate the area.

Environmental precautions

Environmental precautions Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material. Prevent entry into waterways, sewers, basements or confined

areas.

Methods and material for containment and cleaning up

- Methods for containment** If possible, turn leaking containers so that gas escapes rather than liquid. Allow substance to evaporate.
- Methods for cleaning up** Do not direct water at spill or source of leak.
- Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash contaminated clothing before reuse. Use personal protective equipment as required. Contents under pressure. Do not puncture or incinerate cans. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use with local exhaust ventilation. All equipment used when handling the product must be grounded. Do not breathe dust/fume/gas/mist/vapors/spray. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).

Conditions for safe storage, including any incompatibilities

- Storage Conditions** Protect from moisture. Protect from sunlight. Store in a well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep containers tightly closed in a cool, well-ventilated place. Keep away from heat. Keep in properly labeled containers.
- Incompatible materials** Strong oxidizing agents, Acids, Water

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
CALCIUM CARBONATE 471-34-1	-	-	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
LIMESTONE 1317-65-3	-	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
STEARIC ACID 57-11-4	TWA: 10 mg/m ³ inhalable particulate matter TWA: 3 mg/m ³ respirable particulate matter	-	-
CARBON BLACK 1333-86-4	TWA: 3 mg/m ³ inhalable particulate matter	TWA: 3.5 mg/m ³ (vacated) TWA: 3.5 mg/m ³	IDLH: 1750 mg/m ³ TWA: 3.5 mg/m ³ TWA: 0.1 mg/m ³ Carbon black in presence of Polycyclic aromatic hydrocarbons PAH

NIOSH IDLH *Immediately Dangerous to Life or Health*

Appropriate engineering controls

- Engineering Controls** Showers

Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.
Skin and body protection Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.
Respiratory protection Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.

General Hygiene Considerations When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state Paste / Gel Liquid
Appearance Black
Odor Mild
Odor threshold No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No information available	
Melting point / freezing point	No information available	
Boiling point / boiling range	No information available	Polymerization
Flash point	> 93 °C / > 199 °F	
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	No information available	
Lower flammability limit:	No information available	
Vapor pressure	<5 mmHg	
Vapor density	>1	Air = 1
Relative density	1.44	
Water solubility	Not applicable	Polymerization
Solubility(ies)	No information available	
Partition coefficient	No information available	
Autoignition temperature	No information available	
Hyphen	No information available	
Kinematic viscosity	No information available	
Dynamic viscosity	No information available	
Explosive properties	No information available	
Oxidizing properties	No information available	

Other information
Softening point No information available
Molecular weight No information available
Density No information available
Bulk density No information available
SADT (self-accelerating decomposition temperature) No information available

10. STABILITY AND REACTIVITY

Reactivity
No information available

Chemical stability

Stable under normal conditions

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents, Acids, Water

Hazardous decomposition products

Carbon oxides

Nitrogen oxides (NO_x)

Formaldehyde

May release 2-butanone oxime (ethyl methyl ketoxime) at elevated temperature

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation	May cause irritation of respiratory tract.
Eye contact	Contact with eyes may cause irritation. May cause redness and tearing of the eyes.
Skin contact	May cause skin irritation and/or dermatitis. May cause sensitization by skin contact.
Ingestion	Ingestion may cause irritation to mucous membranes.

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
CALCIUM CARBONATE 471-34-1	= 6450 mg/kg (Rat)	> 2000 mg/kg (Rat)	> 3 mg/L (Rat) 4 h
STEARIC ACID 57-11-4	= 4600 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	-
CARBON BLACK 1333-86-4	> 15400 mg/kg (Rat)	> 2000 mg/kg (Rat)	> 4.6 mg/m ³ (Rat) 4 h
2-BUTANONE OXIME 96-29-7	= 930 mg/kg (Rat)	1000 - 1800 mg/kg (Rabbit)	> 4.83 mg/L (Rat) 4 h

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
CARBON BLACK 1333-86-4	A3	Group 2B	-	X

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - *Animal Carcinogen*

IARC (International Agency for Research on Cancer)

Group 2B - *Possibly Carcinogenic to Humans*

Occupational Safety and Health Administration of the US Department of Labor

X - *Present*

Target organ effects Eyes, Respiratory system, Skin.

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 13849 mg/kg
ATEmix (dermal) 22776 mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicity

0.054 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

Chemical name	Partition coefficient
2-BUTANONE OXIME 96-29-7	0.65

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number Not applicable

This product contains one or more substances that are listed with the State of California as a hazardous waste.

14. TRANSPORT INFORMATION

DOT

UN/ID No 1950
Proper shipping name Aerosols, Limited Quantity (LQ)
Transport hazard class(es) 2.2
Emergency Response Guide Number 126

IATA

UN number or ID number ID 8000
Proper shipping name Consumer commodity
Transport hazard class(es) 9
ERG Code 9L

IMDG

UN number or ID number 1950
 Proper shipping name Aerosols, Limited Quantity (LQ)
 Transport hazard class(es) 2.2
 EmS-No F-D, S-U

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
 DSL/NDSL Complies
 EINECS/ELINCS Not determined
 ENCS Not determined
 IECSC Complies
 KECI Complies
 PICCS Complies
 AICS Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
 EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
 ENCS - Japan Existing and New Chemical Substances
 IECSC - China Inventory of Existing Chemical Substances
 KECI - Korean Existing and Evaluated Chemical Substances
 PICCS - Philippines Inventory of Chemicals and Chemical Substances
 AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute health hazard Yes
 Chronic Health Hazard No
 Fire hazard Yes
 Sudden release of pressure hazard No
 Reactive Hazard No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical name	California Proposition 65
CARBON BLACK 1333-86-4	*Carcinogen (airborne, unbound particles of respirable size)

*The asterisked chemical(s) listed are not subject to Proposition 65 because they are not airborne in the finished product

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
LIMESTONE 1317-65-3	X	X	X
NITROGEN 7727-37-9	X	X	X
ALUMINIUM POWDER 7429-90-5	X	X	X
CARBON BLACK 1333-86-4	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

D2A - Very toxic materials

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

<u>NFPA</u>	Health hazards 2	Flammability 2	Instability 0	-
<u>HMIS</u>	Health hazards 2	Flammability 2	Physical hazards 0	Personal protection B

Revision Date 17-Jul-2024

Disclaimer

Illinois Tool Works Inc. believes the information contained in this data sheet is accurate as of the date compiled. However, Illinois Tool Works Inc. makes no warranty, express or implied, as to the accuracy, reliability or completeness of the information. User is responsible for evaluating whether such information or this product is fit for a particular purpose and suitable for a particular use or application. The information in this data sheet may not be valid if this product is used in combination with other products or in processes for which it was not designed. Illinois Tool Works Inc. disclaims any liability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of this product. Ensure you have the most current version of this data sheet by contacting us or reviewing our web site.

End of Safety Data Sheet