



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:  
US OSHA Hazard Communication Standard (29 CFR 1910.1200)

Revision Date 28-Aug-2023

Version 5

## 1. IDENTIFICATION

### Product identifier

**Product Name** NON-CHLORINATED BRAKE & PARTS CLEANER 14.5OZ

### Other means of identification

**Product Code** 82450

### Recommended use of the chemical and restrictions on use

**Recommended Use** Brake Cleaner

**Uses advised against** No information available

### Details of the supplier of the safety data sheet

#### Manufacturer Address

ITW Permatex, Inc.  
6875 Parkland Blvd.  
Solon, Ohio 44139 USA  
Telephone: 1-87-Permatex  
(866) 732-9502

#### 24-hour emergency phone number

Chem-Tel: 800-255-3924  
International Emergency:  
00+1+ 813-248-0585  
Contract Number: MIS0003453

**E-mail address:** mail@permatex.com

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable aerosols	Category 1
Gases under pressure	Dissolved gas

### Label elements

#### **Emergency Overview**

#### **Signal word**

**Danger**

Causes skin irritation  
Causes serious eye irritation

May cause respiratory irritation  
May cause drowsiness or dizziness  
May be fatal if swallowed and enters airways  
Extremely flammable aerosol  
Contains gas under pressure; may explode if heated



**Appearance** Clear

**Physical state** Liquid

**Odor** Solvent

**Precautionary Statements - Prevention**

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Use personal protective equipment as required  
Wash face, hands and any exposed skin thoroughly after handling  
Do not eat, drink or smoke when using this product  
Avoid breathing dust/fume/gas/mist/vapors/spray  
Use only outdoors or in a well-ventilated area  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
Do not spray on an open flame or other ignition source  
Do not pierce or burn, even after use  
Pressurized container may burst if heated

**Precautionary Statements - Response**

If exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
If eye irritation persists: Get medical advice/attention  
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
If skin irritation occurs: Get medical advice/attention  
Wash contaminated clothing before reuse  
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
Call a POISON CENTER or doctor/physician if you feel unwell  
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
Do NOT induce vomiting  
IN CASE OF FIRE: Use CO<sub>2</sub>, dry chemical, or foam to extinguish.

**Precautionary Statements - Storage**

Protect from sunlight. Do not expose to temperatures exceeding 49 °C/120 °F  
Store in a well-ventilated place. Keep container tightly closed  
Store locked up

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

Not applicable

**Other Information**

Toxic to aquatic life with long lasting effects. Toxic to aquatic life.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
ACETONE	67-64-1	70-90
HEPTANE	142-82-5	7 - 13
CARBON DIOXIDE	124-38-9	5 - 10

### 4. FIRST AID MEASURES

#### Description of first aid measures

<b>General advice</b>	Get medical advice/attention if you feel unwell.
<b>Eye contact</b>	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
<b>Skin contact</b>	IF ON SKIN: Wash skin with soap and water. If skin irritation persists, call a physician. Take off contaminated clothing and wash before reuse.
<b>Inhalation</b>	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, call a physician.
<b>Ingestion</b>	IF SWALLOWED: Call a physician or poison control center immediately. Do NOT induce vomiting.
<b>Self-protection of the first aider</b>	Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

#### Most important symptoms and effects, both acute and delayed

**Symptoms** See section 2 for more information.

#### Indication of any immediate medical attention and special treatment needed

**Note to physicians** Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

#### Suitable extinguishing media

Carbon dioxide (CO<sub>2</sub>), Use dry chemical, Foam

#### Unsuitable extinguishing media

None

#### Specific hazards arising from the chemical

Extremely flammable. Contains gas under pressure; may explode if heated. Vapors may travel to source of ignition and flash back.

#### Explosion data

**Sensitivity to Mechanical Impact** None.  
**Sensitivity to Static Discharge** None.

#### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Ensure adequate ventilation, especially in confined areas. Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Contents under pressure. Do not puncture or incinerate cans. Remove all sources of ignition.

### Environmental precautions

**Environmental precautions** See section 12 for additional ecological information. Do not flush into surface water or sanitary sewer system.

### Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up** Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Advice on safe handling** Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Wash contaminated clothing before reuse. Wash thoroughly after handling. Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Contents under pressure. Do not puncture or incinerate cans.

### Conditions for safe storage, including any incompatibilities

**Storage Conditions** Protect from sunlight. Do not expose to temperatures exceeding 49 °C/120 °F. Store locked up. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

**Incompatible materials** Strong oxidizing agents, Amines, Acids

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
ACETONE 67-64-1	STEL: 500 ppm TWA: 250 ppm	TWA: 1000 ppm TWA: 2400 mg/m <sup>3</sup> (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m <sup>3</sup> (vacated) STEL: 2400 mg/m <sup>3</sup> The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors. (vacated) STEL: 1000 ppm	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m <sup>3</sup>
HEPTANE 142-82-5	STEL: 500 ppm TWA: 400 ppm	TWA: 500 ppm TWA: 2000 mg/m <sup>3</sup> (vacated) TWA: 400 ppm (vacated) TWA: 1600 mg/m <sup>3</sup> (vacated) STEL: 500 ppm	IDLH: 750 ppm Ceiling: 440 ppm 15 min Ceiling: 1800 mg/m <sup>3</sup> 15 min TWA: 85 ppm TWA: 350 mg/m <sup>3</sup>

		(vacated) STEL: 2000 mg/m <sup>3</sup>	
CARBON DIOXIDE 124-38-9	STEL: 30000 ppm TWA: 5000 ppm	TWA: 5000 ppm TWA: 9000 mg/m <sup>3</sup> (vacated) TWA: 10000 ppm (vacated) TWA: 18000 mg/m <sup>3</sup> (vacated) STEL: 30000 ppm (vacated) STEL: 54000 mg/m <sup>3</sup>	IDLH: 40000 ppm TWA: 5000 ppm TWA: 9000 mg/m <sup>3</sup> STEL: 30000 ppm STEL: 54000 mg/m <sup>3</sup>

NIOSH IDLH *Immediately Dangerous to Life or Health*

**Appropriate engineering controls**

**Engineering Controls**                      Showers  
   Eyewash stations  
   Ventilation systems

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**                      Wear safety glasses with side shields (or goggles).

**Skin and body protection**                Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.

**Respiratory protection**                    Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.

**General Hygiene Considerations**      Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**9.1. Information on basic physical and chemical properties**

**Physical state**                                Liquid  
**Appearance**                                Clear  
**Odor**    Solvent  
**Odor threshold**                              No information available

<u>Property</u>	<u>Values</u>
pH	No information available
Melting point / freezing point	No information available
Boiling point / boiling range	56 °C / 133 °F
Flash point	-17 °C / 1 °F
Evaporation rate	No information available
Flammability (solid, gas)	No information available
Flammability Limit in Air	
Upper flammability limit:	12.8%
Lower flammability limit:	2.5%
Vapor pressure	No information available
Vapor density	No information available
Relative density	0.8
Water solubility	No information available
Solubility(ies)	No information available
Partition coefficient	No information available
Autoignition temperature	No information available
Hyphen	No information available
Kinematic viscosity	No information available
Dynamic viscosity	No information available
Explosive properties	No information available
Oxidizing properties	No information available

**Remarks • Method**

Gives a flame projection at full valve opening or flashback at any degree of valve opening

**Other information**

**Softening point** No information available  
**Molecular weight** No information available  
**VOC content** 10%  
**Density** No information available  
**Bulk density** No information available  
**SADT (self-accelerating decomposition temperature)** No information available

**10. STABILITY AND REACTIVITY**

**Reactivity**

No information available

**Chemical stability**

Stable under normal conditions

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks. Temperatures >50 °C / 122 °F.

**Incompatible materials**

Strong oxidizing agents, Amines, Acids

**Hazardous decomposition products**

Carbon oxides

**11. TOXICOLOGICAL INFORMATION**

**Information on likely routes of exposure**

**Inhalation** May cause irritation of respiratory tract. May cause drowsiness or dizziness.  
**Eye contact** Contact with eyes may cause irritation. May cause redness and tearing of the eyes.  
**Skin contact** May cause skin irritation and/or dermatitis.  
**Ingestion** Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis.

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
ACETONE 67-64-1	= 5800 mg/kg ( Rat )	> 15700 mg/kg ( Rabbit )	= 50100 mg/m <sup>3</sup> ( Rat ) 8 h
HEPTANE 142-82-5	-	= 3000 mg/kg ( Rabbit )	> 73.5 mg/L ( Rat ) 4 h

**Symptoms related to the physical, chemical and toxicological characteristics**

**Symptoms** No information available.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization** No information available.  
**Germ cell mutagenicity** No information available.  
**Carcinogenicity** No information available.  
**Target organ effects** Central nervous system, Central Vascular System (CVS), Eyes, Respiratory system, Skin.

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 7250 mg/kg  
ATEmix (dermal) 11871 mg/kg  
ATEmix (inhalation-dust/mist) 101 mg/l

## 12. ECOLOGICAL INFORMATION

This product contains a chemical which is listed as a marine pollutant according to DOT.

### Ecotoxicity

3 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

### Persistence and degradability

No information available.

### Bioaccumulation

No information available.

### Mobility

No information available.

Chemical name	Partition coefficient
ACETONE 67-64-1	-0.24
HEPTANE 142-82-5	4.66

### Other adverse effects

No information available

## 13. DISPOSAL CONSIDERATIONS

### Waste treatment methods

**Disposal of wastes** This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

**Contaminated packaging** Do not reuse container.

**US EPA Waste Number** D001

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste Status
ACETONE 67-64-1	Ignitable
HEPTANE 142-82-5	Toxic Ignitable

## 14. TRANSPORT INFORMATION

### DOT

UN/ID No 1950  
Proper shipping name Aerosols, Limited Quantity (LQ)  
Transport hazard class(es) 2.1

**Marine pollutant** This product contains a chemical which is listed as a marine pollutant according to DOT.  
**Emergency Response Guide** 126  
**Number**

**IATA**

**UN number or ID number** ID 8000  
**Proper shipping name** Consumer commodity  
**Transport hazard class(es)** 9  
**ERG Code** 9L

**IMDG**

**UN number or ID number** 1950  
**Proper shipping name** Aerosols, Limited Quantity (LQ)  
**Transport hazard class(es)** 2.1  
**EmS-No** F-D, S-U  
**Marine pollutant** This product contains a chemical which is listed as a marine pollutant according to IMDG/IMO.

**15. REGULATORY INFORMATION**

**International Inventories**

**TSCA** Complies  
**DSL/NDSL** Complies  
**EINECS/ELINCS** Complies  
**ENCS** Complies  
**IECSC** Complies  
**KECL** Complies  
**PICCS** Complies  
**AICS** Complies

**Legend:**

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List  
**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**IECSC** - China Inventory of Existing Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances

**US Federal Regulations**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

**SARA 311/312 Hazard Categories**

**Acute health hazard** Yes  
**Chronic Health Hazard** No  
**Fire hazard** Yes  
**Sudden release of pressure hazard** No  
**Reactive Hazard** No

**CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive



Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
ACETONE 67-64-1	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ

**US State Regulations**

**California Proposition 65**

This product contains the following Proposition 65 chemicals

**U.S. State Right-to-Know Regulations**

Chemical name	New Jersey	Massachusetts	Pennsylvania
ACETONE 67-64-1	X	X	X

**U.S. EPA Label Information**

**EPA Pesticide Registration Number** Not applicable

**WHMIS Hazard Class**

A Compressed gases, B5 - Flammable aerosol, D2B - Toxic materials

**16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION**

<b><u>NFPA</u></b>	<b>Health hazards</b> 2	<b>Flammability</b> 3	<b>Instability</b> 0	-
<b><u>HMIS</u></b>	<b>Health hazards</b> 2	<b>Flammability</b> 3	<b>Physical hazards</b> 0	<b>Personal protection</b> B

NFPA (National Fire Protection Association)  
HMIS (Hazardous Material Information System)

**Revision Date** 28-Aug-2023

**Disclaimer**

Illinois Tool Works Inc. believes the information contained in this data sheet is accurate as of the date compiled. However, Illinois Tool Works Inc. makes no warranty, express or implied, as to the accuracy, reliability or completeness of the information. User is responsible for evaluating whether such information or this product is fit for a particular purpose and suitable for a particular use or application. The information in this data sheet may not be valid if this product is used in combination with other products or in processes for which it was not designed. Illinois Tool Works Inc. disclaims any liability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of this product. Ensure you have the most current version of this data sheet by contacting us or reviewing our web site.

**End of Safety Data Sheet**