

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 as amended by Regulation (EU) No. 2020/878, and Regulation (EC) No. 1272/2008

Revision Date 14-Oct-2024 Version 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Code 22072

Product Name SENSOR-SAFE VALVE COVER AND OIL PAN OEM RTV .50Z TB CG

Other means of identification

Unique Formula Identifier (UFI) KJPH-U0GG-U00W-8KSK

Mixture. Contains 2-BUTANONE OXIME

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Sealant

Uses advised against No information available

1.3. Details of the supplier of the safety data sheet

Manufacturer Only Representative (OR)

ITW Permatex, Inc. ITW Permatex, Inc.

6875 Parkland Blvd. Bay 150

Solon, Ohio 44139 USA Shannon Industrial Estate

Telephone: 1-87-Permatex Co. Clare (866) 732-9502 Ireland V14 DF82

V14 DF82 353(61)771500 353(61)471285

customerservice.shannon@itwpp.com

For further information, please contact

Contact Point ITW Permatex

6875 Parkland Blvd. Solon, Ohio 44139 USA Telephone: 1-87-Permatex

(866) 732-9502

E-mail address: mail@permatex.com

Non-Emergency Telephone Number 866-732-9502

1.4. Emergency telephone number

24-hour emergency phone number EU Member States information as follows:

24-hour emergency phone number	- §45 - (EC)1272/2008
Europe	112
Austria	01 406 43 43

Belgium	070 245 245
Bulgaria	+359 2 9154 233
Croatia	+3851 2348 342
Cyprus	1401
Czech Republic	+420 224 919 293/ +420 224 915 402
Denmark	+ 45 8212 1212
Estonia	16662/ (+372) 7943 794
Finland	0800 147 111/ 09 471 977
France	+33 (0)1 45 42 59 59
Germany	+49 228 192 40
Greece	(003) 2107793777
Hungary	+36 80 201 199
Iceland	543 2222
Ireland	01 809 2166
Italy	0382-24444
Latvia	+371 67042473
Liechtenstein	01 406 43 43
Lithuania	+370 (85) 2362052
Luxembourg	(+352) 8002 5500
Malta	112
Netherlands	+31 (0)88 755 8000
Norway	22 59 13 00
Poland	112
Portugal	+351 800 250 250
Romania	+40213183606
Slovakia	+421 2 5477 4166
Slovenia	112
Spain	+34 91 562 04 20
Sweden	112
Switzerland	145
United Kingdom	844 892 0111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixtureClassification according to Regulation (EC) No. 1272/2008 [CLP]

Carcinogenicity Category 1B - (H350)

2.2. Label elements

Contains 2-BUTANONE OXIME



Signal word Danger

Hazard statements

H350 - May cause cancer.

EUH208 Contains 2-BUTANONE OXIME May produce an allergic reaction.

Precautionary Statements - EU (§28, 1272/2008)

P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P280 - Wear protective gloves, protective clothing, eye protection and face protection.

P308 + P313 - IF exposed or concerned: Get medical advice/attention.

P405 - Store locked up.

P501 - Dispose of contents and container in accordance with local, regional, national, and international regulations as applicable.

42.24 % of the mixture consists of ingredient(s) of unknown acute toxicity.

3.09 % of the mixture consists of ingredient(s) of unknown acute oral toxicity.

0 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity.

42.24 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas).

42.24 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor).

10.74 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist).

Unknown aquatic toxicity

Contains 0 % of components with unknown hazards to the aquatic environment.

2.3. Other hazards

Other hazards No information available.

PBT & vPvB The components in this formulation do not meet the criteria for classification as PBT or

vPvB.

Endocrine Disruptor InformationThis product does not contain any known or suspected endocrine disruptors.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Chemical name	Weight-%	REACH registration number	EC No (EU Index No)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-ter m)	Notes
CALCIUM CARBONATE 471-34-1	15-40%	No data available	207-439-9	No data available	-	-	-	-
LIMESTONE 1317-65-3	10-30%	No data available	215-279-6	No data available	-	-	-	-
SYNTHETIC ISOPARAFFINIC HYDROCARBON 64742-47-8	3-7%	No data available	265-149-8 (649-422-00-2)	Asp. Tox. 1 (H304)	-	-	-	-
POLYDIMETHYLSIL OXANE 63148-62-9	1-5%	No data available	-	No data available	-	-	-	-
STEARIC ACID 57-11-4	1-5%	No data available	200-313-4	No data available	-	-	-	-
ALUMINIUM POWDER	0.1-1%	No data available	231-072-3 (013-002-00-1)	Flam. Sol. 1 (H228) Water-react. 2	-	-	-	Т

7429-90-5			(013-001-00-6)	(H261)				
CARBON BLACK 1333-86-4	0.1-1%	No data available	215-609-9	No data available	-	-	-	-
2-BUTANONE OXIME 96-29-7	0.1-1%	No data available	202-496-6 (616-014-00-0)	Acute Tox. 3 (H301) Acute Tox. 4 (H312) Skin Irrit. 2 (H315) Skin Sens. 1 (H317) Eye Dam. 1 (H318) STOT SE 3 (H336) STOT SE 1 (H370) Carc. 1B (H350) STOT RE 2 (H373)		-	-	-
MINERAL OIL 8042-47-5	0.1-1%	No data available	232-455-8	No data available	-	-	-	-
SILICA, QUARTZ 14808-60-7	<0.1%	No data available	238-878-4	No data available	- -	-	-	-

Note T - This substance may be marketed in a form which does not have the physical hazards as indicated by the classification in the entry in Part 3. If the results of the relevant method or methods in accordance with Part 2 of Annex I of this Regulation show that the specific form of substance marketed does not exhibit this physical property or these physical hazards, the substance shall be classified in accordance with the result or results of this test or these tests. Relevant information, including reference to the relevant test method(s) shall be included in the safety data sheet.

Full text of H- and EUH-phrases: see section 16

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	Oral LD50 mg/kg		Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapor - mg/L	Inhalation LC50 - 4 hour - gas - ppm
CALCIUM CARBONATE 471-34-1	6450	2000	3	No data available	No data available
SYNTHETIC ISOPARAFFINIC HYDROCARBON 64742-47-8	5000	2000	No data available	No data available	No data available
POLYDIMETHYLSILOXA NE 63148-62-9	24000	No data available	No data available	No data available	No data available
STEARIC ACID 57-11-4	4600	2000	No data available	No data available	No data available
ALUMINIUM POWDER 7429-90-5	No data available	No data available	0.888	No data available	No data available
CARBON BLACK 1333-86-4	10000	2000	0.0046	No data available	No data available
2-BUTANONE OXIME 96-29-7	100+ 930	1100+ 1000	No data available	No data available	No data available
MINERAL OIL 8042-47-5	5000	No data available	No data available	No data available	No data available

⁺ This value is the harmonized acute toxicity estimate (ATE) listed in CLP Annex VI, Part 3. This harmonized ATE value must be used when calculating the acute toxicity estimate (ATEmix) for classifying a mixture containing the listed substance

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59).

Section 4: First aid measures

4.1. Description of first aid measures

General advice IF exposed or concerned: Get medical advice/attention.

Inhalation Remove to fresh air.

Eye contact Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids.

Consult a physician.

Skin contact Wash skin with soap and water. In the case of skin irritation or allergic reactions see a

physician.

Ingestion Rinse mouth.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Effects of Exposure May cause cancer.

4.3. Indication of any immediate medical attention and special treatment needed

Note to physiciansTreat symptomatically.

Section 5: Firefighting measures

5.1. Extinguishing media

surrounding environment.

Small Fire In case of fire, use water spray, foam, dry chemical, or CO2. **Large Fire** In case of fire, use water spray, foam, dry chemical, or CO2.

Unsuitable extinguishing media Do not scatter spilled material with high pressure water streams.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

chemical

No information available.

Hazardous combustion products No information available

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear.

Use personal protection equipment.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation.

Other information Refer to protective measures listed in Sections 7 and 8.

6.2. Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with

skin, eyes or clothing.

General hygiene considerations Do not eat, drink or smoke when using this product. Wash hands before breaks and

immediately after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed in a dry and well-ventilated place.

Storage class (TRGS 510) Storage class 6.1C.

7.3. Specific end use(s)

Specific use(s)
Automotive Sealant.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	Austria	Belgium	Bulgaria	Croatia
CALCIUM CARBONATE	-	-	-	-	TWA: 10 mg/m ³
471-34-1					TWA: 4 mg/m ³

LIMESTONE	_	_	TWA: 10 mg/m ³	TWA: 10.0 mg/m ³	
1317-65-3	-	-	•	TVVA. 10.0 Hig/III°	-
ALUMINIUM POWDER 7429-90-5	-	TWA: 10 mg/m ³ STEL 20 mg/m ³	TWA: 1 mg/m ³	TWA: 10.0 mg/m ³ TWA: 1.5 mg/m ³	TWA: 10 mg/m ³ TWA: 4 mg/m ³
CARBON BLACK 1333-86-4	-	-	TWA: 3 mg/m ³	-	TWA: 3.5 mg/m ³ STEL: 7 mg/m ³
2-BUTANONE OXIME 96-29-7	-	Sh+	-	-	-
SILICA, QUARTZ 14808-60-7	TWA: 0.1 mg/m ³	TWA: 0.05 mg/m ³	TWA: 0.1 mg/m ³ TWA: 0.05 mg/m ³	TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³
Chemical name	Cyprus	Czech Republic	Denmark	Estonia	Finland
LIMESTONE 1317-65-3	-	TWA: 10.0 mg/m ³	-	TWA: 10 mg/m ³ TWA: 5 mg/m ³	-
ALUMINIUM POWDER 7429-90-5	-	TWA: 10.0 mg/m ³	TWA: 5 mg/m ³ TWA: 2 mg/m ³ STEL: 10 mg/m ³ STEL: 4 mg/m ³	TWA: 10 mg/m ³ TWA: 4 mg/m ³	TWA: 1.5 mg/m ³
CARBON BLACK 1333-86-4	-	TWA: 2.0 mg/m ³	TWA: 3.5 mg/m ³ STEL: 7 mg/m ³	TWA: 3 mg/m ³	TWA: 3.5 mg/m ³ STEL: 7 mg/m ³
SILICA, QUARTZ 14808-60-7	TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³	TWA: 0.3 mg/m ³ TWA: 0.1 mg/m ³ STEL: 0.6 mg/m ³ STEL: 0.2 mg/m ³	TWA: 0.1 mg/m ³	TWA: 0.05 mg/m ³ TWA: 0.1 mg/m ³
Chemical name	France	Germany TRGS	Germany DFG	Greece	Hungary
CALCIUM CARBONATE 471-34-1	TWA: 10 mg/m ³	-	-	-	1
LIMESTONE 1317-65-3	-	-	-	TWA: 10 mg/m ³ TWA: 5 mg/m ³	TWA: 10 mg/m ³
SYNTHETIC ISOPARAFFINIC HYDROCARBON 64742-47-8	-	TWA:	TWA: 5 mg/m ³ TWA: 50 ppm TWA: 350 mg/m ³ Peak: 20 mg/m ³ Peak: 100 ppm Peak: 700 mg/m ³	-	
ALUMINIUM POWDER 7429-90-5	TWA: 10 mg/m ³ TWA: 5 mg/m ³	TWA: 1.25 mg/m ³ TWA: 10 mg/m ³	TWA: 0.5 mg/m ³ TWA: 0.05 mg/m ³ Peak: 0.4 mg/m ³ Peak: 4 mg/m ³	TWA: 10 mg/m ³ TWA: 5 mg/m ³	TWA: 1 mg/m³
CARBON BLACK 1333-86-4	TWA: 3.5 mg/m ³	-	-	TWA: 3.5 mg/m ³ STEL: 7 mg/m ³	TWA: 3 mg/m ³
2-BUTANONE OXIME 96-29-7	-	TWA: 0.3 ppm TWA: 1 mg/m³ Sk* Sh+	Sk* skin sensitizer	-	-
MINERAL OIL 8042-47-5	-	TWA: 5 mg/m ³	TWA: 5 mg/m ³ Peak: 20 mg/m ³	-	TWA: 5 mg/m ³
SILICA, QUARTZ 14808-60-7	TWA: 0.1 mg/m ³	-	-	TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³
Chemical name	Ireland	Italy MDLPS	Italy AIDII	Latvia	Lithuania
CALCIUM CARBONATE 471-34-1	-	-	-	TWA: 6 mg/m ³	-
LIMESTONE 1317-65-3	TWA: 10 mg/m ³ TWA: 4 mg/m ³ STEL: 30 mg/m ³ STEL: 12 mg/m ³	-	-	-	-
STEARIC ACID 57-11-4	-	-	TWA: 10 mg/m ³ TWA: 3 mg/m ³	-	-

ALUMINIUM POWDER 7429-90-5	TWA: 1 m STEL: 3 n	mg/m³	-	TWA: 1 mg/m ³	TWA: 2	mg/m³	TWA: 5 mg/m ³ TWA: 2 mg/m ³ TWA: 1 mg/m ³
CARBON BLACK 1333-86-4	TWA: 3 mg/m ³ STEL: 15 mg/m ³		-	TWA: 3 mg/m ³	-		-
2-BUTANONE OXIME 96-29-7	TWA: 3 ppm TWA: 10 mg/m³ STEL: 10 ppm STEL: 33 mg/m³ Sens+		-	-	-		-
MINERAL OIL 8042-47-5	-		-	-	TWA: 5	mg/m³	-
SILICA, QUARTZ 14808-60-7	TWA: 0.1 STEL: 0.3	mg/m³ mg/m³	TWA: 0.1 mg/m ³	TWA: 0.025 mg/m ³	-		TWA: 0.1 ppm
Chemical name	Luxemb	oura	Malta	Netherlands	Norv	vav	Poland
CALCIUM CARBONATE 471-34-1	-	3 a. g	-	-	-		TWA: 10 mg/m ³
ALUMINIUM POWDER 7429-90-5	-		-	-	TWA: 5 STEL: 10		TWA: 2.5 mg/m ³ TWA: 1.2 mg/m ³
CARBON BLACK 1333-86-4	-		-	-	TWA: 3.5 STEL: 7		TWA: 4 mg/m ³
SILICA, QUARTZ 14808-60-7	-		-	TWA: 0.075 mg/m ³			TWA: 0.1 mg/m³
Chemical name	Portug	gal	Romania	Slovakia	Slovenia		Spain
LIMESTONE 1317-65-3	-		TWA: 10 mg/m ³	-	-		<u>-</u>
POLYDIMETHYLSILOXA NE 63148-62-9	-		TWA: 200 mg/m³ STEL: 300 mg/m³ Sk*	-	-		-
ALUMINIUM POWDER 7429-90-5	TWA: 1 m	ng/m³	TWA: 3 mg/m ³ TWA: 1 mg/m ³ STEL: 10 mg/m ³ STEL: 3 mg/m ³	TWA: 4 mg/m ³ TWA: 1.5 mg/m ³	- I		TWA: 1 mg/m³
CARBON BLACK 1333-86-4	TWA: 3 m	ng/m³	-	TWA: 2 mg/m ³ TWA: 10 mg/m ³ Ceiling: 10 mg/m ³	-		TWA: 3.5 mg/m ³
2-BUTANONE OXIME 96-29-7	-		-	-	TWA: 1 TWA: 0 STEL: 2 STEL: 8 Sk	.3 ppm .4 ppm mg/m ³	-
MINERAL OIL 8042-47-5	-		-	-	TWA: 5 STEL: 20		-
SILICA, QUARTZ	TWA: 0.025	5 mg/m ³	TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³	TWA: 0.0		TWA: 0.05 mg/m ³
14808-60-7	TWA: 0.05			STEL: 0.5 mg/m ³			
Chemical name			Sweden	Switzerlan		Un	ited Kingdom
CALCIUM CARBON 471-34-1	IATE		-	TWA: 3 mg/ TWA: 10 mg			-
LIMESTONE 1317-65-3	LIMESTONE		-		y 1 (1	T\ ST	VA: 10 mg/m³ VA: 4 mg/m³ EL: 30 mg/m³ EL: 12 mg/m³
SYNTHETIC ISOPARAFFINIC HYDROCARBON 64742-47-8			-	TWA: 50 ppm TWA: 350 mg/m³ TWA: 5 mg/m³ STEL: 100 ppm			_

		STEL: 700 mg/m ³	
ALUMINIUM POWDER	NGV: 5 mg/m ³	TWA: 3 mg/m ³	TWA: 10 mg/m ³
7429-90-5	NGV: 2 mg/m ³	TWA: 10 mg/m ³	TWA: 4 mg/m ³
			STEL: 30 mg/m ³
			STEL: 12 mg/m ³
CARBON BLACK	NGV: 3 mg/m ³	-	TWA: 3.5 mg/m ³
1333-86-4			STEL: 7 mg/m ³
MINERAL OIL	-	TWA: 5 mg/m ³	-
8042-47-5			
SILICA, QUARTZ	NGV: 0.1 mg/m ³	TWA: 0.15 mg/m ³	TWA: 0.1 mg/m ³
14808-60-7	_		STEL: 0.3 mg/m ³

Biological occupational exposure limits

Chemical name	Furo	pean Union	Αι	ıstria	Bulgar	ia	Croatia		Czech Republic
ALUMINIUM POWDER		-		Creatinine -			200 μg/L - urin	ne	-
7429-90-5			urine (A	luminum) -			(Aluminum) - at	the	
				nd of work			end of the work s	shift	
				ne end of a					
				eek/end of					
			the	shift					
				ote 1)					
CARBON BLACK 1333-86-4		-	(No	ote 1)	-		-		-
SILICA, QUARTZ		-	(No	ote 1)	-		-		-
14808-60-7			,	•					
Chemical name		Denmark	Fir	nland	Franc	е	Germany DFC		Germany TRGS
ALUMINIUM POWDER		-		-	-		50 μg/g Creatin		50 μg/g Creatinine
7429-90-5							(urine - Aluminu		(urine - Aluminum
							for long-term		for long-term
							exposures: at the		exposures: at the
							several shifts		end of the shift after several shifts)
							50 μg/g Creatinii		Several Stills)
							BAT (for long-te		
							exposures: at t		
							end of the shift a		
							several shifts) ui		
							15 μg/g Creatinii		
							BAR (for long-te		
							exposures: at t	he	
							end of the shift a		
							several shifts) u	rine	
Chemical name		Latvia		Luxer	nbourg		Romania	000	Slovakia
ALUMINIUM POWDER		50 μg/g Crea			-				ug/g creatinine (urine
7429-90-5		urine (Aluminu of shift				(Alumin	um) - ena or snirt	- A	luminum not critical)
Chemical name		Sloveni		Sp	pain		Switzerland		United Kingdom
ALUMINIUM POWDER	1	50 μg/L - υ			-		creatinine (urine		-
7429-90-5		(Aluminum)				_	num after several		
		ong-term expo					(for long-term		
	ļtr	ne end of the v					xposures))		
		after seve					1 µmol/mmol		
	[]	consecutive w	orkuays				tinine (urine - um after several		
						shifts	(for long-term		

exposures))

Note 1: Details about BEL values can be found in Annex 2 of the Austrian Ordinance on Health Monitoring in the Workplace.

Derived No Effect Level (DNEL) - Workers

Chemical name	Oral	Dermal	Inhalation
CALCIUM CARBONATE	-	-	6.36 mg/m ³ [5] [6]
471-34-1			
VINYL OXIMINOSILANE 2224-33-1	-	0.15 mg/kg bw/day [4] [6]	1.06 mg/m³ [4] [6]
STEARIC ACID 57-11-4	-	10 mg/kg bw/day [4] [6]	17.632 mg/m³ [4] [6]
CARBON BLACK 1333-86-4	-	-	1 mg/m³ [4] [6] 0.5 mg/m³ [5] [6]
OXIMINOSILANE 34206-40-1	-	0.134 mg/kg bw/day [4] [6]	0.942 mg/m³ [4] [6]
2-BUTANONE OXIME	-	1.3 mg/kg bw/day [4] [6]	9 mg/m³ [4] [6]
96-29-7		2.5 mg/kg bw/day [4] [7]	3.33 mg/m³ [5] [6]
MINERAL OIL 8042-47-5	-	217.05 mg/kg bw/day [4] [6]	164.56 mg/m³ [4] [6]

Notes

[4] [5] [6] [7] Systemic health effects. Local health effects. Long term.

Short term.

Derived No Effect Level (DNEL) - General Public

Chemical name	Oral	Dermal	Inhalation
CALCIUM CARBONATE 471-34-1	6.1 mg/kg bw/day [4] [6] 6.1 mg/kg bw/day [4] [7]	-	1.06 mg/m³ [5] [6]
SYNTHETIC ISOPARAFFINIC HYDROCARBON 64742-47-8	18.75 mg/kg bw/day [4] [6]	-	-
VINYL OXIMINOSILANE 2224-33-1	0.075 mg/kg bw/day [4] [6]	-	0.26 mg/m³ [4] [6]
STEARIC ACID 57-11-4	2.5 mg/kg bw/day [4] [6]	-	4.348 mg/m³ [4] [6]
CARBON BLACK 1333-86-4	-	-	0.06 mg/m³ [4] [6]
OXIMINOSILANE 34206-40-1	0.067 mg/kg bw/day [4] [6]	-	0.232 mg/m³ [4] [6]
2-BUTANONE OXIME 96-29-7	-	1.5 mg/kg bw/day [4] [6] 1.5 mg/kg bw/day [4] [7]	2.7 mg/m³ [4] [6] 2 mg/m³ [5] [6]
MINERAL OIL 8042-47-5	25 mg/kg bw/day [4] [6]	-	34.78 mg/m³ [4] [6]

Notes

[4] [5] [6] Systemic health effects. Local health effects.

Long term. Short term. [7]

Predicted No Effect Concentration (PNEC)

Chemical name	Freshwater	Freshwater	Marine water	Marine water	Air
		(intermittent release)		(intermittent release)	
VINYL OXIMINOSILANE	0.01919 mg/L	-	0.001919 mg/L	-	-
2224-33-1					
OXIMINOSILANE	0.0171 mg/L	-	0.00171 mg/L	-	-
34206-40-1					
2-BUTANONE OXIME	0.256 mg/L	0.118 mg/L	-	-	-
96-29-7					
GAMMA-AMINOPROPYL	0.5 mg/L	2.05 mg/L	0.05 mg/L	-	-
TRIMETHOXYSILANE					
13822-56-5					

Chemical name	Freshwater sediment	Marine sediment	Sewage treatment	Soil	Food chain
CALCIUM CARBONATE 471-34-1	-	-	100 mg/L	-	-
VINYL OXIMINOSILANE 2224-33-1	1136.562 mg/kg sediment dw	113.656 mg/kg sediment dw	4.06 mg/L	133.8 mg/kg soil dw	3.333 mg/kg food
ALUMINIUM POWDER 7429-90-5	-	-	20 mg/L	-	-
OXIMINOSILANE 34206-40-1	9835.346 mg/kg sediment dw	983.535 mg/kg sediment dw	4.825 mg/L	1157.93 mg/kg soil dw	2.97 mg/kg food
2-BUTANONE OXIME 96-29-7	-	-	177 mg/L	-	-
GAMMA-AMINOPROPYL TRIMETHOXYSILANE 13822-56-5	1.8 mg/kg sediment dw	0.18 mg/kg sediment dw	0.81 mg/L	0.069 mg/kg soil dw	11.1 mg/kg food

8.2. Exposure controls

Engineering controls No information available.

Personal protective equipment

Eye/face protection Appropriate eye/face protection should be selected and used according to the chemical

nature, hazards and use of this product and safety requirements of the local jurisdiction.

Hand protection Wear suitable gloves.

Skin and body protection Wear suitable protective clothing.

Respiratory protection Appropriate respiratory protection should be selected and used according to the chemical

nature, hazards and use of this product and safety requirements of the local jurisdiction. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be

required.

Thermal hazards No information available.

Environmental exposure controls No information available.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Paste / Gel Liquid

Appearance Paste Color Black Odor Mild.

Odor threshold No information available

Property Values Remarks • Method

No data available Melting point / freezing point Estimated No data available Boiling point / boiling range Polymerization

No data available Flammable in the presence of the following materials Flammability (solid, gas)

or conditions: open flames, sparks and static

discharge. None known

Upper flammability limit: No data available

No data available Lower flammability limit: > 95 °C Flash point

Autoignition temperature No data available

Estimated **Decomposition temperature** Remarks: Self-Accelerating decomposition

> temperature (SADT): 50 °C SADT-Self Accelerating Decomposition Temperature. Lowest temperature at which the tested package size will undergo a

Tag Closed Cup

None known

None known

Air = 1

self-accelerating decomposition reaction.

No data available 10% in deionized water pН

No data available None known pH (as aqueous solution)

Kinematic viscosity at 100 degrees C Kinematic viscosity No Data Available Remarks: Self-Accelerating decomposition **Dynamic viscosity** No data available

temperature (SADT): 50 °C SADT-Self Accelerating Decomposition Temperature. Lowest temperature at which the tested package size will undergo a

self-accelerating decomposition reaction.

Water solubility No data available Not applicable Polymerization

None known

Solubility(ies) No Data Available No Data Available Partition coefficient <5 mm Hg @ 80°F Vapor pressure

Relative density 1.44

Bulk density No data available No data available Density

Vapor density >1

Particle characteristics

Flammability Limit in Air

No information available **Particle Size Particle Size Distribution** No information available

9.2. Other information

3% VOC content

9.2.1. Information with regard to physical hazard classes Not applicable

9.2.2. Other safety characteristics

No information available

Section 10: Stability and reactivity

Page 12 / 20

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None. Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Hazardous polymerization No information available.

10.4. Conditions to avoid

Conditions to avoid None known based on information supplied.

10.5. Incompatible materials

Incompatible materialsNone known based on information supplied.

10.6. Hazardous decomposition products

Hazardous Decomposition Products None known based on information supplied.

Section 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Inhalation Specific test data for the substance or mixture is not available.

Eye contact Specific test data for the substance or mixture is not available.

Skin contact Specific test data for the substance or mixture is not available.

Ingestion Specific test data for the substance or mixture is not available.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Acute toxicity Based on available data, the classification criteria are not met.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document:

ATEmix (oral) 12,206.40 mg/kg ATEmix (dermal) 4,736.40 mg/kg ATEmix (inhalation-gas) 99,999.00 ppm

ATEmix (inhalation-vapor) 99,999.00 mg/l ATEmix (inhalation-dust/mist) 8.50 mg/l

3.09 % of the mixture consists of ingredient(s) of unknown acute oral toxicity.

0 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity.

42.24 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas).

42.24 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor).

10.74 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist).

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
CALCIUM CARBONATE	= 6450 mg/kg (Rat)	> 2000 mg/kg (Rat)	> 3 mg/L (Rat) 4 h
SYNTHETIC ISOPARAFFINIC HYDROCARBON	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat)4 h
POLYDIMETHYLSILOXANE	> 24 g/kg (Rat)	-	-
STEARIC ACID	= 4600 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	-
ALUMINIUM POWDER	-	-	> 0.888 mg/L (Rat) 4 h
CARBON BLACK	> 10000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 4.6 mg/m³ (Rat) 4 h
2-BUTANONE OXIME	= 930 mg/kg (Rat)	1000 - 1800 mg/kg (Rabbit)	> 4.83 mg/L (Rat) 4 h
MINERAL OIL	> 5000 mg/kg (Rat)	-	-

Skin corrosion/irritationBased on available data, the classification criteria are not met.

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitization Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for

ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

the table below maleures micros each agency has noted any ingreation as a salemeger.				
Chemical name	European Union			
2-BUTANONE OXIME	Carc. 1B			

Reproductive toxicityBased on available data, the classification criteria are not met.

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposureBased on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties Based on available data, the classification criteria are not met.

11.2.2. Other information

Other adverse effects No information available.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity

Unknown aquatic toxicityContains 0 % of components with unknown hazards to the aquatic environment.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
SYNTHETIC ISOPARAFFINIC HYDROCARBON	-	LC50: =45mg/L (96h, Pimephales promelas) LC50: =2.2mg/L (96h, Lepomis macrochirus) LC50: =2.4mg/L (96h, Oncorhynchus mykiss)	-	-
2-BUTANONE OXIME	EC50: =83mg/L (72h, Desmodesmus subspicatus)	LC50: 777 - 914mg/L (96h, Pimephales promelas) LC50: =760mg/L (96h, Poecilia reticulata)	-	EC50: =750mg/L (48h, Daphnia magna)
MINERAL OIL	-	LC50: >10000mg/L (96h, Lepomis macrochirus)	-	-

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation

Chemical name	Partition coefficient	
2-BUTANONE OXIME	0.65	
MINERAL OIL	6	

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment Based on available data, the classification criteria are not met.

Chemical name	PBT and vPvB assessment	
CALCIUM CARBONATE	The substance is not PBT / vPvB	
SYNTHETIC ISOPARAFFINIC HYDROCARBON	The substance is not PBT / vPvB	
STEARIC ACID	The substance is not PBT / vPvB	
ALUMINIUM POWDER	The substance is not PBT / vPvB	
CARBON BLACK	The substance is not PBT / vPvB	
2-BUTANONE OXIME	The substance is not PBT / vPvB	
MINERAL OIL	The substance is not PBT / vPvB	

12.6. Endocrine disrupting properties

Based on available data, the classification criteria are not met. **Endocrine disrupting properties**

12.7. Other adverse effects

No information available. Other adverse effects

PMT or vPvM properties Based on available data, the classification criteria are not met.

Section 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused

products

Dispose of in accordance with local regulations. Dispose of waste in accordance with

environmental legislation.

Contaminated packaging Do not reuse empty containers.

Section 14: Transport information

IATA

14.1	UN number or ID number	Not regulated
14.2	UN proper shipping name	Not regulated
14.3	Transport hazard class(es)	Not regulated
14.4	Packing group	Not regulated
14.5	Environmental hazards	Not applicable

14.6 Special precautions for user

Special Provisions None

IMDG

14.1	UN number or ID number	Not regulated
14.2	UN proper shipping name	Not regulated
14.3	Transport hazard class(es)	Not regulated
14.4	Packing group	Not regulated
14.5	Environmental hazards	Not applicable

14.6 Special precautions for user

Special Provisions None

14.7 Maritime transport in bulk according to IMO instruments

No information available

RID

14.1 UN number or ID number
 14.2 UN proper shipping name
 14.3 Transport hazard class(es)
 14.4 Packing group
 14.5 Environmental hazards
 Not regulated Not regulated Not applicable

14.6 Special precautions for user

Special Provisions None

<u>ADR</u>

14.1 UN number or ID number
14.2 UN proper shipping name
14.3 Transport hazard class(es)
14.4 Packing group
14.5 Environmental hazards
Not regulated
Not regulated
Not regulated
Not applicable

14.6 Special precautions for user

Special Provisions None

ADN

14.1UN number or ID numberNot regulated14.2UN proper shipping nameNot regulated14.3Transport hazard class(es)Not regulated14.4Packing groupNot regulated14.5Environmental hazardNot applicable

14.6 Special precautions for user

Special Provisions None

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

<u>France</u>

Occupational Illnesses (R-463-3, France)

occupational filliesses (11-400-0, 1 rance)				
Chemical name	French RG number			
SYNTHETIC ISOPARAFFINIC HYDROCARBON - 64742-47-8	RG 84			
ALUMINIUM POWDER - 7429-90-5	RG 32			
	RG 16,RG 16bis			
CARBON BLACK - 1333-86-4	RG 16,RG 16bis			
MINERAL OIL - 8042-47-5	RG 36bis			
SILICA, QUARTZ - 14808-60-7	RG 25			

Germany

Water hazard class (WGK) strongly hazardous to water (WGK 3)

TA Luft (German Air Pollution Control Regulation)

Chemical name	Number	Class
SILICA, QUARTZ	5.2.7.1.1	-

Netherlands

Carcinogenic, mutagenic and reproductive toxic effects

Chemical name	Netherlands - List of	Netherlands - List of Mutagens	Netherlands - List of
	Carcinogens		Reproductive Toxins

Chemical name	Netherlands - List of Carcinogens	Netherlands - List of Mutagens	Netherlands - List of Reproductive Toxins
2-BUTANONE OXIME	Present		-
SILICA, QUARTZ	Present	-	-

Ordinance on the Incentive Tax on Volatile Organic Compounds (OVOC) SR 814.018 Not applicable WPO (GSchV) SR 814.201; WPA (GSchG) SR 814.20 Not applicable

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work.

Authorizations and/or restrictions on use:

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII)

Chemical name	Restricted substance per REACH Annex XVII	Substance subject to authorization per REACH Annex XIV
CALCIUM CARBONATE - 471-34-1	75	-
ALUMINIUM POWDER - 7429-90-5	75	-
CARBON BLACK - 1333-86-4	75	-
2-BUTANONE OXIME - 96-29-7	75	-
	28	

Persistent Organic Pollutants

Not applicable

Ozone-depleting substances (ODS) Regulation (EU) 2024/590

Not applicable

EU - Plant Protection Products (1107/2009/EC)

20 Tiant Totobion Todabio (1101/200/20)		
Chemical name	EU - Plant Protection Products (1107/2009/EC)	
CALCIUM CARBONATE - 471-34-1	Plant protection agent	
CARBON BLACK - 1333-86-4	Plant protection agent	
MINERAL OIL - 8042-47-5	Plant protection agent	
SILICA, QUARTZ - 14808-60-7	Plant protection agent	

International Inventories

TSCA Complies Complies **DSL/NDSL** Does not comply **EINECS/ELINCS** Does not comply **ENCS IECSC** Complies Complies **KECI** Complies **PICCS** Complies **AICS** Complies **NZIoC**

TCSI Contact supplier for inventory compliance status

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing Chemicals Inventory

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

TCSI - Taiwan Chemical Substance Inventory

15.2. Chemical safety assessment

Chemical Safety Report No information available

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of any hazard and/or precautionary statements referred to under Sections 2-15

H228 - Flammable solid

H261 - In contact with water releases flammable gas

H301 - Toxic if swallowed

H304 - May be fatal if swallowed and enters airways

H312 - Harmful in contact with skin

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H336 - May cause drowsiness or dizziness

H350 - May cause cancer

H370 - Causes damage to organs

H373 - May cause damage to organs through prolonged or repeated exposure

SVHC: Substances of Very High Concern for Authorization:

PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances

vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances

STOT: Specific Target Organ Toxicity

ATE: Acute Toxicity Estimate

LC50: 50% Lethal Concentration

LD50: 50% Lethal Dose

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA (time-weighted average) STEL (Short Term Exposure Limit) TWA

Ceiling Maximum limit value Skin designation

Sensitizers

Classification procedure		
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used	
Acute oral toxicity	Calculation method	
Acute dermal toxicity	Calculation method	
Acute inhalation toxicity - gas	Calculation method	
Acute inhalation toxicity - vapor	Calculation method	
Acute inhalation toxicity - dust/mist	Calculation method	
Skin corrosion/irritation	Calculation method	
Serious eye damage/eye irritation	Calculation method	
Respiratory sensitization	Calculation method	
Skin sensitization	Calculation method	

Mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Acute aquatic toxicity	Calculation method
Chronic aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR)

U.S. Environmental Protection Agency ChemView Database

European Food Safety Authority (EFSA)

European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA RAC)

European Chemicals Agency (ECHA) (ECHA_API)

Environmental Protection Agency

Acute Exposure Guideline Level(s) (AEGL(s))

U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act

U.S. Environmental Protection Agency High Production Volume Chemicals

Food Research Journal

Hazardous Substance Database

International Uniform Chemical Information Database (IUCLID)

National Institute of Technology and Evaluation (NITE)

Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)

NIOSH (National Institute for Occupational Safety and Health)

National Library of Medicine's ChemID Plus (NLM CIP)

National Library of Medicine's PubMed database (NLM PUBMED)

U.S. National Toxicology Program (NTP)

New Zealand's Chemical Classification and Information Database (CCID)

Organization for Economic Co-operation and Development Environment, Health, and Safety Publications

Organization for Economic Co-operation and Development High Production Volume Chemicals Program

Organization for Economic Co-operation and Development Screening Information Data Set

World Health Organization

Revision Date 14-Oct-2024

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006 Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet