

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 as amended by Regulation (EU) No. 2020/878, and Regulation (EC) No. 1272/2008

Revision Date 06-Feb-2025

Version 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Code 33694

Product Name THE RIGHT STUFF GASKET MAKER 10.1 FL.OZ

Other means of identification

Unique Formula Identifier (UFI) ED5J-D0W5-U00H-QNKR

Synonyms 30874

Mixture. Contains CARBON BLACK; 2-BUTANONE OXIME

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Sealant

Uses advised against No information available

1.3. Details of the supplier of the safety data sheet

Manufacturer Only Representative (OR)

ITW Permatex, Inc. ITW Permatex, Inc.

6875 Parkland Blvd. Bay 150

Solon, Ohio 44139 USA Shannon Industrial Estate

Telephone: 1-87-Permatex Co. Clare (866) 732-9502 Ireland V14 DF82

353(61)771500 353(61)471285

customerservice.shannon@itwpp.com

For further information, please contact

Contact Point ITW Permatex

6875 Parkland Blvd. Solon, Ohio 44139 USA Telephone: 1-87-Permatex

(866) 732-9502

E-mail address: mail@permatex.com

Non-Emergency Telephone Number 866-732-9502

1.4. Emergency telephone number

24-hour emergency phone number
EU Member States information as follows:

24-hour emergency phone number - §45 - (EC)1272/2008

Europe	112
Austria	01 406 43 43
Belgium	070 245 245
Bulgaria	+359 2 9154 233
Croatia	+3851 2348 342
Cyprus	1401
Czech Republic	+420 224 919 293/ +420 224 915 402
Denmark	+ 45 8212 1212
Estonia	16662/ (+372) 7943 794
Finland	0800 147 111/ 09 471 977
France	+33 (0)1 45 42 59 59
Germany	+49 228 192 40
Greece	(003) 2107793777
Hungary	+36 80 201 199
Iceland	543 2222
Ireland	01 809 2166
Italy	0382-24444
Latvia	+371 67042473
Liechtenstein	01 406 43 43
Lithuania	+370 (85) 2362052
Luxembourg	(+352) 8002 5500
Malta	112
Netherlands	+31 (0)88 755 8000
Norway	22 59 13 00
Poland	112
Portugal	+351 800 250 250
Romania	+40213183606
Slovakia	+421 2 5477 4166
Slovenia	112
Spain	+34 91 562 04 20
Sweden	112
Switzerland	145
United Kingdom	111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixtureClassification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity - Inhalation (Dusts/Mists)	Category 2 - (H330)
Carcinogenicity	Category 1B - (H350)

2.2. Label elements

Contains CARBON BLACK; 2-BUTANONE OXIME



Signal word Danger

Hazard statements

H330 - Fatal if inhaled.

H350 - May cause cancer.

EUH208 Contains 2-BUTANONE OXIME May produce an allergic reaction.

Precautionary Statements - EU (§28, 1272/2008)

P201 - Obtain special instructions before use.

P260 - Do not breathe dust, fume, gas, mist, vapors and spray.

P280 - Wear protective gloves, protective clothing, eye protection and face protection.

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P310 - Immediately call a POISON CENTER or doctor.

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.

Unknown acute toxicity

50.552 % of the mixture consists of ingredient(s) of unknown acute toxicity.

6.402 % of the mixture consists of ingredient(s) of unknown acute oral toxicity.

2.871 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity.

 $50.552\ \%$ of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas).

50.552 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor).

9.552 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist).

Unknown aquatic toxicity

Contains 48.681 % of components with unknown hazards to the aquatic environment.

Additional information

This product requires child resistant fastenings if supplied to the general public. This product requires tactile warnings if supplied to the general public.

2.3. Other hazards

Other hazards No information available.

PBT & vPvB The components in this formulation do not meet the criteria for classification as PBT or

vPvB.

Endocrine Disruptor InformationThis product does not contain any known or suspected endocrine disruptors.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

		5=1011			1 2 14			
Chemical name	Weight-%	REACH	EC No (EU	Classification	Specific	M-Factor	M-Factor	Notes
		registration	Index No)	according to	concentration		(long-ter	
		number		Regulation (EC) No.	limit (SCL)		m)	
				1272/2008 [CLP]	, ,		,	
CALCIUM	30-60%	No data	207-439-9	No data available	-	-	-	-
CARBONATE		available						
471-34-1								
POLYDIMETHYLSIL	7-13%	No data	-	No data available	-	-	-	-
OXANE		available						
63148-62-9								
STEARIC ACID	1-5%	No data	200-313-4	No data available	-	-	-	-
57-11-4		available						
CARBON BLACK	0.5-1.5%	No data	215-609-9	No data available	-	-	-	-
1333-86-4		available						
ALUMINIUM	0.1-1%	No data	231-072-3	Flam. Sol. 1 (H228)	_	-	-	Т
POWDER		available	(013-002-00-1)	Water-react. 2				
7429-90-5			(013-001-00-6)	(H261)				
2-BUTANONE OXIME	0.1-1%	No data	202-496-6	Acute Tox. 3 (H301)	-	-	-	-
96-29-7		available	(616-014-00-0)	Acute Tox. 4 (H312)				
				Skin Irrit. 2 (H315)				
				Skin Sens. 1 (H317)				
				Eye Dam. 1 (H318)				

				STOT SE 3 (H336) STOT SE 1 (H370) Carc. 1B (H350) STOT RE 2 (H373)				
MINERAL 8042-47	· I · · · · ·	No data available	232-455-8	No data available	-	-	-	-

Note T - This substance may be marketed in a form which does not have the physical hazards as indicated by the classification in the entry in Part 3. If the results of the relevant method or methods in accordance with Part 2 of Annex I of this Regulation show that the specific form of substance marketed does not exhibit this physical property or these physical hazards, the substance shall be classified in accordance with the result or results of this test or these tests. Relevant information, including reference to the relevant test method(s) shall be included in the safety data sheet.

Full text of H- and EUH-phrases: see section 16

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	Oral LD50 mg/kg	Dermal LD50	Inhalation LC50 - 4	Inhalation LC50 - 4	Inhalation LC50 - 4
		mg/kg	hour - dust/mist - mg/L	hour - vapor - mg/L	hour - gas - ppm
CALCIUM CARBONATE 471-34-1	6450	2000	3	No data available	No data available
POLYDIMETHYLSILOXA NE 63148-62-9	24000	No data available	No data available	No data available	No data available
STEARIC ACID 57-11-4	4600	2000	No data available	No data available	No data available
CARBON BLACK 1333-86-4	10000	2000	0.0046	No data available	No data available
ALUMINIUM POWDER 7429-90-5	No data available	No data available	0.888	No data available	No data available
2-BUTANONE OXIME 96-29-7	100 + 930	1100+ 1000	No data available	No data available	No data available
MINERAL OIL 8042-47-5	5000	No data available	No data available	No data available	No data available

⁺ This value is the harmonized acute toxicity estimate (ATE) listed in CLP Annex VI, Part 3. This harmonized ATE value must be used when calculating the acute toxicity estimate (ATEmix) for classifying a mixture containing the listed substance

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59).

Section 4: First aid measures

4.1. Description of first aid measures

General advice	Immediate medical attention is required. Show this safety data sheet to the doctor in
----------------	---

attendance. IF exposed or concerned: Get medical advice/attention.

Inhalation Remove to fresh air. Do not use mouth-to-mouth method if victim ingested or inhaled the

substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If breathing is difficult, (trained personnel

should) give oxygen.

Eye contact Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids.

Consult a physician.

Skin contact Wash skin with soap and water. In the case of skin irritation or allergic reactions see a

physician.

Ingestion Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious

person. Call a physician or poison control center immediately.

Self-protection of the first aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination. Do not breathe vapor or mist. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Use personal protective equipment as required. See section 8

for more information.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms Coughing and/ or wheezing. Difficulty in breathing.

Effects of Exposure May cause cancer.

4.3. Indication of any immediate medical attention and special treatment needed

Note to physiciansTreat symptomatically.

Section 5: Firefighting measures

5.1. Extinguishing media

surrounding environment.

Small Fire In case of fire, use water spray, foam, dry chemical, or CO2. Large Fire In case of fire, use water spray, foam, dry chemical, or CO2.

Unsuitable extinguishing media Do not scatter spilled material with high pressure water streams.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

chemical

No information available.

Hazardous combustion products No information available

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear.

Use personal protection equipment.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation. Avoid contact with skin, eyes or clothing. Do not breathe vapor

or mist. Use personal protective equipment as required. Evacuate personnel to safe areas.

Keep people away from and upwind of spill/leak.

Other information Refer to protective measures listed in Sections 7 and 8.

6.2. Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Should not be released into the

environment. Do not allow to enter into soil/subsoil. Prevent product from entering drains.

FL.OZ

6.3. Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning upTake up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with

skin, eyes or clothing. Do not breathe vapor or mist. In case of insufficient ventilation, wear suitable respiratory equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Do not eat, drink or smoke when using this product. Take off

contaminated clothing and wash before reuse.

General hygiene considerations Avoid contact with skin, eyes or clothing. Do not breathe vapor or mist. Wear suitable gloves

and eye/face protection. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after

handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up.

Keep out of the reach of children.

Packaging materials No information available.

Storage class (TRGS 510) Storage class 6.1A.

7.3. Specific end use(s)

Specific use(s)
Automotive Sealant.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	Austria	Belgium	Bulgaria	Croatia
CALCIUM CARBONATE	-	-	-	-	TWA: 10 mg/m ³
471-34-1					TWA: 4 mg/m ³
CARBON BLACK	=	=	TWA: 3 mg/m ³	-	TWA: 3.5 mg/m ³
1333-86-4					STEL: 7 mg/m ³
ALUMINIUM POWDER	-	TWA: 10 mg/m ³	TWA: 1 mg/m ³	TWA: 10.0 mg/m ³	TWA: 10 mg/m ³
7429-90-5		STEL 20 mg/m ³		TWA: 1.5 mg/m ³	TWA: 4 mg/m ³
2-BUTANONE OXIME	-	Sh+	-	-	-
96-29-7					

33694 - THE RIGHT STUFF GASKET MAKER 10.1 FL.OZ

Chemical name	Cyprus	Czech Republic	Denmark	Estonia	Finland
CARBON BLACK	-	TWA: 2.0 mg/m ³	TWA: 3.5 mg/m ³	TWA: 3 mg/m ³	TWA: 3.5 mg/m ³
1333-86-4			STEL: 7 mg/m ³		STEL: 7 mg/m ³
ALUMINIUM POWDER	-	TWA: 10.0 mg/m ³	TWA: 5 mg/m ³	TWA: 10 mg/m ³	TWA: 1.5 mg/m ³
7429-90-5			TWA: 2 mg/m ³ STEL: 10 mg/m ³	TWA: 4 mg/m ³	
			STEL: 10 mg/m ³		
Chemical name	France	Germany TRGS	Germany DFG	Greece	Hungary
CALCIUM CARBONATE 471-34-1	TWA: 10 mg/m ³	-	-	-	-
CARBON BLACK	TWA: 3.5 mg/m ³	_	_	TWA: 3.5 mg/m ³	TWA: 3 mg/m ³
1333-86-4	,			STEL: 7 mg/m ³	
ALUMINIUM POWDER 7429-90-5	TWA: 10 mg/m ³ TWA: 5 mg/m ³	TWA: 1.25 mg/m ³ TWA: 10 mg/m ³	TWA: 0.5 mg/m ³ TWA: 0.05 mg/m ³	TWA: 10 mg/m ³ TWA: 5 mg/m ³	TWA: 1 mg/m ³
7429-90-5	TWA. 5 mg/m²	I IVVA. 10 mg/m²	Peak: 0.4 mg/m ³	TWA. 5 mg/m²	
			Peak: 4 mg/m ³		
2-BUTANONE OXIME	-	TWA: 0.3 ppm	Sk*	-	-
96-29-7		TWA: 1 mg/m ³	skin sensitizer		
		Sk*			
MINERAL OIL	_	Sh+ TWA: 5 mg/m ³	TWA: 5 mg/m ³	-	TWA: 5 mg/m ³
8042-47-5	<u>-</u>	TWA. 5 mg/m²	Peak: 20 mg/m ³	-	i vva. Jilig/ili²
Chemical name	Ireland	Italy MDLPS	Italy AIDII	Latvia	Lithuania
CALCIUM CARBONATE	-	-	-	TWA: 6 mg/m ³	-
471-34-1			TIMA 40 / 3		
STEARIC ACID 57-11-4	-	-	TWA: 10 mg/m ³ TWA: 3 mg/m ³	-	-
CARBON BLACK	TWA: 3 mg/m ³	_	TWA: 3 mg/m ³	_	_
1333-86-4	STEL: 15 mg/m ³		1 vv/ (. 5 mg/m		
ALUMINIUM POWDER	TWA: 1 mg/m ³	-	TWA: 1 mg/m ³	TWA: 2 mg/m ³	TWA: 5 mg/m ³
7429-90-5	STEL: 3 mg/m ³			-	TWA: 2 mg/m ³
2-BUTANONE OXIME	TWA: 3 ppm				TWA: 1 mg/m ³
96-29-7	TWA: 3 ppm TWA: 10 mg/m ³	-	-	-	-
00 20 7	STEL: 10 ppm				
	STEL: 33 mg/m ³				
MINIEDALOU	Sens+			T14/4 5 / 3	
MINERAL OIL 8042-47-5	-	-	-	TWA: 5 mg/m ³	-
Chemical name	Luxembourg	Malta	Netherlands	Norway	Poland
CALCIUM CARBONATE	-	-	-	-	TWA: 10 mg/m ³
471-34-1 CARBON BLACK	_	_	_	TWA: 3.5 mg/m ³	TWA: 4 mg/m ³
1333-86-4	-	_	_	STEL: 7 mg/m ³	T WA. 4 mg/m
ALUMINIUM POWDER	-	-	-	TWA: 5 mg/m ³	TWA: 2.5 mg/m ³
7429-90-5	Dantanal	D : -	011	STEL: 10 mg/m ³	TWA: 1.2 mg/m ³
Chemical name POLYDIMETHYLSILOXA	Portugal	Romania TWA: 200 mg/m ³	Slovakia	Slovenia	Spain
NE	-	STEL: 300 mg/m ³	_	-	-
63148-62-9		Sk*			
CARBON BLACK	TWA: 3 mg/m ³	-	TWA: 2 mg/m ³	-	TWA: 3.5 mg/m ³
1333-86-4			TWA: 10 mg/m ³		
ALUMINIUM POWDER	TWA: 1 mg/m ³	TWA: 3 mg/m ³	Ceiling: 10 mg/m ³ TWA: 4 mg/m ³	_	TWA: 1 mg/m ³
7429-90-5	1 177 (. 1 1119/111	TWA: 1 mg/m ³	TWA: 1.5 mg/m ³	-	' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' '
		STEL: 10 mg/m ³	- 1. 3		
		STEL: 3 mg/m ³			
2-BUTANONE OXIME	-	-	-	TWA: 1 mg/m ³	-
96-29-7				TWA: 0.3 ppm STEL: 2.4 ppm	
				STEL: 2.4 ppm STEL: 8 mg/m ³	
				Sk*	
		•			

MINERAL OIL 8042-47-5	-	-	-	TWA: 5 STEL: 20		-
Chemical name		Sweden	Switzerlan	d	Un	ited Kingdom
CALCIUM CARBON 471-34-1	ATE	-	TWA: 3 mg/m ³ TWA: 10 mg/m ³			-
CARBON BLACH 1333-86-4	<	NGV: 3 mg/m ³	-		TWA: 3.5 mg/m ³ STEL: 7 mg/m ³	
ALUMINIUM POWE 7429-90-5	DER	NGV: 5 mg/m ³ NGV: 2 mg/m ³		TWA: 3 mg/m³ TWA: 10 r TWA: 10 mg/m³ TWA: 4 r STEL: 30 r		/A: 10 mg/m³ VA: 4 mg/m³ EL: 30 mg/m³ EL: 12 mg/m³
MINERAL OIL 8042-47-5		-	TWA: 5 mg/m³		-	

Biological occupational exposure limits

Chemical name	Eur	opean Union	Αι	ıstria	Bulgar	ia	Croatia		Czech Republic
CARBON BLACK 1333-86-4		-	(No	ote 1)	-		-		-
ALUMINIUM POWDER		-	60 µg/g (Creatinine -	-		200 μg/L - urin		-
7429-90-5				luminum) -			(Aluminum) - at t		
				nd of work			end of the work s	nitt	
				ne end of a eek/end of					
				shift					
				· · · · · ·					
				ote 1)	_				
Chemical name		Denmark	Fir	nland	Franc	<u>e </u>	Germany DFG		Germany TRGS
ALUMINIUM POWDER 7429-90-5		-		-	-		50 μg/g Creatini (urine - Aluminu		50 µg/g Creatinine (urine - Aluminum
7429-90-5							for long-term		for long-term
							exposures: at the		exposures: at the
									end of the shift after
							several shifts)		several shifts)
							50 μg/g Creatinir		
							BAT (for long-te		
							exposures: at the		
							end of the shift a several shifts) ur		
							15 µg/g Creatinir		
							BAR (for long-te		
							exposures: at th		
							end of the shift a		
							several shifts) ur	ine	
Chemical name		Latvia		Luxer	nbourg		Romania		Slovakia
ALUMINIUM POWDER		50 μg/g Crea			-				g/g creatinine (urine
7429-90-5		urine (Aluminu of shift	,			(Alumin	um) - end of shift	- Alu	minum not critical)
Chemical name		Sloveni		Sr	ain	S	Switzerland	U	Jnited Kingdom
	ALUMINIUM POWDER 50 µg/L - ui				-		creatinine (urine		-
7429-90-5		(Aluminum)	- for		- Alumir		num after several		
		long-term expo					(for long-term		
	ļt	the end of the v					xposures))		
		after seve					1 µmol/mmol itinine (urine -		
		consecutive w	orkuays				um after several		
							(for long-term		
							xposures))		

Note 1: Details about BEL values can be found in Annex 2 of the Austrian Ordinance on Health Monitoring in the Workplace.

Chemical name	Oral	Dermal	Inhalation
CALCIUM CARBONATE 471-34-1	-	-	6.36 mg/m³ [5] [6]
VINYL OXIMINOSILANE 2224-33-1	-	0.15 mg/kg bw/day [4] [6]	1.06 mg/m³ [4] [6]
STEARIC ACID 57-11-4	-	10 mg/kg bw/day [4] [6]	17.632 mg/m³ [4] [6]
CARBON BLACK 1333-86-4	-	-	1 mg/m³ [4] [6] 0.5 mg/m³ [5] [6]
OXIMINOSILANE 34206-40-1	-	0.134 mg/kg bw/day [4] [6]	0.942 mg/m³ [4] [6]
2-BUTANONE OXIME 96-29-7	-	1.3 mg/kg bw/day [4] [6] 2.5 mg/kg bw/day [4] [7]	9 mg/m³ [4] [6] 3.33 mg/m³ [5] [6]
MINERAL OIL 8042-47-5	-	217.05 mg/kg bw/day [4] [6]	164.56 mg/m³ [4] [6]

Notes

[4] Systemic health effects.
[5] Local health effects.
[6] Long term.
[7] Short term.

Derived No Effect Level (DNEL) - General Public

Chemical name	Oral	Dermal	Inhalation
CALCIUM CARBONATE	6.1 mg/kg bw/day [4] [6]	-	1.06 mg/m³ [5] [6]
471-34-1	6.1 mg/kg bw/day [4] [7]		
VINYL OXIMINOSILANE	0.075 mg/kg bw/day [4] [6]	-	0.26 mg/m³ [4] [6]
2224-33-1			
STEARIC ACID	2.5 mg/kg bw/day [4] [6]	-	4.348 mg/m ³ [4] [6]
57-11-4			
CARBON BLACK	-	-	0.06 mg/m³ [4] [6]
1333-86-4			
OXIMINOSILANE	0.067 mg/kg bw/day [4] [6]	-	0.232 mg/m³ [4] [6]
34206-40-1			-
2-BUTANONE OXIME	-	1.5 mg/kg bw/day [4] [6]	2.7 mg/m³ [4] [6]
96-29-7		1.5 mg/kg bw/day [4] [7]	2 mg/m³ [5] [6]
MINERAL OIL	25 mg/kg bw/day [4] [6]	-	34.78 mg/m³ [4] [6]
8042-47-5			

Notes

[4] Systemic health effects.
[5] Local health effects.
[6] Long term.
[7] Short term.

Predicted No Effect Concentration (PNEC)

Chemical name	Freshwater	Freshwater	Marine water	Marine water	Air
		(intermittent release)		(intermittent release)	
VINYL OXIMINOSILANE	0.01919 mg/L	-	0.001919 mg/L	-	-
2224-33-1					
OXIMINOSILANE	0.0171 mg/L	-	0.00171 mg/L	-	-
34206-40-1					
GAMMA-AMINOPROPYL	0.5 mg/L	2.05 mg/L	0.05 mg/L	-	-
TRIMETHOXYSILANE					
13822-56-5					
2-BUTANONE OXIME	0.256 mg/L	0.118 mg/L	-	-	-
96-29-7					

Chemical name	Freshwater sediment	Marine sediment	Sewage treatment	Soil	Food chain
CALCIUM CARBONATE 471-34-1	-	-	100 mg/L	-	-
VINYL OXIMINOSILANE 2224-33-1	1136.562 mg/kg sediment dw	113.656 mg/kg sediment dw	4.06 mg/L	133.8 mg/kg soil dw	3.333 mg/kg food
ALUMINIUM POWDER 7429-90-5	-	-	20 mg/L	-	-
OXIMINOSILANE 34206-40-1	9835.346 mg/kg sediment dw	983.535 mg/kg sediment dw	4.825 mg/L	1157.93 mg/kg soil dw	2.97 mg/kg food
GAMMA-AMINOPROPYL TRIMETHOXYSILANE 13822-56-5	1.8 mg/kg sediment dw	0.18 mg/kg sediment dw	0.81 mg/L	0.069 mg/kg soil dw	11.1 mg/kg food
2-BUTANONE OXIME 96-29-7	-	-	177 mg/L	-	-

8.2. Exposure controls

Engineering controls No information available.

Personal protective equipment

Eye/face protection Appropriate eye/face protection should be selected and used according to the chemical

nature, hazards and use of this product and safety requirements of the local jurisdiction.

Hand protection Wear suitable gloves.

Skin and body protectionWear suitable protective clothing.

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators.

Thermal hazards No information available.

Other protective equipment No information available.

Environmental exposure controls No information available.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Paste / Gel Liquid

Color Black

Odor No information available Odor threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

Melting point / freezing point No data available Boiling point / boiling No data available

range

Polymerization Flammability (solid, gas)No data available

None known

Flammability Limit in Air
Upper flammability limit:
No data available
No data available

Flash point > 95 °C

Autoignition temperature No data available

> 95 °C Tag Closed Cup
No data available Decomposition
temperature

pH No data available

pH (as aqueous solution)No data available
None known

Kinematic viscosity No Data Available Dynamic viscosity No data available

Water solubilityNo data availableNot applicablePolymerizationSolubility(ies)No Data AvailableNone knownPartition coefficientNo Data AvailableNone known

Vapor pressure <5 mmHg @ 70°F

Relative density 1.34

Bulk density No data available Density No data available

Vapor density 3 Air = 1

Particle characteristics

Particle Size No information available Particle Size Distribution No information available

9.2. Other information

VOC content <3%

9.2.1. Information with regard to physical hazard classes

Not applicable

9.2.2. Other safety characteristics

No information available

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None. Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions
None under normal processing.

Hazardous polymerization No information available.

10.4. Conditions to avoid

Conditions to avoid Excessive heat.

10.5. Incompatible materials

Incompatible materialsNone known based on information supplied.

10.6. Hazardous decomposition products

Hazardous Decomposition Products Carbon oxides. Nitrogen oxides (NOx). Formaldehyde. May release 2-butanone oxime (ethyl methyl ketoxime) at elevated temperature.

Section 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Inhalation Specific test data for the substance or mixture is not available. Fatal if inhaled. (based on

components).

Eye contact Specific test data for the substance or mixture is not available.

Skin contact Specific test data for the substance or mixture is not available.

Ingestion Specific test data for the substance or mixture is not available.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Coughing and/ or wheezing. Difficulty in breathing.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Acute toxicity Fatal if inhaled.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document:

ATEmix (oral) 11,469.30 mg/kg ATEmix (dermal) 4,196.30 mg/kg ATEmix (inhalation-gas) 99,999.00 ppm ATEmix (inhalation-vapor) 99,999.00 mg/l ATEmix (inhalation-dust/mist) 0.433 mg/l

Unknown acute toxicity

6.402 % of the mixture consists of ingredient(s) of unknown acute oral toxicity.

2.871 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity.

50.552 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas).

50.552 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor).

9.552 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist).

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
CALCIUM CARBONATE	= 6450 mg/kg (Rat)	> 2000 mg/kg (Rat)	> 3 mg/L (Rat) 4 h
POLYDIMETHYLSILOXANE	> 24 g/kg (Rat)	-	-
STEARIC ACID	= 4600 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	-
CARBON BLACK	> 10000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 4.6 mg/m³ (Rat) 4 h
ALUMINIUM POWDER	-	-	> 0.888 mg/L (Rat) 4 h
2-BUTANONE OXIME	= 930 mg/kg (Rat)	1000 - 1800 mg/kg (Rabbit)	> 4.83 mg/L (Rat)4 h
MINERAL OIL	> 5000 mg/kg (Rat)	-	-

Skin corrosion/irritationBased on available data, the classification criteria are not met.

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitization Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for

ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	European Union	
2-BUTANONE OXIME	Carc. 1B	

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties Based on available data, the classification criteria are not met.

11.2.2. Other information

Other adverse effects No information available.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity

Unknown aquatic toxicityContains 48.681 % of components with unknown hazards to the aquatic environment.

Chemical name	Algae/aquatic plants	Fish	Toxicity to	Crustacea
			microorganisms	
2-BUTANONE OXIME	EC50: =83mg/L (72h, Desmodesmus subspicatus)	LC50: 777 - 914mg/L (96h, Pimephales promelas) LC50: =760mg/L (96h,	-	EC50: =750mg/L (48h, Daphnia magna)
		Poecilia reticulata)		
MINERAL OIL	-	LC50: >10000mg/L	-	-
		(96h, Lepomis macrochirus)		

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation

Chemical name	Partition coefficient
2-BUTANONE OXIME	0.65
MINERAL OIL	6

12.4. Mobility in soil

No information available. Mobility in soil

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment Based on available data, the classification criteria are not met.

Chemical name	PBT and vPvB assessment
CALCIUM CARBONATE	The substance is not PBT / vPvB
STEARIC ACID	The substance is not PBT / vPvB
CARBON BLACK	The substance is not PBT / vPvB
ALUMINIUM POWDER	The substance is not PBT / vPvB
2-BUTANONE OXIME	The substance is not PBT / vPvB
MINERAL OIL	The substance is not PBT / vPvB

12.6. Endocrine disrupting properties

Endocrine disrupting properties Based on available data, the classification criteria are not met.

12.7. Other adverse effects

Other adverse effects No information available.

PMT or vPvM properties Based on available data, the classification criteria are not met.

Section 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused

products

Dispose of in accordance with local regulations. Dispose of waste in accordance with

environmental legislation.

Contaminated packaging Do not reuse empty containers.

Other information No information available.

Section 14: Transport information

<u>IATA</u>

14.1 UN number or ID number Not regulated Not regulated 14.2 UN proper shipping name 14.3 Transport hazard class(es) Not regulated 14.4 Packing group Not regulated 14.5 Environmental hazards Not applicable

14.6 Special precautions for user

Special Provisions None

IMDG

14.1 UN number or ID number Not regulated 14.2 UN proper shipping name Not regulated 14.3 Transport hazard class(es) Not regulated 14.4 Packing group Not regulated 14.5 Environmental hazards Not applicable

14.6 Special precautions for user

Special Provisions

None 14.7 Maritime transport in bulk

No information available

according to IMO instruments

RID

14.1 UN number or ID number
 14.2 UN proper shipping name
 14.3 Transport hazard class(es)
 14.4 Packing group
 14.5 Environmental hazards
 Not regulated Not regulated Not applicable

14.6 Special precautions for user

Special Provisions None

ADR

14.1UN number or ID numberNot regulated14.2UN proper shipping nameNot regulated14.3Transport hazard class(es)Not regulated14.4Packing groupNot regulated14.5Environmental hazardsNot applicable

14.6 Special precautions for user

Special Provisions None

ADN

14.1 UN number or ID number
 14.2 UN proper shipping name
 14.3 Transport hazard class(es)
 14.4 Packing group
 14.5 Environmental hazard
 Not regulated Not regulated Not applicable

14.6 Special precautions for user

Special Provisions None

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

<u>France</u>

Occupational Illnesses (R-463-3, France)

Chemical name	French RG number
CARBON BLACK - 1333-86-4	RG 16,RG 16bis
ALUMINIUM POWDER - 7429-90-5	RG 32
	RG 16,RG 16bis
MINERAL OIL - 8042-47-5	RG 36bis

Germany

Water hazard class (WGK) strongly hazardous to water (WGK 3)

Netherlands

Carcinogenic, mutagenic and reproductive toxic effects

Chemical name	Netherlands - List of Carcinogens	Netherlands - List of Mutagens	Netherlands - List of Reproductive Toxins
2-BUTANONE OXIME	Present	-	-

Ordinance on the Incentive Tax on Volatile Organic Compounds (OVOC) SR 814.018 Not applicable WPO (GSchV) SR 814.201; WPA (GSchG) SR 814.20 Not applicable

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work.

Authorizations and/or restrictions on use:

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII)

Chemical name	Restricted substance per REACH Annex XVII	Substance subject to authorization per REACH Annex XIV
CALCIUM CARBONATE - 471-34-1	75	-
CARBON BLACK - 1333-86-4	75	-
ALUMINIUM POWDER - 7429-90-5	75	-
2-BUTANONE OXIME - 96-29-7	75	-
	28	

Persistent Organic Pollutants

Not applicable

Dangerous substance category per Seveso Directive (2012/18/EU)

H2 - ACUTE TOXIC

Ozone-depleting substances (ODS) Regulation (EU) 2024/590

Not applicable

EU - Plant Protection Products (1107/2009/EC)

EO - Flant Frotection Froducts (From 2003/EO)				
Chemical name	EU - Plant Protection Products (1107/2009/EC)			
CALCIUM CARBONATE - 471-34-1	Plant protection agent			
CARBON BLACK - 1333-86-4	Plant protection agent			
MINERAL OIL - 8042-47-5	Plant protection agent			

International Inventories

Complies **TSCA** DSL/NDSL Complies **EINECS/ELINCS** Does not comply **ENCS** Does not comply Complies **IECSC** Complies KECI **PICCS** Complies Complies AICS **NZIoC** Complies

TCSI Contact supplier for inventory compliance status

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing Chemicals Inventory

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

TCSI - Taiwan Chemical Substance Inventory

15.2. Chemical safety assessment

Chemical Safety Report No information available

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of any hazard and/or precautionary statements referred to under Sections 2-15

H228 - Flammable solid

H261 - In contact with water releases flammable gas

H301 - Toxic if swallowed

H312 - Harmful in contact with skin

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H318 - Causes serious eve damage

H336 - May cause drowsiness or dizziness

H350 - May cause cancer

H370 - Causes damage to organs

H373 - May cause damage to organs through prolonged or repeated exposure

Legend

SVHC: Substances of Very High Concern for Authorization:
PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances
vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances

STOT: Specific Target Organ Toxicity

ATE: Acute Toxicity Estimate LC50: 50% Lethal Concentration

LD50: 50% Lethal Dose

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value * Skin designation

+ Sensitizers

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - vapor	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitization	Calculation method
Skin sensitization	Calculation method
Mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Chronic aquatic toxicity	Calculation method
Acute aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR)

U.S. Environmental Protection Agency ChemView Database

European Food Safety Authority (EFSA)

European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA_RAC)

European Chemicals Agency (ECHA) (ECHA_API)

Environmental Protection Agency

Acute Exposure Guideline Level(s) (AEGL(s))

U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act

U.S. Environmental Protection Agency High Production Volume Chemicals

Food Research Journal

Hazardous Substance Database

International Uniform Chemical Information Database (IUCLID)

National Institute of Technology and Evaluation (NITE)

Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)

NIOSH (National Institute for Occupational Safety and Health)

National Library of Medicine's ChemID Plus (NLM CIP)

National Library of Medicine's PubMed database (NLM PUBMED)

U.S. National Toxicology Program (NTP)

New Zealand's Chemical Classification and Information Database (CCID)

Organization for Economic Co-operation and Development Environment, Health, and Safety Publications

Organization for Economic Co-operation and Development High Production Volume Chemicals Program

Organization for Economic Co-operation and Development Screening Information Data Set

World Health Organization

Revision Date

06-Feb-2025

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006 Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet