



Revision Date 22-Jul-2024

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Version 3

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Code 80045
Product Name 51D PIPE JOINT COMPOUND 16.2 FL.OZ

Other means of identification

Contains ROSIN

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Sealant
Uses advised against No information available

1.3. Details of the supplier of the safety data sheet

Only Representative (OR)

ITW Performance Polymers
Bay 150
Shannon Industrial Estate
Co. Clare
Ireland
V14 DF82
353(61)771500
353(61)471285
customerservice.shannon@itwpp.com

For further information, please contact

Contact Point ITW Permatex
6875 Parkland Blvd.
Solon, Ohio 44139 USA
Telephone: 1-87-Permatex
(866) 732-9502

1.4. Emergency telephone number

24-hour emergency phone number - §45 - (EC)1272/2008	
Europe	112
Austria	01 406 43 43
Belgium	070 245 245
Denmark	+ 45 8212 1212
Finland	0800 147 111/ 09 471 977
France	+33 (0)1 45 42 59 59
Germany	+49 228 192 40
Ireland	01 809 2166
Italy	0382-24444

Netherlands	+31 (0)88 755 8000
Norway	22 59 13 00
Poland	112
Portugal	+351 800 250 250
Slovenia	112
Spain	+34 91 562 04 20
Sweden	112
Switzerland	145
United Kingdom	111
Bulgaria	+359 2 9154 233
Croatia	+3851 2348 342
Cyprus	1401
Czech Republic	+420 224 919 293/ +420 224 915 402
Estonia	16662/ (+372) 7943 794
Greece	(003) 2107793777
Hungary	+36 80 201 199
Iceland	543 2222
Latvia	+371 67042473
Liechtenstein	01 406 43 43
Lithuania	+370 (85) 2362052
Luxembourg	(+352) 8002 5500
Romania	+40213183606
Slovakia	+421 2 5477 4166
Malta	112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flammable liquids	Category 3 - (H226)
Skin sensitization	Category 1 - (H317)
Chronic aquatic toxicity	Category 3 - (H412)

2.2. Label elements

Contains ROSIN



Signal word

Warning

Hazard statements

H226 - Flammable liquid and vapor.

H317 - May cause an allergic skin reaction. H412 - Harmful to aquatic life with long lasting effects.

P321 - Specific treatment (see supplemental first aid instructions on this label). P261 - Avoid breathing dust/fume/gas/mist/vapors/spray. P272 - Contaminated work clothing should not be allowed out of the workplace. P280 - Wear protective gloves. P273 - Avoid release to the environment. P210 - Keep away from open flames/hot surfaces. - No smoking. P233 - Keep container tightly closed. P242 - Use only non-sparking tools. P243 - Take precautionary measures against static discharge.

22.3455 % of the mixture consists of ingredient(s) of unknown acute oral toxicity.

13.9955 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity.

35.8155 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas).

35.8155 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor).

35.8155 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist).

Unknown aquatic toxicity

Contains 2.6355 % of components with unknown hazards to the aquatic environment.

2.3. Other hazards

Harmful to aquatic life.

Endocrine Disruptor Information**SECTION 3: Composition/information on ingredients****3.1 Substances**

Chemical name	Weight-%	REACH registration No.	EC No (EU Index No)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)
ROSIN 8050-09-7	20 - <25%	Registration no. 01-211948041 8-32-XXXX	(650-015-00-7) 232-475-7	Skin Sens. 1 (H317)	-	-	-
ETHANOL 64-17-5	10 - <20%		(603-002-00-5) 200-578-6	Flam. Liq. 2 (H225)	-	-	-
2-PROPANOL 67-63-0	1 - <2.5%		(603-117-00-0) 200-661-7	Eye Irrit. 2 (H319) STOT SE 3 (H336) Flam. Liq. 2 (H225)	-	-	-
METHANOL 67-56-1	0.5 - <1%		(603-001-00-X) 200-659-6	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370) Flam. Liq. 2 (H225)	STOT SE 1 :: C>=10% STOT SE 2 :: 3%<=C<10%	-	-
TITANIUM DIOXIDE 13463-67-7	0.1 - <0.5%	Registration no: 01-211948937 9-17-XXXX	(022-006-00-2) 236-675-5	Carc. 2 (H351i)	-	-	-
CARBON BLACK 1333-86-4	0.1 - <0.5%	Registration no. 01-211938482 2-32-XXXX	215-609-9 435-640-3	-	-	-	-
SILICA, QUARTZ 14808-60-7	0.1 - <0.5%	Exempt	238-878-4	-	-	-	-
METHYL ISOBUTYL KETONE 108-10-1	0.1 - <0.5%		(606-004-00-4) 203-550-1	Acute Tox. 4 (H332) Eye Irrit. 2 (H319) Carc. 2 (H351) STOT SE 3 (H335) Flam. Liq. 2 (H225)	-	-	-

				(EUH066)			
--	--	--	--	----------	--	--	--

Full text of H- and EUH-phrases: see section 16

Acute Toxicity Estimate

No information available

Chemical name	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapor - mg/L	Inhalation LC50 - 4 hour - gas - ppm
ROSIN 8050-09-7	7600	2500	No data available	No data available	No data available
ETHANOL 64-17-5	7060	No data available	116.9 133.8	No data available	No data available
2-PROPANOL 67-63-0	1870	4059	No data available	30.1002	No data available
METHANOL 67-56-1	6200	Methanol	6200	15840	No data available
TITANIUM DIOXIDE 13463-67-7	10000	No data available	5.09	No data available	No data available
CARBON BLACK 1333-86-4	15400	2000	0.0046	No data available	No data available
METHYL ISOBUTYL KETONE 108-10-1	2080	3000	No data available	11 + 8.1922	No data available

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Remove to fresh air.
Eye contact	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.
Skin contact	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a physician.
Ingestion	Rinse mouth.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	No information available.
----------	---------------------------

4.3. Indication of any immediate medical attention and special treatment needed

Effects of Exposure	No information available.
Note to physicians	Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Large Fire CAUTION: Use of water spray when fighting fire may be inefficient.

Unsuitable extinguishing media Do not scatter spilled material with high pressure water streams.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical No information available.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Personal precautions Ensure adequate ventilation.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Advice on safe handling Ensure adequate ventilation.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed in a dry and well-ventilated place.

7.3. Specific end use(s)

Specific use(s)

Automotive Sealant.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Exposure Limits**

This product, as supplied, does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies.

Chemical name	European Union	Austria	Belgium	Bulgaria	Croatia
ROSIN 8050-09-7	-	-	-	-	TWA: 0.05 mg/m ³ STEL: 0.15 mg/m ³ Skin Sensitisation
ETHANOL 64-17-5	-	TWA: 1000 ppm TWA: 1900 mg/m ³ STEL 2000 ppm STEL 3800 mg/m ³	TWA: 1000 ppm TWA: 1907 mg/m ³	TWA: 1000 mg/m ³	TWA: 1000 ppm TWA: 1900 mg/m ³
2-PROPANOL 67-63-0	-	TWA: 200 ppm TWA: 500 mg/m ³ STEL 800 ppm STEL 2000 mg/m ³	TWA: 200 ppm TWA: 500 mg/m ³ STEL: 400 ppm STEL: 1000 mg/m ³	STEL: 1225.0 mg/m ³ TWA: 980.0 mg/m ³	TWA: 400 ppm TWA: 999 mg/m ³ STEL: 500 ppm STEL: 1250 mg/m ³
METHANOL 67-56-1	TWA: 200 ppm TWA: 260 mg/m ³ *	TWA: 200 ppm TWA: 260 mg/m ³ STEL 800 ppm STEL 1040 mg/m ³ H*	TWA: 200 ppm TWA: 266 mg/m ³ STEL: 250 ppm STEL: 333 mg/m ³ D*	TWA: 200 ppm TWA: 260.0 mg/m ³ K*	TWA: 200 ppm TWA: 260 mg/m ³ *
TITANIUM DIOXIDE 13463-67-7	-	TWA: 5 mg/m ³ STEL 10 mg/m ³	TWA: 10 mg/m ³	TWA: 10.0 mg/m ³ TWA: 1.0 mg/m ³	TWA: 10 mg/m ³ TWA: 4 mg/m ³
CARBON BLACK 1333-86-4	-	-	TWA: 3 mg/m ³	-	TWA: 3.5 mg/m ³ STEL: 7 mg/m ³
SILICA, QUARTZ 14808-60-7	TWA: 0.1 mg/m ³	TWA: 0.05 mg/m ³	TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³
METHYL ISOBUTYL KETONE 108-10-1	TWA: 20 ppm TWA: 83 mg/m ³ STEL: 50 ppm STEL: 208 mg/m ³	TWA: 20 ppm TWA: 83 mg/m ³ STEL 50 ppm STEL 208 mg/m ³ H*	TWA: 20 ppm TWA: 83 mg/m ³ STEL: 50 ppm STEL: 208 mg/m ³	STEL: 200 mg/m ³ TWA: 50 mg/m ³	TWA: 20 ppm TWA: 83 mg/m ³ STEL: 50 ppm STEL: 208 mg/m ³
Chemical name	Cyprus	Czech Republic	Denmark	Estonia	Finland
ROSIN 8050-09-7	-	TWA: 1 mg/m ³ S+	-	-	-
ETHANOL 64-17-5	-	TWA: 1000 mg/m ³ Ceiling: 3000 mg/m ³	TWA: 1000 ppm TWA: 1900 mg/m ³ STEL: 2000 ppm STEL: 3800 mg/m ³	TWA: 500 ppm TWA: 1000 mg/m ³ STEL: 1000 ppm STEL: 1900 mg/m ³	TWA: 1000 ppm TWA: 1900 mg/m ³ STEL: 1300 ppm STEL: 2500 mg/m ³
2-PROPANOL 67-63-0	-	TWA: 500 mg/m ³ Ceiling: 1000 mg/m ³ D*	TWA: 200 ppm TWA: 490 mg/m ³ STEL: 400 ppm STEL: 980 mg/m ³	TWA: 150 ppm TWA: 350 mg/m ³ STEL: 250 ppm STEL: 600 mg/m ³	TWA: 200 ppm TWA: 500 mg/m ³ STEL: 250 ppm STEL: 620 mg/m ³
METHANOL 67-56-1	* TWA: 200 ppm TWA: 260 mg/m ³	TWA: 250 mg/m ³ Ceiling: 1000 mg/m ³ D*	TWA: 200 ppm TWA: 260 mg/m ³ H* STEL: 400 ppm STEL: 520 mg/m ³	TWA: 200 ppm TWA: 250 mg/m ³ STEL: 250 ppm STEL: 350 mg/m ³ A*	TWA: 200 ppm TWA: 270 mg/m ³ STEL: 250 ppm STEL: 330 mg/m ³ iho*
TITANIUM DIOXIDE 13463-67-7	-	-	TWA: 6 mg/m ³ STEL: 12 mg/m ³	TWA: 5 mg/m ³	-
CARBON BLACK	-	TWA: 2.0 mg/m ³	TWA: 3.5 mg/m ³	TWA: 3 mg/m ³	TWA: 3.5 mg/m ³

1333-86-4			STEL: 7 mg/m ³		STEL: 7 mg/m ³
SILICA, QUARTZ 14808-60-7	TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³	TWA: 0.3 mg/m ³ TWA: 0.1 mg/m ³ STEL: 0.6 mg/m ³ STEL: 0.2 mg/m ³	TWA: 0.1 mg/m ³	TWA: 0.05 mg/m ³ TWA: 0.1 mg/m ³
METHYL ISOBUTYL KETONE 108-10-1	STEL: 50 ppm STEL: 208 mg/m ³ TWA: 20 ppm TWA: 83 mg/m ³	TWA: 80 mg/m ³ Ceiling: 200 mg/m ³ D*	TWA: 20 ppm TWA: 83 mg/m ³ H* STEL: 208 mg/m ³ STEL: 50 ppm	TWA: 20 ppm TWA: 83 mg/m ³ STEL: 50 ppm STEL: 208 mg/m ³	TWA: 20 ppm TWA: 80 mg/m ³ STEL: 50 ppm STEL: 210 mg/m ³
Chemical name	France	Germany TRGS	Germany DFG	Greece	Hungary
ROSIN 8050-09-7	TWA: 0.1 mg/m ³	-	skin sensitizer	-	-
ETHANOL 64-17-5	TWA: 1000 ppm TWA: 1900 mg/m ³ STEL: 5000 ppm STEL: 9500 mg/m ³	TWA: 200 ppm TWA: 380 mg/m ³	TWA: 200 ppm TWA: 380 mg/m ³ Peak: 800 ppm Peak: 1520 mg/m ³	TWA: 1000 ppm TWA: 1900 mg/m ³	TWA: 1000 ppm TWA: 1900 mg/m ³ STEL: 2000 ppm STEL: 3800 mg/m ³
2-PROPANOL 67-63-0	STEL: 400 ppm STEL: 980 mg/m ³	TWA: 200 ppm TWA: 500 mg/m ³	TWA: 200 ppm TWA: 500 mg/m ³ Peak: 400 ppm Peak: 1000 mg/m ³	TWA: 400 ppm TWA: 980 mg/m ³ STEL: 500 ppm STEL: 1225 mg/m ³	TWA: 500 mg/m ³ TWA: 200 ppm STEL: 1000 mg/m ³ STEL: 400 ppm b*
METHANOL 67-56-1	TWA: 200 ppm TWA: 260 mg/m ³ STEL: 1000 ppm STEL: 1300 mg/m ³ *	TWA: 100 ppm TWA: 130 mg/m ³ H*	TWA: 100 ppm TWA: 130 mg/m ³ Peak: 200 ppm Peak: 260 mg/m ³ *	TWA: 200 ppm TWA: 260 mg/m ³ STEL: 250 ppm STEL: 325 mg/m ³ *	TWA: 260 mg/m ³ TWA: 200 ppm b*
TITANIUM DIOXIDE 13463-67-7	TWA: 10 mg/m ³	TWA: 1.25 mg/m ³ TWA: 10 mg/m ³	TWA: 0.3 mg/m ³ Peak: 2.4 mg/m ³	TWA: 10 mg/m ³ TWA: 5 mg/m ³	-
CARBON BLACK 1333-86-4	TWA: 3.5 mg/m ³	-	-	TWA: 3.5 mg/m ³ STEL: 7 mg/m ³	TWA: 3 mg/m ³
SILICA, QUARTZ 14808-60-7	TWA: 0.1 mg/m ³	-	-	TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³
METHYL ISOBUTYL KETONE 108-10-1	TWA: 20 ppm TWA: 83 mg/m ³ STEL: 50 ppm STEL: 208 mg/m ³	TWA: 20 ppm TWA: 83 mg/m ³ H*	TWA: 20 ppm TWA: 83 mg/m ³ Peak: 40 ppm Peak: 166 mg/m ³ *	TWA: 100 ppm TWA: 410 mg/m ³ STEL: 100 ppm STEL: 410 mg/m ³ *	TWA: 20 ppm TWA: 83 mg/m ³ STEL: 208 mg/m ³ STEL: 50 ppm
Chemical name	Ireland	Italy MDLPS	Italy AIDII	Latvia	Lithuania
ROSIN 8050-09-7	TWA: 0.05 mg/m ³ STEL: 0.15 mg/m ³ Sens+	-	senR+ senD+	TWA: 4 mg/m ³	-
ETHANOL 64-17-5	STEL: 1000 ppm	-	STEL: 1000 ppm STEL: 1884 mg/m ³	TWA: 1000 mg/m ³	TWA: 500 ppm TWA: 1000 mg/m ³ STEL: 1000 ppm STEL: 1900 mg/m ³
2-PROPANOL 67-63-0	TWA: 200 ppm STEL: 400 ppm Sk*	-	TWA: 200 ppm TWA: 492 mg/m ³ STEL: 400 ppm STEL: 983 mg/m ³	TWA: 350 mg/m ³ STEL: 600 mg/m ³	TWA: 150 ppm TWA: 350 mg/m ³ STEL: 250 ppm STEL: 600 mg/m ³
METHANOL 67-56-1	TWA: 200 ppm TWA: 260 mg/m ³ STEL: 600 ppm STEL: 780 mg/m ³ Sk*	TWA: 200 ppm TWA: 260 mg/m ³ cute*	TWA: 200 ppm TWA: 262 mg/m ³ STEL: 250 ppm STEL: 328 mg/m ³ cute*	TWA: 200 ppm TWA: 260 mg/m ³ Ada*	O* TWA: 200 ppm TWA: 260 mg/m ³
TITANIUM DIOXIDE 13463-67-7	TWA: 10 mg/m ³ TWA: 4 mg/m ³ STEL: 30 mg/m ³ STEL: 12 mg/m ³	-	TWA: 10 mg/m ³	TWA: 10 mg/m ³	TWA: 5 mg/m ³
CARBON BLACK 1333-86-4	TWA: 3 mg/m ³ STEL: 15 mg/m ³	-	TWA: 3 mg/m ³	-	-

SILICA, QUARTZ 14808-60-7	TWA: 0.1 mg/m ³ STEL: 0.3 mg/m ³	TWA: 0.1 mg/m ³	TWA: 0.025 mg/m ³	TWA: 0.1 mg/m ³	TWA: 0.1 ppm
METHYL ISOBUTYL KETONE 108-10-1	TWA: 20 ppm TWA: 83 mg/m ³ STEL: 50 ppm STEL: 208 mg/m ³ Sk*	TWA: 20 ppm TWA: 83 mg/m ³ STEL: 50 ppm STEL: 208 mg/m ³	TWA: 20 ppm TWA: 82 mg/m ³ STEL: 75 ppm STEL: 307 mg/m ³	TWA: 20 ppm TWA: 83 mg/m ³ STEL: 50 ppm STEL: 208 mg/m ³	TWA: 20 ppm TWA: 83 mg/m ³ STEL: 50 ppm STEL: 208 mg/m ³
Chemical name	Luxembourg	Malta	Netherlands	Norway	Poland
ETHANOL 64-17-5	-	-	TWA: 137 ppm TWA: 260 mg/m ³ STEL: 1000 ppm STEL: 1900 mg/m ³ H*	TWA: 500 ppm TWA: 950 mg/m ³ STEL: 625 ppm STEL: 1187.5 mg/m ³	TWA: 1900 mg/m ³
2-PROPANOL 67-63-0	-	-	-	TWA: 100 ppm TWA: 245 mg/m ³ STEL: 150 ppm STEL: 306.25 mg/m ³	STEL: 1200 mg/m ³ TWA: 900 mg/m ³ skóra*
METHANOL 67-56-1	Peau* TWA: 200 ppm TWA: 260 mg/m ³	skin* TWA: 200 ppm TWA: 260 mg/m ³	TWA: 100 ppm TWA: 133 mg/m ³ H*	TWA: 100 ppm TWA: 130 mg/m ³ STEL: 150 ppm STEL: 162.5 mg/m ³ H*	STEL: 300 mg/m ³ TWA: 100 mg/m ³ Prohibited - substances or mixtures containing Methanol in weight concentration >3%;except fuels used in the model building, powerboating, fuel cells and biofuels skóra*
TITANIUM DIOXIDE 13463-67-7	-	-	-	TWA: 5 mg/m ³ STEL: 10 mg/m ³	STEL: 30 mg/m ³ TWA: 10 mg/m ³
CARBON BLACK 1333-86-4	-	-	-	TWA: 3.5 mg/m ³ STEL: 7 mg/m ³	TWA: 4 mg/m ³
SILICA, QUARTZ 14808-60-7	-	-	TWA: 0.075 mg/m ³	TWA: 0.05 mg/m ³ TWA: 0.1 mg/m ³ TWA: 0.3 mg/m ³ STEL: 0.9 mg/m ³ STEL: 0.15 mg/m ³ STEL: 0.3 mg/m ³	TWA: 0.1 mg/m ³
METHYL ISOBUTYL KETONE 108-10-1	STEL: 50 ppm STEL: 208 mg/m ³ TWA: 20 ppm TWA: 83 mg/m ³	STEL: 50 ppm STEL: 208 mg/m ³ TWA: 20 ppm TWA: 83 mg/m ³	TWA: 25 ppm TWA: 104 mg/m ³ STEL: 50 ppm STEL: 208 mg/m ³	TWA: 20 ppm TWA: 83 mg/m ³ STEL: 50 ppm STEL: 208 mg/m ³ H*	STEL: 200 mg/m ³ TWA: 83 mg/m ³
Chemical name	Portugal	Romania	Slovakia	Slovenia	Spain
ROSIN 8050-09-7	Sensitizer Rosin core solder thermal decomposition products Sensitizer dermal and respiratory	TWA: 0.1 mg/m ³	-	-	Sen+
ETHANOL 64-17-5	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1900 mg/m ³ STEL: 5000 ppm STEL: 9500 mg/m ³	TWA: 500 ppm TWA: 960 mg/m ³ Ceiling: 1920 mg/m ³	TWA: 960 mg/m ³ TWA: 500 ppm STEL: 1000 ppm STEL: 1920 mg/m ³	STEL: 1000 ppm STEL: 1910 mg/m ³
2-PROPANOL 67-63-0	TWA: 200 ppm STEL: 400 ppm	TWA: 81 ppm TWA: 200 mg/m ³ STEL: 203 ppm STEL: 500 mg/m ³	TWA: 200 ppm TWA: 500 mg/m ³ Ceiling: 1000 mg/m ³	TWA: 200 ppm TWA: 500 mg/m ³ STEL: 400 ppm STEL: 1000 mg/m ³	TWA: 200 ppm TWA: 500 mg/m ³ STEL: 400 ppm STEL: 1000 mg/m ³
METHANOL	TWA: 200 ppm	TWA: 200 ppm	TWA: 200 ppm	TWA: 200 ppm	TWA: 200 ppm

67-56-1	TWA: 260 mg/m ³ STEL: 250 ppm Cutânea*	TWA: 260 mg/m ³ P*	TWA: 260 mg/m ³ K*	TWA: 260 mg/m ³ STEL: 800 ppm STEL: 1040 mg/m ³ K*	TWA: 266 mg/m ³ via dérmica*
TITANIUM DIOXIDE 13463-67-7	TWA: 10 mg/m ³	TWA: 10 mg/m ³ STEL: 15 mg/m ³	TWA: 5 mg/m ³	-	TWA: 10 mg/m ³
CARBON BLACK 1333-86-4	TWA: 3 mg/m ³	-	TWA: 2 mg/m ³ TWA: 10 mg/m ³	-	TWA: 3.5 mg/m ³
SILICA, QUARTZ 14808-60-7	TWA: 0.025 mg/m ³ TWA: 0.05 mg/m ³	TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³ STEL: 0.5 mg/m ³	TWA: 0.05 mg/m ³	TWA: 0.05 mg/m ³
METHYL ISOBUTYL KETONE 108-10-1	TWA: 20 ppm TWA: 83 mg/m ³ STEL: 50 ppm STEL: 208 mg/m ³	TWA: 20 ppm TWA: 83 mg/m ³ STEL: 50 ppm STEL: 208 mg/m ³	TWA: 20 ppm TWA: 83 mg/m ³ K* Ceiling: 166 mg/m ³	TWA: 20 ppm TWA: 83 mg/m ³ STEL: 50 ppm STEL: 208 mg/m ³ K*	TWA: 20 ppm TWA: 83 mg/m ³ STEL: 50 ppm STEL: 208 mg/m ³
Chemical name	Sweden		Switzerland		United Kingdom
ROSIN 8050-09-7	-		S+		TWA: 0.05 mg/m ³ STEL: 0.15 mg/m ³ Sen+
ETHANOL 64-17-5	NGV: 500 ppm NGV: 1000 mg/m ³ Vägledande KGV: 1000 ppm Vägledande KGV: 1900 mg/m ³		TWA: 500 ppm TWA: 960 mg/m ³ STEL: 1000 ppm STEL: 1920 mg/m ³		TWA: 1000 ppm TWA: 1920 mg/m ³ STEL: 3000 ppm STEL: 5760 mg/m ³
2-PROPANOL 67-63-0	NGV: 150 ppm NGV: 350 mg/m ³ Vägledande KGV: 250 ppm Vägledande KGV: 600 mg/m ³		TWA: 200 ppm TWA: 500 mg/m ³ STEL: 400 ppm STEL: 1000 mg/m ³		TWA: 400 ppm TWA: 999 mg/m ³ STEL: 500 ppm STEL: 1250 mg/m ³
METHANOL 67-56-1	NGV: 200 ppm NGV: 250 mg/m ³ Vägledande KGV: 250 ppm Vägledande KGV: 350 mg/m ³ H*		TWA: 200 ppm TWA: 260 mg/m ³ STEL: 400 ppm STEL: 520 mg/m ³ H*		TWA: 200 ppm TWA: 266 mg/m ³ STEL: 250 ppm STEL: 333 mg/m ³ Sk*
TITANIUM DIOXIDE 13463-67-7	NGV: 5 mg/m ³		TWA: 3 mg/m ³ TWA: 10 mg/m ³		TWA: 10 mg/m ³ TWA: 4 mg/m ³ STEL: 30 mg/m ³ STEL: 12 mg/m ³
CARBON BLACK 1333-86-4	NGV: 3 mg/m ³		-		TWA: 3.5 mg/m ³ STEL: 7 mg/m ³
SILICA, QUARTZ 14808-60-7	NGV: 0.1 mg/m ³		TWA: 0.15 mg/m ³		TWA: 0.1 mg/m ³ STEL: 0.3 mg/m ³
METHYL ISOBUTYL KETONE 108-10-1	NGV: 20 ppm NGV: 83 mg/m ³ Bindande KGV: 50 ppm Bindande KGV: 200 mg/m ³		TWA: 20 ppm TWA: 82 mg/m ³ STEL: 40 ppm STEL: 164 mg/m ³ H*		TWA: 50 ppm TWA: 208 mg/m ³ STEL: 100 ppm STEL: 416 mg/m ³ Sk*

Biological occupational exposure limits

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies.

Chemical name	European Union	Austria	Bulgaria	Croatia	Czech Republic
2-PROPANOL 67-63-0	-	-	-	50 mg/L - blood (Acetone) - at the end of the work shift 50 mg/L - urine (Acetone) - at the end of the work shift	-
METHANOL 67-56-1	-	-	-	7.0 mg/g Creatinine - urine (Methanol) - at the end of the work shift	0.47 mmol/L (urine - Methanol end of shift) 15 mg/L (urine -

					Methanol end of shift)
CARBON BLACK 1333-86-4	-	(-)	-	-	-
SILICA, QUARTZ 14808-60-7	-	(-)	-	-	-
METHYL ISOBUTYL KETONE 108-10-1	-	-	-	3.5 mg/L - urine (4-Methyl-pentan-2-on) - not critical	-
Chemical name	Denmark	Finland	France	Germany DFG	Germany TRGS
2-PROPANOL 67-63-0	-	-	-	25 mg/L (whole blood - Acetone end of shift) 25 mg/L (urine - Acetone end of shift) 25 mg/L - BAT (end of exposure or end of shift) urine 25 mg/L - BAT (end of exposure or end of shift) blood	25 mg/L (whole blood - Acetone end of shift) 25 mg/L (urine - Acetone end of shift)
METHANOL 67-56-1	-	-	- urine (Methanol) - end of shift	15 mg/L (urine - Methanol end of shift) 15 mg/L (urine - Methanol for long-term exposures: at the end of the shift after several shifts) 15 mg/L - BAT (end of exposure or end of shift) urine	15 mg/L (urine - Methanol end of shift) 15 mg/L (urine - Methanol for long-term exposures: at the end of the shift after several shifts)
METHYL ISOBUTYL KETONE 108-10-1	-	-	- urine (Methylisobutylketone) - end of shift	0.7 mg/L (urine - 4-Methylpentan-2-one end of shift) 0.7 mg/L - BAT (end of exposure or end of shift) urine	0.7 mg/L (urine - 4-Methylpentan-2-one end of shift)
Chemical name	Hungary	Ireland	Italy MDLPS	Italy AIDII	
2-PROPANOL 67-63-0	-	40 mg/L (urine - Acetone end of shift at end of workweek)	-	40 mg/L - urine (Acetone) - end of shift at end of workweek	
METHANOL 67-56-1	30 mg/L (urine - Methanol end of shift) 940 µmol/L (urine - Methanol end of shift)	15 mg/L (urine - Methanol end of shift)	-	15 mg/L - urine (Methanol) - end of shift	
METHYL ISOBUTYL KETONE 108-10-1	-	1 mg/L (urine - Methyl isobutyl ketone end of shift)	-	1 mg/L - urine (MIBK) - end of shift	
Chemical name	Latvia	Luxembourg	Romania	Slovakia	
2-PROPANOL 67-63-0	-	-	50 mg/L - urine (Acetone) - end of shift	-	
METHANOL 67-56-1	-	-	6 mg/L - urine (Methanol) - end of shift	30 mg/L (urine - Methanol end of exposure or work shift) 30 mg/L (urine - Methanol after all work shifts)	
METHYL ISOBUTYL KETONE 108-10-1	-	-	-	3.5 mg/L (urine - 4-Methyl-2-pentanone end of exposure or work	

Chemical name	Slovenia	Spain	Switzerland	shift) United Kingdom
2-PROPANOL 67-63-0	25 mg/L - blood (Acetone) - at the end of the work shift 25 mg/L - urine (Acetone) - at the end of the work shift	40 mg/L (urine - Acetone end of workweek)	25 mg/L (urine - Acetone end of shift) 0.4 mmol/L (urine - Acetone end of shift) 25 mg/L (whole blood - Acetone end of shift) 0.4 mmol/L (whole blood - Acetone end of shift)	-
METHANOL 67-56-1	15 mg/L - urine (Methanol) - at the end of the work shift; for long-term exposure: at the end of the work shift after several consecutive workdays	15 mg/L (urine - Methanol end of shift)	30 mg/L (urine - Methanol end of shift, and after several shifts (for long-term exposures)) 936 µmol/L (urine - Methanol end of shift, and after several shifts (for long-term exposures))	-
METHYL ISOBUTYL KETONE 108-10-1	0.7 mg/L - urine (4-Methylpentan-2-one) - at the end of the work shift	1 mg/L (urine - Methyl isobutyl ketone end of shift)	0.7 mg/L (urine - 4-Methylpentane-2-one end of shift)	20 µmol/L - urine (4-Methylpentan-2-one) - post shift

8.2. Exposure controls

Derived No Effect Level (DNEL) - Workers No information available

Derived No Effect Level (DNEL) - General Public No information available.

Predicted No Effect Concentration (PNEC) No information available.

Personal protective equipment

Eye/face protection No special protective equipment required.

Skin and body protection No special protective equipment required.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice.

Environmental exposure controls No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Paste / Gel Liquid
Appearance Black
Color No information available
Odor Alcohol
Odor threshold No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
Melting point / freezing point	No data available	None known
Boiling point / boiling range	82 °C	
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		None known
Upper flammability limit:	12.7%	
Lower flammability limit:	2.3%	
Flash point	25 °C	Tag Closed Cup
Autoignition temperature	No data available	None known
Decomposition temperature		None known
pH	No data available	
pH (as aqueous solution)	No data available	No information available
Kinematic viscosity	No Data Available	None known
Dynamic viscosity	No data available	None known
Water solubility	No data available	Partially soluble
Solubility(ies)	No Data Available	None known
Partition coefficient	No Data Available	None known
Vapor pressure	33 mm Hg @ 68°F	
Relative density	1.25-1.32	
Bulk density	No data available	
Density	No data available	
Vapor density	>1	Air = 1
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	

9.2. Other information

VOC content 14.2%

9.2.1. Information with regard to physical hazard classes

Not applicable

9.2.2. Other safety characteristics

No information available < 1 Butyl acetate = 1

SECTION 10: Stability and reactivity**10.1. Reactivity**

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

 Sensitivity to mechanical impact None.

 Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid None known based on information supplied.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous Decomposition Products Carbon oxides. Aldehydes. Carboxylic acids.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation	Specific test data for the substance or mixture is not available.
Eye contact	Specific test data for the substance or mixture is not available.
Skin contact	Specific test data for the substance or mixture is not available.
Ingestion	Specific test data for the substance or mixture is not available.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Numerical measures of toxicity

Acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	9,253.00
ATEmix (dermal)	8,291.00
ATEmix (inhalation-dust/mist)	50.24

22.3455 % of the mixture consists of ingredient(s) of unknown acute oral toxicity.
 13.9955 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity.
 35.8155 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas).
 35.8155 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor).
 35.8155 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist).

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
ROSIN	= 7600 mg/kg (Rat) = 3000 mg/kg (Rat)	> 2500 mg/kg (Rabbit)	= 1.5 mg/L (Rat) 4 h
ETHANOL	= 7060 mg/kg (Rat)	-	= 116.9 mg/L (Rat) 4 h = 133.8 mg/L (Rat) 4 h
2-PROPANOL	5050 mg/kg	12800 mg/kg	> 10000 ppm (Rat) 6 h
METHANOL	= 6200 mg/kg (Rat)	= 15840 mg/kg (Rabbit)	= 22500 ppm (Rat) 8 h
TITANIUM DIOXIDE	> 10000 mg/kg (Rat)	-	= 5.09 mg/L (Rat) 4 h
CARBON BLACK	> 15400 mg/kg (Rat)	> 2000 mg/kg (Rat)	> 4.6 mg/m ³ (Rat) 4 h
METHYL ISOBUTYL KETONE	= 2080 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	2000 - 4000 ppm (Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation No information available.

Serious eye damage/eye irritation No information available.

Respiratory or skin sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity No information available.

Chemical name	European Union
TITANIUM DIOXIDE	Carc. 2
METHYL ISOBUTYL KETONE	Carc. 2

Reproductive toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposure No information available.

Aspiration hazard No information available.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity The environmental impact of this product has not been fully investigated.

Unknown aquatic toxicity Contains 2.6355 % of components with unknown hazards to the aquatic environment.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
ROSIN	EC50: =400mg/L (72h, Desmodesmus subspicatus)	-	-	EC50: 3.8 - 5.4mg/L (48h, Daphnia magna)
ETHANOL	-	LC50: 12.0 - 16.0mL/L (96h, Oncorhynchus mykiss) LC50: >100mg/L (96h, Pimephales promelas) LC50: 13400 - 15100mg/L (96h, Pimephales promelas)	-	LC50: 9268 - 14221mg/L (48h, Daphnia magna) EC50: =2mg/L (48h, Daphnia magna)
2-PROPANOL	EC50: >1000mg/L (96h, Desmodesmus)	LC50: =9640mg/L (96h, Pimephales promelas)	-	EC50: =13299mg/L (48h, Daphnia magna)

	subspicatus) EC50: >1000mg/L (72h, Desmodesmus subspicatus)	LC50: =11130mg/L (96h, Pimephales promelas) LC50: >1400000µg/L (96h, Lepomis macrochirus)		
METHANOL	-	LC50: =28200mg/L (96h, Pimephales promelas) LC50: >100mg/L (96h, Pimephales promelas) LC50: 19500 - 20700mg/L (96h, Oncorhynchus mykiss) LC50: 18 - 20mL/L (96h, Oncorhynchus mykiss) LC50: 13500 - 17600mg/L (96h, Lepomis macrochirus)	-	-
METHYL ISOBUTYL KETONE	EC50: =400mg/L (96h, Pseudokirchneriella subcapitata)	LC50: 496 - 514mg/L (96h, Pimephales promelas)	-	EC50: =170mg/L (48h, Daphnia magna)

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation No information available.

Chemical name	Partition coefficient
ROSIN	7.7
ETHANOL	-0.35
2-PROPANOL	0.05
METHANOL	-0.77
METHYL ISOBUTYL KETONE	1.9

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment No information available.

Chemical name	PBT and vPvB assessment
ROSIN	The substance is not PBT / vPvB
ETHANOL	The substance is not PBT / vPvB
2-PROPANOL	The substance is not PBT / vPvB
METHANOL	The substance is not PBT / vPvB
TITANIUM DIOXIDE	The substance is not PBT / vPvB
CARBON BLACK	The substance is not PBT / vPvB
METHYL ISOBUTYL KETONE	The substance is not PBT / vPvB

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products	Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Do not reuse empty containers.

SECTION 14: Transport information

IATA

14.1 UN number or ID number	ID8000
14.2 Proper shipping name	Consumer commodity
14.3 Transport hazard class(es)	9
14.4 Packing group	Not regulated
14.5 Environmental hazard	Not applicable
14.6 Special precautions for user	

IMDG

14.1 UN number or ID number	1866
14.2 Proper shipping name	Resin Solution Flammable Liquid NOS (Petroleum Distillates) Limited Quantity (LQ)
14.3 Transport hazard class(es)	3
14.4 Packing Group	III
14.5 Environmental hazard	Not applicable
14.6 Special precautions for user	
14.7 Maritime transport in bulk according to IMO instruments	

RID

14.1 UN/ID No	1866
14.2 Proper shipping name	Resin Solution Flammable Liquid NOS (Petroleum Distillates) Limited Quantity (LQ)
14.3 Transport hazard class(es)	3
14.4 Packing Group	III
14.5 Environmental hazard	Not applicable
14.6 Special precautions for user	

ADR

14.1 UN number or ID number	1866
14.2 Proper shipping name	Resin Solution Flammable Liquid NOS (Petroleum Distillates) Limited Quantity (LQ)
14.3 Transport hazard class(es)	3
14.4 Packing Group	III
14.5 Environmental hazard	Not applicable
14.6 Special precautions for user	
Classification code	F1

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Chemical name	French RG number
ROSIN - 8050-09-7	RG 65, RG 66
ETHANOL - 64-17-5	RG 84
2-PROPANOL - 67-63-0	RG 84
METHANOL - 67-56-1	RG 84
CARBON BLACK - 1333-86-4	RG 16, RG 16bis

SILICA, QUARTZ - 14808-60-7	RG 25
METHYL ISOBUTYL KETONE - 108-10-1	RG 84

Chemical name	Netherlands - List of Carcinogens	Netherlands - List of Mutagens	Netherlands - List of Reproductive Toxins
ETHANOL	Present	-	Fertility Category 1A Development Category 1A Can be harmful via breastfeeding
SILICA, QUARTZ	Present	-	-

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work.

Authorizations and/or restrictions on use:

This product does not contain substances subject to authorization (Regulation (EC) No. 1907/2006 (REACH), Annex XIV) This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII)

Chemical name	Restricted substance per REACH Annex XVII	Substance subject to authorization per REACH Annex XIV
ROSIN - 8050-09-7	75.	-
2-PROPANOL - 67-63-0	75.	-
METHANOL - 67-56-1	69. 75.	-
TITANIUM DIOXIDE - 13463-67-7	75.	-
CARBON BLACK - 1333-86-4	75.	-
METHYL ISOBUTYL KETONE - 108-10-1	75.	-

Persistent Organic Pollutants

Not applicable

Chemical name	Lower-tier requirements (tons)	Upper-tier requirements (tons)
METHANOL - 67-56-1	500	5000

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Chemical name	EU - Plant Protection Products (1107/2009/EC)
CARBON BLACK - 1333-86-4	Plant protection agent
SILICA, QUARTZ - 14808-60-7	Plant protection agent

Chemical name	Biocidal Products Regulation (EU) No 528/2012 (BPR)
ETHANOL - 64-17-5	Product-type 1: Human hygiene Product-type 2: Disinfectants and algaecides not intended for direct application to humans or animals Product-type 4: Food and feed area
2-PROPANOL - 67-63-0	Product-type 2: Disinfectants and algaecides not intended for direct application to humans or animals Product-type 4: Food and feed area Product-type 1: Human hygiene

International Inventories

TSCA

Complies

DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Does not comply
IECSC	Complies
KECI	Complies
PICCS	Complies
AICS	Complies

Legend:

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

15.2. Chemical safety assessment

Chemical Safety Report No information available

SECTION 16: Other information**Key or legend to abbreviations and acronyms used in the safety data sheet****Full text of H-Statements referred to under section 3**

H332 - Harmful if inhaled
H319 - Causes serious eye irritation
H335 - May cause respiratory irritation
H225 - Highly flammable liquid and vapor
H301 - Toxic if swallowed
H311 - Toxic in contact with skin
H331 - Toxic if inhaled
H370 - Causes damage to organs if inhaled
H336 - May cause drowsiness or dizziness
H317 - May cause an allergic skin reaction
EUH066 - Repeated exposure may cause skin dryness or cracking

Legend

SVHC: Substances of Very High Concern for Authorization:
vPvB: Very Persistent and very Bioaccumulative (vPvB) Chemicals

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR)
U.S. Environmental Protection Agency ChemView Database
European Food Safety Authority (EFSA)
Environmental Protection Agency
Acute Exposure Guideline Level(s) (AEGL(s))
U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
U.S. Environmental Protection Agency High Production Volume Chemicals
Food Research Journal
Hazardous Substance Database
International Uniform Chemical Information Database (IUCLID)
Japan GHS Classification
Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)
NIOSH (National Institute for Occupational Safety and Health)
National Library of Medicine's ChemID Plus (NLM CIP)
National Library of Medicine's PubMed database (NLM PUBMED)
U.S. National Toxicology Program (NTP)
New Zealand's Chemical Classification and Information Database (CCID)
Organization for Economic Co-operation and Development Environment, Health, and Safety Publications
Organization for Economic Co-operation and Development High Production Volume Chemicals Program

Organization for Economic Co-operation and Development Screening Information Data Set
World Health Organization

Revision Date 22-Jul-2024

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

Illinois Tool Works Inc. believes the information contained in this data sheet is accurate as of the date compiled. However, Illinois Tool Works Inc. makes no warranty, express or implied, as to the accuracy, reliability or completeness of the information. User is responsible for evaluating whether such information or this product is fit for a particular purpose and suitable for a particular use or application. The information in this data sheet may not be valid if this product is used in combination with other products or in processes for which it was not designed. Illinois Tool Works Inc. disclaims any liability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of this product. Ensure you have the most current version of this data sheet by contacting us or reviewing our web site.

End of Safety Data Sheet

EU SDS version information - EGHS

UL release:

GHS Revision 7

2023 Q1

Full text of H-Statements referred to under section 3

H332 - Harmful if inhaled H319 - Causes serious eye irritation H335 - May cause respiratory irritation
H225 - Highly flammable liquid and vapor H301 - Toxic if swallowed H311 - Toxic in contact with skin
H331 - Toxic if inhaled H370 - Causes damage to organs if inhaled H336 - May cause drowsiness or
dizziness H317 - May cause an allergic skin reaction EUH066 - Repeated exposure may cause skin
dryness or cracking

Chemical name	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)
ROSIN	Skin Sens. 1 (H317)	
ETHANOL	Flam. Liq. 2 (H225)	
2-PROPANOL	Eye Irrit. 2 (H319) STOT SE 3 (H336) Flam. Liq. 2 (H225)	
METHANOL	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370) Flam. Liq. 2 (H225)	STOT SE 1 :: C ≥ 10% STOT SE 2 :: 3% ≤ C < 10%
TITANIUM DIOXIDE	Carc. 2 (H351i)	
METHYL ISOBUTYL KETONE	Acute Tox. 4 (H332) Eye Irrit. 2 (H319) Carc. 2 (H351) STOT SE 3 (H335) Flam. Liq. 2 (H225) (EUH066)	

Chemical name	CAS No.	French RG number
ROSIN	8050-09-7	RG 65, RG 66
ETHANOL	64-17-5	RG 84
2-PROPANOL	67-63-0	RG 84
METHANOL	67-56-1	RG 84
CARBON BLACK	1333-86-4	RG 16, RG 16bis
SILICA, QUARTZ	14808-60-7	RG 25
METHYL ISOBUTYL KETONE	108-10-1	RG 84

VOC content