



SAFETY DATA SHEET

This safety data sheet complies with the requirements of: (CLP) Regulation (EC 1272/2008)

Revision Date 10-Apr-2020

Version 2

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Code 81833
Product Name 135EA HEAVY DUTY RUBBERIZED UNDERCOATING 16OZ AE

Contains TOLUENE, STODDARD SOLVENT, BUTANE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Undercoating - Aerosol
Uses advised against No information available

1.3. Details of the supplier of the safety data sheet

Manufacturer

ITW Permatex
6875 Parkland Blvd.
Solon, Ohio 44139 USA
Telephone: 1-87-Permatex
(866) 732-9502

E-mail address:

mail@permatex.com

1.4. Emergency telephone number

24-hour emergency phone number - 800-255-3924 (00+ 1+ 813-248-0585) ChemTel

SECTION 2: HAZARDS IDENTIFICATION:

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Aspiration toxicity	Category 1 - (H304)
Skin corrosion/irritation	Category 2 - (H315)
Germ cell mutagenicity	Category 1B - (H340)
Carcinogenicity	Category 1A - (H350)
Reproductive Toxicity	Category 2 - (H361)
Specific target organ toxicity (repeated exposure)	Category 2 - (H373)

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Full text of R-phrases: see section 16

2.2. Label elements

Contains TOLUENE, STODDARD SOLVENT, BUTANE



Signal word
Danger

Statements of hazard

H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H340 - May cause genetic defects
H350 - May cause cancer
H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary Statements

P264 - Wash face, hands and any exposed skin thoroughly after handling
P280 - Wear protective gloves
P302 + P352 - IF ON SKIN: Wash with plenty of water and soap
P321 - Specific treatment (see supplemental first aid instructions on this label)
P332 + P313 - If skin irritation occurs: Get medical advice/attention
P362 + P364 - Take off all contaminated clothing and wash it before reuse
P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P308 + P313 - IF exposed or concerned: Get medical advice/attention
P405 - Store locked up
P501 - Dispose of contents/ container to an approved waste disposal plant
P260 - Do not breathe dust/fume/gas/mist/vapors/spray
P314 - Get medical advice/attention if you feel unwell
P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor
P331 - Do NOT induce vomiting

Other Information

• Not applicable

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures

Chemical Name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	REACH Registration Number
PROPANE	200-827-9	74-98-6	10 - 30	Flam. Gas 1 (H220) Press. Gas	Exempt - Annex V
ASPHALT (PETROLEUM)	232-490-9	8052-42-4	10 - 30		Not available
TOLUENE	203-625-9	108-88-3	10 - 30	Skin Irrit. 2 (H315) Repr. 2 (H361d) STOT SE 3 (H336) STOT RE 2 (H373) Asp. Tox. 1 (H304) Flam. Liq. 2 (H225)	01-2119471310-51-XXXX
TALC	238-877-9	14807-96-6	5 - 10		Exempt - Annex V
STODDARD SOLVENT	232-489-3	8052-41-3	3 - 7	Muta. 1B (H340) Carc. 1B (H350) STOT RE 1 (H372) Asp. Tox. 1 (H304)	Exempt - Volume

KAOLIN	310-194-1	1332-58-7	3 - 7		Exempt - Annex V
BUTANE	203-448-7	106-97-8	3 - 7	Carc. 1A (H350) Muta. 1B (H340) Flam. Gas 1 (H220) Press. Gas	Exempt - Volume
ACETONE	200-662-2	67-64-1	3 - 7	Eye Irrit. 2 (H319) (EUH066) STOT SE 3 (H336) Flam. Liq. 2 (H225)	01-2119471330-49-XXXX

Full text of H- and EUH-phrases: see section 16

Section 4: FIRST AID MEASURES

4.1. Description of first aid measures

General advice	Call 911 or emergency medical service. Remove and isolate contaminated clothing and shoes.
Inhalation	Move victim to fresh air. If breathing is irregular or stopped, administer artificial respiration. Administer oxygen if breathing is difficult.
Skin contact	In case of contact with liquefied gas, thaw frosted parts with lukewarm water.
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	IF SWALLOWED: Call a physician or poison control center immediately. Do NOT induce vomiting.
Self-protection of the first aider	Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms See section 2 for more information

4.3. Indication of any immediate medical attention and special treatment needed

Note to physicians Keep victim warm and quiet.

Section 5: FIRE FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media

Use extinguishing agent suitable for type of surrounding fire. Dry chemical or CO2. Water spray, fog or regular foam. Move containers from fire area if you can do it without risk. Damaged cylinders should be handled only by specialists.

Unsuitable extinguishing media

No information available

5.2. Special hazards arising from the substance or mixture

Some may burn but none ignite readily. Ruptured cylinders may rocket.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit. Use personal protective equipment as required.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions

Do not touch or walk through spilled material. Stop leak if you can do it without risk.

Ventilate the area.

For emergency responders

Use personal protection recommended in Section 8.

6.2. Environmental precautions

Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material. Prevent entry into waterways, sewers, basements or confined areas.

6.3. Methods and material for containment and cleaning up

Methods for containment

If possible, turn leaking containers so that gas escapes rather than liquid. Allow substance to evaporate.

Methods for cleaning up

Do not direct water at spill or source of leak.

6.4. Reference to other sections

See section 8 for more information. See section 13 for more information.

Section 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Advice on safe handling

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Contents under pressure. Do not puncture or incinerate cans. Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required. Do not stick pin or any other sharp object into opening on top of can.

General Hygiene Considerations

Do not eat, drink or smoke when using this product. Take off all contaminated clothing and wash it before reuse. Wash hands and face thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions

Store locked up. Do not expose to temperatures exceeding 50 °C/122 °F.

Incompatible materials

Nitrates, Fluorine, Chlorine, Strong oxidizing agents

7.3. Specific end use(s)

Specific use(s)

Automotive Care Product.

Risk Management Methods (RMM)

The information required is contained in this Safety Data Sheet.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Chemical Name	European Union	United Kingdom	France	Spain	Germany	
PROPANE 74-98-6	-	-	-	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m ³	
ASPHALT (PETROLEUM) 8052-42-4	-	TWA: 5 mg/m ³ STEL: 10 mg/m ³	-	TWA: 0.5 mg/m ³	-	
TOLUENE 108-88-3	TWA: 50 ppm TWA: 192 mg/m ³ *	TWA: 50 ppm TWA: 191 mg/m ³ STEL: 100 ppm STEL: 384 mg/m ³ Sk*	TWA: 20 ppm TWA: 76.8 mg/m ³ TWA: 1000 mg/m ³ STEL: 100 ppm STEL: 384 mg/m ³ STEL: 1500 mg/m ³ *	TWA: 50 ppm TWA: 192 mg/m ³ STEL: 100 ppm STEL: 384 mg/m ³ via dérmica*	TWA: 50 ppm TWA: 190 mg/m ³ H*	
TALC 14807-96-6	-	TWA: 1 mg/m ³ STEL: 3 mg/m ³	-	TWA: 2 mg/m ³	-	
KAOLIN 1332-58-7	-	TWA: 2 mg/m ³ STEL: 6 mg/m ³	TWA: 10 mg/m ³	TWA: 2 mg/m ³	-	
BUTANE 106-97-8	-	TWA: 600 ppm TWA: 1450 mg/m ³ STEL: 750 ppm STEL: 1810 mg/m ³	TWA: 800 ppm TWA: 1900 mg/m ³	TWA: 1000 ppm	TWA: 1000 ppm TWA: 2400 mg/m ³	
ACETONE 67-64-1	TWA 500 ppm TWA 1210 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³ STEL: 1500 ppm STEL: 3620 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³ STEL: 1000 ppm STEL: 2420 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³	TWA: 500 ppm TWA: 1200 mg/m ³	
Chemical Name	Italy	Portugal	Netherlands	Finland	Denmark	
PROPANE 74-98-6	-	TWA: 1000 ppm	-	TWA: 800 ppm TWA: 1500 mg/m ³ STEL: 1100 ppm STEL: 2000 mg/m ³	TWA: 1000 ppm TWA: 1800 mg/m ³	
ASPHALT (PETROLEUM) 8052-42-4	-	TWA: 0.5 mg/m ³	-	-	TWA: 1 mg/m ³	
TOLUENE 108-88-3	TWA: 50 ppm TWA: 192 mg/m ³ pelle*	TWA: 50 ppm TWA: 192 mg/m ³ STEL: 100 ppm STEL: 384 mg/m ³ P*	TWA: 150 mg/m ³ STEL: 384 mg/m ³	TWA: 25 ppm TWA: 81 mg/m ³ STEL: 100 ppm STEL: 380 mg/m ³ iho*	TWA: 25 ppm TWA: 94 mg/m ³ H*	
TALC 14807-96-6	-	TWA: 2 mg/m ³	TWA: 0.25 mg/m ³	TWA: 0.5 fiber/cm3 STEL: 2 ppm STEL: 1 ppm	TWA: 0.3 fiber/cm3	
STODDARD SOLVENT 8052-41-3	-	TWA: 100 ppm	-	-	TWA: 25 ppm TWA: 145 mg/m ³	
KAOLIN 1332-58-7	-	TWA: 2 mg/m ³	-	TWA: 2 mg/m ³	TWA: 2 mg/m ³	
BUTANE 106-97-8	-	TWA: 1000 ppm	-	TWA: 800 ppm TWA: 1900 mg/m ³ STEL: 1000 ppm STEL: 2400 mg/m ³	TWA: 500 ppm TWA: 1200 mg/m ³	
ACETONE 67-64-1	TWA: 500 ppm TWA: 1210 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³ STEL: 750 ppm	TWA: 1210 mg/m ³ STEL: 2420 mg/m ³	TWA: 500 ppm TWA: 1200 mg/m ³ STEL: 630 ppm STEL: 1500 mg/m ³	TWA: 250 ppm TWA: 600 mg/m ³	
Chemical Name	Austria	Switzerland	Poland	Norway	Ireland	Slovenia
PROPANE 74-98-6	TWA: 1000 ppm TWA: 1800 mg/m ³ STEL 2000 ppm STEL 3600 mg/m ³	TWA: 1000 ppm TWA: 1800 mg/m ³ STEL: 4000 ppm STEL: 7200 mg/m ³	TWA: 1800 mg/m ³	TWA: 500 ppm TWA: 900 mg/m ³ TWA: 40 ppm TWA: 275 mg/m ³ STEL: 625 ppm STEL: 1125 mg/m ³ STEL: 60 ppm STEL: 343.75 mg/m ³	STEL: 3000 ppm	TWA: 1000 ppm TWA: 1800 mg/m ³ STEL: STEL ppm STEL: STEL mg/m ³
ASPHALT (PETROLEUM)	-	TWA: 10 mg/m ³	STEL: 10 mg/m ³	TWA: 5 mg/m ³	TWA: 0.5 mg/m ³	

8052-42-4		H*	TWA: 5 mg/m ³	STEL: 10 mg/m ³	STEL: 10 mg/m ³	
TOLUENE 108-88-3	TWA: 50 ppm TWA: 190 mg/m ³ STEL 100 ppm STEL 380 mg/m ³ H*	TWA: 50 ppm TWA: 190 mg/m ³ STEL: 200 ppm STEL: 760 mg/m ³ H*	STEL: 200 mg/m ³ TWA: 100 mg/m ³	TWA: 25 ppm TWA: 94 mg/m ³ STEL: 37.5 ppm STEL: 141 mg/m ³ H*	TWA: 192 mg/m ³ TWA: 50 ppm STEL: 384 mg/m ³ STEL: 100 ppm Sk*	TWA: 50 ppm TWA: 192 mg/m ³ STEL: STEL ppm STEL: STEL mg/m ³ K*
TALC 14807-96-6	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 4 mg/m ³ TWA: 1 mg/m ³	TWA: 6 mg/m ³ TWA: 2 mg/m ³ STEL: 12 mg/m ³ STEL: 4 mg/m ³	TWA: 10 mg/m ³ TWA: 0.8 mg/m ³ STEL: 30 mg/m ³ STEL: 2.4 mg/m ³	
STODDARD SOLVENT 8052-41-3	-	-	STEL: 900 mg/m ³ TWA: 300 mg/m ³	-	TWA: 100 ppm TWA: 573 mg/m ³	
KAOLIN 1332-58-7	-	TWA: 3 mg/m ³	TWA: 10.0 mg/m ³	-	TWA: 2 mg/m ³	
BUTANE 106-97-8	TWA: 800 ppm TWA: 1900 mg/m ³ STEL 1600 ppm STEL 3800 mg/m ³	TWA: 800 ppm TWA: 1900 mg/m ³ STEL: 3200 ppm STEL: 7600 mg/m ³	STEL: 3000 mg/m ³ TWA: 1900 mg/m ³	TWA: 250 ppm TWA: 600 mg/m ³ TWA: 40 ppm TWA: 275 mg/m ³ STEL: 312.5 ppm STEL: 750 mg/m ³ STEL: 60 ppm STEL: 343.75 mg/m ³	TWA: 1000 ppm STEL: 3000 ppm	TWA: 1000 ppm TWA: 2400 mg/m ³ STEL: STEL ppm STEL: STEL mg/m ³
ACETONE 67-64-1	TWA: 500 ppm TWA: 1200 mg/m ³ STEL 2000 ppm STEL 4800 mg/m ³	TWA: 500 ppm TWA: 1200 mg/m ³ STEL: 1000 ppm STEL: 2400 mg/m ³	STEL: 1800 mg/m ³ TWA: 600 mg/m ³	TWA: 125 ppm TWA: 295 mg/m ³ STEL: 156.25 ppm STEL: 368.75 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³ STEL: 1500 ppm STEL: 3630 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³ STEL: STEL mg/m ³ STEL: STEL ppm

Chemical Name	European Union	United Kingdom	France	Spain	Germany
TOLUENE 108-88-3	-	-	-	0.6 0.05 0.08	600 µg/L 75 µg/L 1.5 mg/L
ACETONE 67-64-1	-	-	-	50	80 mg/L
Chemical Name	Italy	Portugal	Netherlands	Finland	Denmark
TOLUENE 108-88-3	-	-	-	500	-
Chemical Name	Austria	Switzerland	Poland	Norway	Ireland
TOLUENE 108-88-3	-	600 2 0.5	-	-	-
ACETONE 67-64-1	-	80	-	-	-

Derived No Effect Level (DNEL) No information available.

Predicted No Effect Concentration (PNEC) No information available.

8.2. Exposure controls

Engineering Controls Use exhaust ventilation to keep airborne concentrations below exposure limits.

Personal protective equipment

- Eye/face protection** Wear safety glasses with side shields (or goggles).
- Skin and body protection** Suitable protective clothing. Gloves made of plastic or rubber.
- Respiratory protection** In case of insufficient ventilation, wear suitable respiratory equipment. Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.

Environmental exposure controls Local authorities should be advised if significant spillages cannot be contained.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state	Flammable Aerosol
Appearance	Black
Odor	Solvent
Odor threshold	No information available

<u>Property</u>	<u>Values</u>
pH	No information available
Melting point / freezing point	No information available
Boiling point / boiling range	249 °C / 480 °F
Flash point	-104 °C / -155 °F
Evaporation rate	No information available
Flammability (solid, gas)	No information available
Flammability Limit in Air	
Upper flammability limit:	8.8%
Lower flammability limit:	1.6%
Vapor pressure	70-80 psig @ 20°C (68°F)
Vapor density	No information available
Relative density	0.906
Water solubility	No information available
Solubility(ies)	No information available
Partition coefficient	No information available
Autoignition temperature	480°C (896°F)
Decomposition temperature	No information available
Kinematic viscosity	No information available
Dynamic viscosity	No information available
Explosive properties	No information available
Oxidizing properties	No information available

Remarks • Method

Gives a flame projection at full valve opening or flashback at any degree of valve opening

9.2. Other information

Softening point	No information available
Molecular weight	No information available
VOC Content (%)	40
Density	No information available
Bulk density	No information available

Section 10: STABILITY AND REACTIVITY

10.1. Reactivity

Not applicable

10.2. Chemical stability

Stable under normal conditions.

Explosion data

Sensitivity to Mechanical Impact	None.
Sensitivity to Static Discharge	None.

10.3. Possibility of hazardous reactions

None under normal processing.

10.4. Conditions to avoid

Heat, flames and sparks.

10.5. Incompatible materials

Nitrates
Fluorine
Chlorine
Strong oxidizing agents

10.6. Hazardous decomposition products

Carbon oxides
Oxides of sulfur
Hydrogen sulfide

Section 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Product Information

Inhalation Causes damage to organs if inhaled.
Eye contact Irritating to eyes. May cause redness and tearing of the eyes.
Skin contact May cause skin irritation and/or dermatitis. Prolonged contact may cause redness and irritation.
Ingestion Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis.

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 5,204.00 mg/kg
ATEmix (dermal) 5,246.90 mg/kg mg/l

Unknown acute toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity.
 53 % of the mixture consists of ingredient(s) of unknown acute oral toxicity.
 53 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity.
 66 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas).
 87 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor).
 87 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist).

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
PROPANE			> 800000 ppm (Rat) 15 min
ASPHALT (PETROLEUM)	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 94.4 mg/m ³ (Rat) 4.5 h
TOLUENE	= 2600 mg/kg (Rat)	= 12000 mg/kg (Rabbit)	= 12.5 mg/L (Rat) 4 h
KAOLIN	> 5000 mg/kg (Rat)	> 5000 mg/kg (Rat)	
ACETONE	= 5800 mg/kg (Rat)	> 15700 mg/kg (Rabbit)	= 50100 mg/m ³ (Rat) 8 h
BUTANE			= 658 g/m ³ (Rat) 4 h

Skin corrosion/irritation No information available.
Serious eye damage/eye irritation No information available.
Sensitization No information available.
Germ cell mutagenicity No information available.
Carcinogenicity No information available.

Chemical Name	European Union
STODDARD SOLVENT	Carc. 1B
BUTANE	Carc. 1A

Reproductive toxicity	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Target Organ Effects	Central nervous system, Central Vascular System (CVS), Eyes, kidney, Liver, Respiratory system, Skin.
Aspiration hazard:	No information available.

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Chemical Name	Algae/aquatic plants	Fish	Crustacea
TOLUENE	12.5: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 433: 96 h Pseudokirchneriella subcapitata mg/L EC50	14.1 - 17.16: 96 h Oncorhynchus mykiss mg/L LC50 static 28.2: 96 h Poecilia reticulata mg/L LC50 semi-static 5.89 - 7.81: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 54: 96 h Oryzias latipes mg/L LC50 static 12.6: 96 h Pimephales promelas mg/L LC50 static 15.22 - 19.05: 96 h Pimephales promelas mg/L LC50 flow-through 11.0 - 15.0: 96 h Lepomis macrochirus mg/L LC50 static 50.87 - 70.34: 96 h Poecilia reticulata mg/L LC50 static 5.8: 96 h Oncorhynchus mykiss mg/L LC50 semi-static	11.5: 48 h Daphnia magna mg/L EC50 5.46 - 9.83: 48 h Daphnia magna mg/L EC50 Static
TALC	-	100: 96 h Brachydanio rerio g/L LC50 semi-static	-
ACETONE	-	8300: 96 h Lepomis macrochirus mg/L LC50 4.74 - 6.33: 96 h Oncorhynchus mykiss mL/L LC50 6210 - 8120: 96 h Pimephales promelas mg/L LC50 static	10294 - 17704: 48 h Daphnia magna mg/L EC50 Static 12600 - 12700: 48 h Daphnia magna mg/L EC50

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

Chemical Name	Partition coefficient
PROPANE	2.3
ASPHALT (PETROLEUM)	6
TOLUENE	2.7
BUTANE	2.89
ACETONE	-0.24

12.4. Mobility in soil

Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

No information available.

12.6. Other adverse effects

No information available

Endocrine Disruptor Information

None known.

Section 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from residues/unused products	Disposal should be in accordance with applicable regional, national and local laws and regulations.
Contaminated packaging	Do not reuse container.
Waste codes / waste designations according to EWC / AVV	No Data Available
Other Information	Waste codes should be assigned by the user based on the application for which the product was used.

Section 14: TRANSPORT INFORMATION

IMDG

14.1 UN/ID No	1950
14.2 Proper shipping name:	Aerosols, Limited Quantity (LQ)
14.3 Hazard Class	2
14.4 Packing Group	None
14.5 Environmental hazard	Not applicable
14.6 Special Provisions	No information available
14.7 EmS-No	F-D, S-U

RID

14.1 UN/ID No	1950
14.2 Proper shipping name:	Aerosols, Limited Quantity (LQ)
14.3 Hazard Class	2.1
14.4 Packing Group	None
14.5 Environmental hazard	Not applicable
14.6 Special Provisions	No information available
14.7 Classification code	5F

ADR

14.1 UN/ID No	1950
14.2 Proper shipping name:	Aerosols, Limited Quantity (LQ)
14.3 Hazard Class	2.1
14.4 Packing Group	None
14.5 Environmental hazard	Not applicable
14.6 Special Provisions	No information available
14.7 Classification code	5F

IATA

14.1 UN/ID No	ID 8000
14.2 Proper shipping name:	Consumer commodity
14.3 Hazard Class	9
14.4 Packing Group	None
14.5 Environmental hazard	Not applicable
14.6 Special Provisions	No information available
14.7 ERG Code	9L

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Chemical Name	French RG number	Title
TOLUENE 108-88-3	RG 4bis, RG 84	-
TALC 14807-96-6	RG 25	-
STODDARD SOLVENT 8052-41-3	RG 84	-
ACETONE 67-64-1	RG 84	-

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Authorizations and/or restrictions on use:

This product does not contain substances subject to authorization (Regulation (EC) No. 1907/2006 (REACH), Annex XIV) This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII)

Chemical Name	Restricted substance per REACH Annex XVII	Substance subject to authorization per REACH Annex XIV
TOLUENE - 108-88-3	48.	
STODDARD SOLVENT - 8052-41-3	28. 29.	
BUTANE - 106-97-8	28. 29.	

Persistent Organic Pollutants

Not applicable

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

International Inventories

TSCA	Complies
DSL/NDL	Complies
EINECS/ELINCS	Not determined
ENCS	Not determined
IECSC	Not determined
KECL	Not determined
PICCS	Not determined
AICS	Not determined

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List
 EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

15.2. Chemical safety assessment

No information available

Section 16: OTHER INFORMATION

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

EUH066 - Repeated exposure may cause skin dryness or cracking
H220 - Extremely flammable gas
H225 - Highly flammable liquid and vapor
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness
H340 - May cause genetic defects
H350 - May cause cancer
H372 - Causes damage to organs through prolonged or repeated exposure
H373 - May cause damage to organs through prolonged or repeated exposure

Legend

SVHC: Substances of Very High Concern for Authorization:

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation

Revision Date 10-Apr-2020

Revision Note Not applicable.

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

Illinois Tool Works Inc. believes the information contained in this data sheet is accurate as of the date compiled. However, Illinois Tool Works Inc. makes no warranty, express or implied, as to the accuracy, reliability or completeness of the information. User is responsible for evaluating whether such information or this product is fit for a particular purpose and suitable for a particular use or application. The information in this data sheet may not be valid if this product is used in combination with other products or in processes for which it was not designed. Illinois Tool Works Inc. disclaims any liability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of this product. Ensure you have the most current version of this data sheet by contacting us or reviewing our web site.

End of Safety Data Sheet