



Toll Free: 87 PERMATEX
(877-376-2839)

10 Columbus Blvd., Hartford,
Connecticut 06106

6875 Parkland Boulevard, Solon
Ohio 44139

Technical Data Sheet

Permatex® Ultra Disc Brake Caliper Lube

AAM Revised 10/17

PRODUCT DESCRIPTION

Permatex® Ultra Disc Brake Caliper Lube is a green, environmentally friendly, non-melting, pure synthetic lubricant. It is formulated to lubricate under the most adverse brake conditions, assuring that critical caliper pins, sleeves, bushings and pistons remain lubricated throughout pad life. Permatex® Ultra Disc Brake Caliper Lube, that is water and corrosion resistant properties, is excellent on rolling and sliding surfaces operating in wet or dry conditions from -40°F to +495°F.

PRODUCT BENEFITS


- Prevents disc brake squealing
- Prevents long bolt and sleeve seizing and galling
- Outperforms ordinary caliper grease and traditional disc brake quiet
- Non-silicone, non-petroleum based formula
- Pure synthetic lubricant, environmentally safe

TYPICAL APPLICATIONS

- Long and short bolts
- Outboard pad backing plate
- Inboard pad backing plate
- Disc brake calipers
- Caliper pins
- Pistons

DIRECTIONS FOR USE

1. Wire brush the caliper housing and anchor plate to remove all dirt and dust.
2. Apply Permatex® Ultra Disc Brake Caliper Lube to all moving caliper hardware, mating surfaces and steel backing plates of the disc brake pads.



3. Any excess grease that squeezes out from the mating surfaces should be removed.

Note: Keep lubricant off pads and rotors.

PROPERTIES OF MATERIAL

	Typical Value
Chemical Type	Synthetic grease
Appearance	Green viscous grease
Specific Gravity	~0.994
Corrosion Preventative Test ASTM D-1743	Pass
Water Washout @ 100 °F, %	
ASTM D-1264	1.7
Pour point, °F, ASTM D-97	-45
Flash Point, ASTM D-92, °F	500
JIS K228 8.10 Standard	Conforms

GENERAL INFORMATION

This product is not recommended for use in pure oxygen and/or oxygen rich systems.

For safe handling information on this product, consult the Material Safety Data Sheet, (MSDS).

ORDERING INFORMATION

Part Number	Container Size
20353	2 oz. tube with nozzle
20356	10g (2-5g pouches)
24110	8 fl oz. brush top bottle
09977	4 g pouch
85188	0.5 oz. tube, carded

STORAGE

Products shall be ideally stored in a cool, dry location in unopened containers at a temperature between 8° and 28°C (46° and 82°F) unless otherwise labeled. Optimal storage is at the lower half of this temperature range. To prevent contamination of unused product, do not return any material to its original container.

NOTE

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. **ITW Permatex, Inc.**

NOT FOR PRODUCT SPECIFICATIONS.
THE TECHNICAL DATA CONTAINED HEREIN ARE INTENDED AS REFERENCE ONLY.
PLEASE CONTACT PERMATEX, INC., TECHNICAL SERVICE DEPARTMENT FOR ASSISTANCE AND RECOMMENDATIONS FOR YOUR SPECIFIC APPLICATION.
PERMATEX, INC., HARTFORD SQUARE NORTH, 10 COLUMBUS BOULEVARD, HARTFORD, CT 06106 PHONE - (1-87PERMATEX)

specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Permatex, Inc. products and disclaims any liability for consequential or incidental damages of any kind, including lost profits. This product may be covered by one or more United States or foreign patents or patent applications.