



Toll Free: 87 PERMATEX  
(877-376-2839)

6875 Parkland Boulevard, Solon  
Ohio 44139

## Technical Data Sheet

# FAST ORANGE® XTREME Pro Grade Hand Cleaner

AAM Revised 02/19

### PRODUCT DESCRIPTION

Fast Orange® Xtreme Professional Grade Hand Cleaner is a premium, fine pumice hand cleaner in lotion form. It is ideal for semi-dried glazes on hands such as gasket sealants. It contains unique odor eliminating additives that **remove** petroleum odors instead of masking them, Microgel® cleaning technology for durable stains, and finely ground pumice for deep scrubbing to remove the most difficult soils. This fast-acting formula won't irritate skin nor deposit a greasy residue, and leaves hands moisturized and refreshed.

### PRODUCT BENEFITS

- Removes grease, grime, inks, soil, paint, gasket cements and adhesives
- Cleans without water
- Utilizes biodegradable surfactants and Microgel® technology for effective cleaning power
- Contains aloe vera, jojoba oil, vitamin E and lanolin to keep hands smooth
- Available in Original Orange and Fresh scents
- Lotion formula is supplied in a no-waste/no-clog self dispensing container
- Leaves hands smooth, not sticky
- Withstands multiple freeze/thaw cycles

### DIRECTIONS FOR USE

1. Rub Fast Orange® Xtreme Professional Grade hand cleaner lotion into hands (do not use water) until dirt and grease are dissolved.
2. Wipe with dry cloth or rinse with water.

### PHYSICAL PROPERTIES

	Typical Value
Chemical Type	Mineral Spirits, Cleaning Agents, Water
Appearance	Off-White viscous lotion
Odor	Orange / Fresh
Specific Gravity	1.004
Flash Point, °F	>200
pH	7.0

### GENERAL INFORMATION

For safe handling information on this product, consult the Safety Data Sheet (SDS) for this product.

### ORDERING INFORMATION

Part Number	Container Size
25616	15.0 fl oz bottle, Orange Scent
25618	1 gal bottle w/ pump, Orange Scent
25414	7.5 fl oz bottle, Fresh Scent
25419	1 gal bottle w/ pump, Fresh Scent

### STORAGE

Products shall be ideally stored in a cool, dry location in unopened containers at a temperature between 46° to 82°F (8° to 28°C) unless otherwise labeled. Optimal storage is at the lower half of this temperature range. To prevent contamination of unused product, do not return any material to its original container.

### NOTE

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. **ITW Permatex, Inc. specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Permatex, Inc. products and disclaims any liability for consequential or incidental damages of any kind, including lost profits.** This product may be covered by one or more United States or foreign patents or patent applications.

NOT FOR PRODUCT SPECIFICATIONS.  
THE TECHNICAL DATA CONTAINED HEREIN ARE INTENDED AS REFERENCE ONLY.  
PLEASE CONTACT PERMATEX, INC., TECHNICAL SERVICE DEPARTMENT FOR ASSISTANCE AND RECOMMENDATIONS FOR YOUR SPECIFIC APPLICATION.  
PERMATEX, INC., 6875 PARKLAND BOULEVARD, SOLON, OH 44139 PHONE - (1-87PERMATEX)