



Toll Free: 87 PERMATEX
(877-376-2839)

6875 Parkland Boulevard, Solon
Ohio 44139

Technical Data Sheet

Permatex® Paint Stripper

AAM Revised 05/19

PRODUCT DESCRIPTION

Permatex® Paint Stripper is a solvent-based stripper specifically designed to quickly remove paint from bumpers and truck bodies.

CAUTION: This product will remove paint. Do not use to remove paint splatter from painted surfaces.

PRODUCT BENEFITS

- Eliminates time consuming scraping and sanding
- Clings to vertical surfaces

TYPICAL APPLICATIONS

Removes paint from:

- Bumpers
- Windows
- Windshields

DIRECTIONS FOR USE

1. Provide adequate ventilation and protect painted surfaces.
2. Shake can thoroughly before use. For best results, aerosol can should be at room temperature before spraying.
3. Hold the can 8 to 10 inches from the surface to be stripped. Press the nozzle and discharge and saturate the product liberally on the area to be removed.
4. Allow 5 to 10 minutes for product to penetrate. Then scrape with a putty knife.
5. May require a second application for baked or catalytically cured paints.

For Cleanup

1. Clean hands with Permatex® brand hand cleaners.

PROPERTIES OF MATERIAL

	Typical Value
Chemical Type	Solvent-based
Appearance	Milky liquid
Odor	Mild
Flash Point	Aerosol, contents under pressure, consult MSDS
NFPA 704 Flammability Rating	4 (Highly flammable)

GENERAL INFORMATION

This product is not recommended for use in pure oxygen and/or oxygen rich systems and should not be selected for use with chlorine or other strong oxidizing materials.

For safe handling information on this product, consult the Material Safety Data Sheet, (MSDS).

ORDERING INFORMATION

Part Number	Container Size
80578	16 oz. aerosol can

STORAGE

Products shall be ideally stored in a cool, dry location in unopened containers at a temperature between 8° and 28°C (46° and 82°F) unless otherwise labeled. Optimal storage is at the lower half of this temperature range.

NOTE

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. **ITW Permatex, Inc. specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Permatex, Inc. products and disclaims any liability for consequential or incidental damages of any kind, including lost profits.** This product may be covered by one or more United States or foreign patents or patent applications.

NOT FOR PRODUCT SPECIFICATIONS.
THE TECHNICAL DATA CONTAINED HEREIN ARE INTENDED AS REFERENCE ONLY.
PLEASE CONTACT PERMATEX, INC., TECHNICAL SERVICE DEPARTMENT FOR ASSISTANCE AND RECOMMENDATIONS FOR YOUR SPECIFIC APPLICATION.
PERMATEX, INC., 6875 PARKLAND BOULEVARD, SOLON, OH 44139 PHONE - (1-877)PERMATEX